
GraphQL-core 3 Documentation

Release 3.2.3

Christoph Zwerschke

Sep 24, 2022

CONTENTS

1	Contents	1
1.1	Introduction	1
1.2	Usage	2
1.3	Differences from GraphQL.js	17
1.4	Reference	19
2	Indices and tables	125
	Python Module Index	127
	Index	129

CONTENTS

1.1 Introduction

GraphQL-core-3 is a Python port of [GraphQL.js](#), the JavaScript reference implementation for [GraphQL](#), a query language for APIs created by Facebook.

GraphQL consists of three parts:

- A type system that you define
- A query language that you use to query the API
- An execution and validation engine

The reference implementation closely follows the [Specification for GraphQL](#) which consists of the following sections:

- Language
- Type System
- Introspection
- Validation
- Execution
- Response

This division into subsections is reflected in the [Sub-Packages](#) of GraphQL-core 3. Each of these sub-packages implements the aspects specified in one of the sections of the specification.

1.1.1 Getting started

You can install GraphQL-core 3 using [pip](#):

```
pip install graphql-core
```

You can also install GraphQL-core 3 with [poetry](#), if you prefer that:

```
poetry install
```

Now you can start using GraphQL-core 3 by importing from the top-level [graphql](#) package. Nearly everything defined in the sub-packages can also be imported directly from the top-level package.

For instance, using the types defined in the [graphql.type](#) package, you can define a GraphQL schema, like this simple one:

```
from graphql import (
    GraphQLSchema, GraphQLObjectType, GraphQLField, GraphQLString)

schema = GraphQLSchema(
    query=GraphQLObjectType(
        name='RootQueryType',
        fields={
            'hello': GraphQLField(
                GraphQLString,
                resolve=lambda obj, info: 'world')
        })
)
```

The `graphql.execution` package implements the mechanism for executing GraphQL queries. The top-level `graphql()` and `graphql_sync()` functions also parse and validate queries using the `graphql.language` and `graphql.validation` modules.

So to validate and execute a query against our simple schema, you can do:

```
from graphql import graphql_sync

query = '{ hello }'

print(graphql_sync(schema, query))
```

This will yield the following output:

```
ExecutionResult(data={'hello': 'world'}, errors=None)
```

1.1.2 Reporting Issues and Contributing

Please visit the [GitHub](#) repository of GraphQL-core 3 if you're interested in the current development or want to report issues or send pull requests.

1.2 Usage

GraphQL-core provides two important capabilities: building a type schema, and serving queries against that type schema.

1.2.1 Building a Type Schema

Using the classes in the `graphql.type` sub-package as building blocks, you can build a complete GraphQL type schema.

Let's take the following schema as an example, which will allow us to query our favorite heroes from the Star Wars trilogy:

```
enum Episode { NEWHOPE, EMPIRE, JEDI }

interface Character {
    id: String!
```

(continues on next page)

(continued from previous page)

```

name: String
friends: [Character]
appearsIn: [Episode]
}

type Human implements Character {
  id: String!
  name: String
  friends: [Character]
  appearsIn: [Episode]
  homePlanet: String
}

type Droid implements Character {
  id: String!
  name: String
  friends: [Character]
  appearsIn: [Episode]
  primaryFunction: String
}

type Query {
  hero(episode: Episode): Character
  human(id: String!): Human
  droid(id: String!): Droid
}

```

We have been using the so called GraphQL schema definition language (SDL) here to describe the schema. While it is also possible to build a schema directly from this notation using GraphQL-core 3, let's first create that schema manually by assembling the types defined here using Python classes, adding resolver functions written in Python for querying the data.

First, we need to import all the building blocks from the `graphql.type` sub-package. Note that you don't need to import from the sub-packages, since nearly everything is also available directly in the top `graphql` package:

```

from graphql import (
    GraphQLArgument, GraphQLObjectType, GraphQLEnumType,
    GraphQLField, GraphQLInterfaceType, GraphQLList, GraphQLNonNull,
    GraphQLObjectType, GraphQLSchema, GraphQLString)

```

Next, we need to build the enum type `Episode`:

```

episode_enum = GraphQLObjectType('Episode', {
    'NEWHOPE': GraphQLEnumValue(4, description='Released in 1977.'),
    'EMPIRE': GraphQLEnumValue(5, description='Released in 1980.'),
    'JEDI': GraphQLEnumValue(6, description='Released in 1983.')
}, description='One of the films in the Star Wars Trilogy')

```

If you don't need the descriptions for the enum values, you can also define the enum type like this using an underlying Python `Enum` type:

```

from enum import Enum

```

(continues on next page)

(continued from previous page)

```
class EpisodeEnum(Enum):
    NEWHOPE = 4
    EMPIRE = 5
    JEDI = 6

episode_enum = GraphQLEnumType(
    'Episode', EpisodeEnum,
    description='One of the films in the Star Wars Trilogy')
```

You can also use a Python dictionary instead of a Python `Enum` type to define the GraphQL enum type:

```
episode_enum = GraphQLEnumType(
    'Episode', {'NEWHOPE': 4, 'EMPIRE': 5, 'JEDI': 6},
    description='One of the films in the Star Wars Trilogy')
```

Our schema also contains a `Character` interface. Here is how we build it:

```
character_interface = GraphQLInterfaceType('Character', lambda: {
    'id': GraphQLField(
        GraphQLNonNull(GraphQLString),
        description='The id of the character.'),
    'name': GraphQLField(
        GraphQLString,
        description='The name of the character.'),
    'friends': GraphQLField(
        GraphQList(character_interface),
        description='The friends of the character,
                    ' or an empty list if they have none.'),
    'appearsIn': GraphQLField(
        GraphQList(episode_enum),
        description='Which movies they appear in.'),
    'secretBackstory': GraphQLField(
        GraphQLString,
        description='All secrets about their past.'),
    resolve_type=get_character_type,
    description='A character in the Star Wars Trilogy'})
```

Note that we did not pass the dictionary of fields to the `GraphQLInterfaceType` directly, but using a lambda function (a so-called “thunk”). This is necessary because the fields are referring back to the character interface that we are just defining. Whenever you have such recursive definitions in GraphQL-core, you need to use thunks. Otherwise, you can pass everything directly.

Characters in the Star Wars trilogy are either humans or droids. So we define a `Human` and a `Droid` type, which both implement the `Character` interface:

```
human_type = GraphQLObjectType('Human', lambda: {
    'id': GraphQLField(
        GraphQLNonNull(GraphQLString),
        description='The id of the human.'),
    'name': GraphQLField(
        GraphQLString,
        description='The name of the human.'),
    'friends': GraphQLField(
```

(continues on next page)

(continued from previous page)

```

GraphQLList(character_interface),
description='The friends of the human,
    ' or an empty list if they have none.',
resolve=get_friends),
'appearsIn': GraphQLField(
    GraphQLList(episode_enum),
    description='Which movies they appear in.'),
'homePlanet': GraphQLField(
    GraphQLString,
    description='The home planet of the human, or null if unknown.'),
'secretBackstory': GraphQLField(
    GraphQLString,
    resolve=get_secret_backstory,
    description='Where are they from'
        ' and how they came to be who they are.'}),
interfaces=[character_interface],
description='A humanoid creature in the Star Wars universe.')

droid_type = GraphQLObjectType('Droid', lambda: {
    'id': GraphQLField(
        GraphQLNonNull(GraphQLString),
        description='The id of the droid.'),
    'name': GraphQLField(
        GraphQLString,
        description='The name of the droid.'),
    'friends': GraphQLField(
        GraphQLList(character_interface),
        description='The friends of the droid,
            ' or an empty list if they have none.',
        resolve=get_friends,
    ),
    'appearsIn': GraphQLField(
        GraphQLList(episode_enum),
        description='Which movies they appear in.'),
    'secretBackstory': GraphQLField(
        GraphQLString,
        resolve=get_secret_backstory,
        description='Construction date and the name of the designer.'),
    'primaryFunction': GraphQLField(
        GraphQLString,
        description='The primary function of the droid.')
},
interfaces=[character_interface],
description='A mechanical creature in the Star Wars universe.')

```

Now that we have defined all used result types, we can construct the `Query` type for our schema:

```

query_type = GraphQLObjectType('Query', lambda: {
    'hero': GraphQLField(character_interface, args={
        'episode': GraphQLArgument(episode_enum, description=(
            'If omitted, returns the hero of the whole saga.'
            ' If provided, returns the hero of that particular episode.'))},

```

(continues on next page)

(continued from previous page)

```

        resolve=get_hero),
'human': GraphQLField(human_type, args={
    'id': GraphQLArgument(
        GraphQLNonNull(GraphQLString), description='id of the human')},
    resolve=get_human),
'droid': GraphQLField(droid_type, args={
    'id': GraphQLArgument(
        GraphQLNonNull(GraphQLString), description='id of the droid')},
    resolve=get_droid)})
```

Using our query type we can define our schema:

```
schema = GraphQLSchema(query_type)
```

Note that you can also pass a mutation type and a subscription type as additional arguments to the *GraphQLSchema*.

1.2.2 Implementing the Resolver Functions

Before we can execute queries against our schema, we also need to define the data (the humans and droids appearing in the Star Wars trilogy) and implement resolver functions that fetch the data (at the beginning of our schema module, because we are referencing them later):

```

luke = dict(
    id='1000', name='Luke Skywalker', homePlanet='Tatooine',
    friends=['1002', '1003', '2000', '2001'], appearsIn=[4, 5, 6])

vader = dict(
    id='1001', name='Darth Vader', homePlanet='Tatooine',
    friends=['1004'], appearsIn=[4, 5, 6])

han = dict(
    id='1002', name='Han Solo', homePlanet=None,
    friends=['1000', '1003', '2001'], appearsIn=[4, 5, 6])

leia = dict(
    id='1003', name='Leia Organa', homePlanet='Alderaan',
    friends=['1000', '1002', '2000', '2001'], appearsIn=[4, 5, 6])

tarkin = dict(
    id='1004', name='Wilhuff Tarkin', homePlanet=None,
    friends=['1001'], appearsIn=[4])

human_data = {
    '1000': luke, '1001': vader, '1002': han, '1003': leia, '1004': tarkin}

threepio = dict(
    id='2000', name='C-3PO', primaryFunction='Protocol',
    friends=['1000', '1002', '1003', '2001'], appearsIn=[4, 5, 6])

artoo = dict(
    id='2001', name='R2-D2', primaryFunction='Astromech',
```

(continues on next page)

(continued from previous page)

```

friends=['1000', '1002', '1003'], appearsIn=[4, 5, 6])

droid_data = {
    '2000': threepio, '2001': artoo}

def get_character_type(character, _info, _type):
    return 'Droid' if character['id'] in droid_data else 'Human'

def get_character(id):
    """Helper function to get a character by ID."""
    return human_data.get(id) or droid_data.get(id)

def get_friends(character, _info):
    """Allows us to query for a character's friends."""
    return map(get_character, character.friends)

def get_hero(root, _info, episode):
    """Allows us to fetch the undisputed hero of the trilogy, R2-D2."""
    if episode == 5:
        return luke # Luke is the hero of Episode V
    return artoo # Artoo is the hero otherwise

def get_human(root, _info, id):
    """Allows us to query for the human with the given id."""
    return human_data.get(id)

def get_droid(root, _info, id):
    """Allows us to query for the droid with the given id."""
    return droid_data.get(id)

def get_secret_backstory(_character, _info):
    """Raise an error when attempting to get the secret backstory."""
    raise RuntimeError('secretBackstory is secret.')

```

Note that the resolver functions get the current object as first argument. For a field on the root Query type this is often not used, but a root object can also be defined when executing the query. As the second argument, they get an object containing execution information, as defined in the `GraphQLResolveInfo` class. This object also has a `context` attribute that can be used to provide every resolver with contextual information like the currently logged in user, or a database session. In our simple example we don't authenticate users and use static data instead of a database, so we don't make use of it here. In addition to these two arguments, resolver functions optionally get the `defined` for the field in the schema, using the same names (the names are not translated from GraphQL naming conventions to Python naming conventions).

Also note that you don't need to provide resolvers for simple attribute access or for fetching items from Python dictionaries.

Finally, note that our data uses the internal values of the `Episode` enum that we have defined above, not the descriptive

enum names that are used externally. For example, NEWHOPE (“A New Hope”) has internally the actual episode number 4 as value.

1.2.3 Executing Queries

Now that we have defined the schema and breathed life into it with our resolver functions, we can execute arbitrary query against the schema.

The `graphql` package provides the `graphql.graphql()` function to execute queries. This is the main feature of GraphQL-core.

Note however that this function is actually a coroutine intended to be used in asynchronous code running in an event loop.

Here is one way to use it:

```
import asyncio
from graphql import graphql

async def query_artoo():
    result = await graphql(schema, """
    {
      droid(id: "2001") {
        name
        primaryFunction
      }
    }
    """)
    print(result)

asyncio.run(query_artoo())
```

In our query, we asked for the droid with the id 2001, which is R2-D2, and its primary function, Astromech. When everything has been implemented correctly as shown above, you should get the expected result:

```
ExecutionResult(
  data={'droid': {'name': 'R2-D2', 'primaryFunction': 'Astromech'}},
  errors=None)
```

The `ExecutionResult` has a `data` attribute with the actual result, and an `errors` attribute with a list of errors if there were any.

If all your resolvers work synchronously, as in our case, you can also use the `graphql.graphql_sync()` function to query the result in ordinary synchronous code:

```
from graphql import graphql_sync

result = graphql_sync(schema, """
query FetchHuman($id: String!) {
  human(id: $id) {
    name
    homePlanet
  }
}
```

(continues on next page)

(continued from previous page)

```
"""", variable_values={'id': '1000'})
print(result)
```

Here we asked for the human with the id 1000, Luke Skywalker, and his home planet, Tatooine. So the output of the code above is:

```
ExecutionResult(
    data={'human': {'name': 'Luke Skywalker', 'homePlanet': 'Tatooine'}},
    errors=None)
```

Let's see what happens when we make a mistake in the query, by querying a non-existing `homeTown` field:

```
result = graphql_sync(schema, """
{
  human(id: "1000") {
    name
    homePlace
  }
}
""")
print(result)
```

You will get the following result as output:

```
ExecutionResult(data=None, errors=[GraphQLError(
    "Cannot query field 'homePlace' on type 'Human'. Did you mean 'homePlanet'?",
    locations=[SourceLocation(line=5, column=9)])])
```

This is very helpful. Not only do we get the exact location of the mistake in the query, but also a suggestion for correcting the bad field name.

GraphQL also allows to request the meta field `__typename`. We can use this to verify that the hero of “The Empire Strikes Back” episode is Luke Skywalker and that he is in fact a human:

```
result = graphql_sync(schema, """
{
  hero(episode: EMPIRE) {
    __typename
    name
  }
}
""")
print(result)
```

This gives the following output:

```
ExecutionResult(
    data={'hero': {'__typename': 'Human', 'name': 'Luke Skywalker'}},
    errors=None)
```

Finally, let's see what happens when we try to access the secret backstory of our hero:

```
result = graphql_sync(schema, """
{
  hero(episode: EMPIRE) {
    name
    secretBackstory
  }
}
""")
print(result)
```

(continues on next page)

(continued from previous page)

```

    hero(episode: EMPIRE) {
      name
      secretBackstory
    }
  """
)
print(result)

```

While we get the name of the hero, the secret backstory fields remains empty, since its resolver function raises an error. However, we get the error that has been raised by the resolver in the `errors` attribute of the result:

```

ExecutionResult(
  data={'hero': {'name': 'Luke Skywalker', 'secretBackstory': None}},
  errors=[GraphQLError('secretBackstory is secret.',,
    locations=[SourceLocation(line=5, column=9)],
    path=['hero', 'secretBackstory'])])

```

1.2.4 Using the Schema Definition Language

Above we defined the GraphQL schema as Python code, using the `GraphQLSchema` class and other classes representing the various GraphQL types.

GraphQL-core 3 also provides a language-agnostic way of defining a GraphQL schema using the GraphQL schema definition language (SDL) which is also part of the GraphQL specification. To do this, we simply feed the SDL as a string to the `build_schema()` function in `graphql.utilities`:

```

from graphql import build_schema

schema = build_schema("""
  enum Episode { NEWHOPE, EMPIRE, JEDI }

  interface Character {
    id: String!
    name: String
    friends: [Character]
    appearsIn: [Episode]
  }

  type Human implements Character {
    id: String!
    name: String
    friends: [Character]
    appearsIn: [Episode]
    homePlanet: String
  }

  type Droid implements Character {
    id: String!
    name: String
    friends: [Character]
  }

```

(continues on next page)

(continued from previous page)

```

    appearsIn: [Episode]
    primaryFunction: String
}

type Query {
  hero(episode: Episode): Character
  human(id: String!): Human
  droid(id: String!): Droid
}
""")
```

The result is a `GraphQLSchema` object just like the one we defined above, except for the resolver functions which cannot be defined in the SDL.

We would need to manually attach these functions to the schema, like so:

```

schema.query_type.fields['hero'].resolve = get_hero
schema.get_type('Character').resolve_type = get_character_type
```

Another problem is that the SDL does not define the server side values of the `Episode` enum type which are returned by the resolver functions and which are different from the names used for the episode.

So we would also need to manually define these values, like so:

```

for name, value in schema.get_type('Episode').values.items():
  value.value = EpisodeEnum[name].value
```

This would allow us to query the schema built from SDL just like the manually assembled schema:

```

from graphql import graphql_sync

result = graphql_sync(schema, """
{
  hero(episode: EMPIRE) {
    name
    appearsIn
  }
}
""")
```

And we would get the expected result:

```

ExecutionResult(
  data={'hero': {'name': 'Luke Skywalker',
                'appearsIn': ['NEWHOPE', 'EMPIRE', 'JEDI']},
  errors=None)
```

1.2.5 Using resolver methods

Above we have attached resolver functions to the schema only. However, it is also possible to define resolver methods on the resolved objects, starting with the `root_value` object that you can pass to the `graphql()` function when executing a query.

In our case, we could create a Root class with three methods as root resolvers, like so:

```
class Root:
    """The root resolvers"""

    def hero(self, info, episode):
        return luke if episode == 5 else artoo

    def human(self, info, id):
        return human_data.get(id)

    def droid(self, info, id):
        return droid_data.get(id)
```

Since we have defined synchronous methods only, we will use the `graphql_sync()` function to execute a query, passing a `Root()` object as the `root_value`:

```
from graphql import graphql_sync

result = graphql_sync(schema, """
{
  droid(id: "2001") {
    name
    primaryFunction
  }
},
Root()
print(result)
```

Even if we haven't attached a resolver to the `hero` field as we did above, this would now still resolve and give the following output:

```
ExecutionResult(
  data={'droid': {'name': 'R2-D2', 'primaryFunction': 'Astromech'}},
  errors=None)
```

Of course you can also define asynchronous methods as resolvers, and execute queries asynchronously with `graphql()`.

In a similar vein, you can also attach resolvers as methods to the resolved objects on deeper levels than the root of the query. In that case, instead of resolving to dictionaries with keys for all the fields, as we did above, you would resolve to objects with attributes for all the fields. For instance, you would define a class `Human` with a method `friends()` for resolving the friends of a human. You can also make use of inheritance in this case. The `Human` class and a `Droid` class could inherit from a `Character` class and use its methods as resolvers for common fields.

1.2.6 Using an Introspection Query

A third way of building a schema is using an introspection query on an existing server. This is what GraphiQL uses to get information about the schema on the remote server. You can create an introspection query using GraphQL-core 3 with the `get_introspection_query()` function:

```
from graphql import get_introspection_query

query = get_introspection_query(descriptions=True)
```

This will also yield the descriptions of the introspected schema fields. You can also create a query that omits the descriptions with:

```
query = get_introspection_query(descriptions=False)
```

In practice you would run this query against a remote server, but we can also run it against the schema we have just built above:

```
from graphql import graphql_sync

introspection_query_result = graphql_sync(schema, query)
```

The `data` attribute of the introspection query result now gives us a dictionary, which constitutes a third way of describing a GraphQL schema:

```
{'__schema': {
    'queryType': {'name': 'Query'},
    'mutationType': None, 'subscriptionType': None,
    'types': [
        {'kind': 'OBJECT', 'name': 'Query', 'description': None,
         'fields': [
             {'name': 'hero', 'description': None,
              'args': [{"name": "episode", "description": ...}],
              ... },
              ... ],
              ... },
              ...
    ]
}}
```

This result contains all the information that is available in the SDL description of the schema, i.e. it does not contain the resolve functions and information on the server-side values of the enum types.

You can convert the introspection result into `GraphQLSchema` with GraphQL-core 3 by using the `build_client_schema()` function:

```
from graphql import build_client_schema

client_schema = build_client_schema(introspection_query_result.data)
```

It is also possible to convert the result to SDL with GraphQL-core 3 by using the `print_schema()` function:

```
from graphql import print_schema

sdl = print_schema(client_schema)
print(sdl)
```

This prints the SDL representation of the schema that we started with.

As you see, it is easy to convert between the three forms of representing a GraphQL schema in GraphQL-core 3 using the `graphql.utilities` module.

1.2.7 Parsing GraphQL Queries and Schema Notation

When executing GraphQL queries, the first step that happens under the hood is parsing the query. But GraphQL-core 3 also exposes the parser for direct usage via the `parse()` function. When you pass this function a GraphQL source code, it will be parsed and returned as a Document, i.e. an abstract syntax tree (AST) of `Node` objects. The root node will be a `DocumentNode`, with child nodes of different kinds corresponding to the GraphQL source. The nodes also carry information on the location in the source code that they correspond to.

Here is an example:

```
from graphql import parse

document = parse("""
    type Query {
        me: User
    }

    type User {
        id: ID
        name: String
    }
""")
```

You can also leave out the information on the location in the source code when creating the AST document:

```
document = parse(..., no_location=True)
```

This will give the same result as manually creating the AST document:

```
from graphql.language.ast import *

document = DocumentNode(definitions=[

    ObjectTypeDefintionNode(
        name=NameNode(value='Query'),
        fields=[

            FieldDefinitionNode(
                name=NameNode(value='me'),
                type=NamedTypeNode(name=NameNode(value='User')),
                arguments=[], directives=[]),
            directives=[], interfaces=[]),

    ObjectTypeDefintionNode(
        name=NameNode(value='User'),
        fields=[

            FieldDefinitionNode(
                name=NameNode(value='id'),
                type=NamedTypeNode(
                    name=NameNode(value='ID')),
                arguments=[], directives=[]),
            FieldDefinitionNode(
                name=NameNode(value='name'))]
```

(continues on next page)

(continued from previous page)

```

    type=NamedTypeNode(
        name=NameNode(value='String')),
        arguments=[], directives=[]),
    ], directives=[], interfaces=[]),
[])
)

```

When parsing with `no_location=False` (the default), the AST nodes will also have a `loc` attribute carrying the information on the source code location corresponding to the AST nodes.

When there is a syntax error in the GraphQL source code, then the `parse()` function will raise a `GraphQLSyntaxError`.

The parser can not only be used to parse GraphQL queries, but also to parse the GraphQL schema definition language. This will result in another way of representing a GraphQL schema, as an AST document.

1.2.8 Extending a Schema

With GraphQL-core 3 you can also extend a given schema using type extensions. For example, we might want to add a `lastName` property to our `Human` data type to retrieve only the last name of the person.

This can be achieved with the `extend_schema()` function as follows:

```

from graphql import extend_schema, parse

schema = extend_schema(schema, parse("""
    extend type Human {
        lastName: String
    }
"""))

```

Note that this function expects the extensions as an AST, which we can get using the `parse()` function. Also note that the `extend_schema()` function does not alter the original schema, but returns a new schema object.

We also need to attach a resolver function to the new field:

```

def get_last_name(human, info):
    return human['name'].rsplit(None, 1)[-1]

schema.get_type('Human').fields['lastName'].resolve = get_last_name

```

Now we can query only the last name of a human:

```

from graphql import graphql_sync

result = graphql_sync(schema, """
{
    human(id: "1000") {
        lastName
        homePlanet
    }
}
""")
print(result)

```

This query will give the following result:

```
ExecutionResult(  
    data={'human': {'lastName': 'Skywalker', 'homePlanet': 'Tatooine'}},  
    errors=None)
```

1.2.9 Validating GraphQL Queries

When executing GraphQL queries, the second step that happens under the hood after parsing the source code is a validation against the given schema using the rules of the GraphQL specification. You can also run the validation step manually by calling the `validate()` function, passing the schema and the AST document:

```
from graphql import parse, validate  
  
errors = validate(schema, parse("""  
  {  
    human(id: NEWHOPE) {  
      name  
      homePlace  
      friends  
    }  
  }  
"""))
```

As a result, you will get a complete list of all errors that the validators has found. In this case, we will get the following three validation errors:

```
[GraphQLError(  
    'String cannot represent a non string value: NEWHOPE',  
    locations=[SourceLocation(line=3, column=17)]),  
GraphQLError(  
    "Cannot query field 'homePlace' on type 'Human'.  
     Did you mean 'homePlanet'?",  
    locations=[SourceLocation(line=5, column=9)]),  
GraphQLError(  
    "Field 'friends' of type '[Character]' must have a selection of subfields.  
     Did you mean 'friends { ... }'?",  
    locations=[SourceLocation(line=6, column=9)])]
```

These rules are available in the `specified_rules` list and implemented in the `graphql.validation.rules` sub-package. Instead of the default rules, you can also use a subset or create custom rules. The rules are based on the `ValidationRule` class which is based on the `Visitor` class which provides a way of walking through an AST document using the visitor pattern.

1.2.10 Subscriptions

Sometimes you need to not only query data from a server, but you also want to push data from the server to the client. GraphQL-core 3 has you also covered here, because it implements the “Subscribe” algorithm described in the GraphQL spec. To execute a GraphQL subscription, you must use the `subscribe()` method from the `graphql.execution` package. Instead of a single `ExecutionResult`, this function returns an asynchronous iterator yielding a stream of those, unless there was an immediate error. Of course you will then also need to maintain a persistent channel to the client (often realized via WebSockets) to push these results back.

1.2.11 Other Usages

GraphQL-core 3 provides many more low-level functions that can be used to work with GraphQL schemas and queries. We encourage you to explore the contents of the various *Sub-Packages*, particularly `graphql.utilities`, and to look into the source code and tests of `GraphQL-core 3` in order to find all the functionality that is provided and understand it in detail.

1.3 Differences from GraphQL.js

The goal of GraphQL-core 3 is to be a faithful replication of `GraphQL.js`, the JavaScript reference implementation for GraphQL, in Python 3, and to keep it aligned and up to date with the ongoing development of `GraphQL.js`. Therefore, we strive to be as compatible as possible to the original JavaScript library, sometimes at the cost of being less Pythonic than other libraries written particularly for Python. We also avoid incorporating additional features that do not exist in the JavaScript library, in order to keep the task of maintaining the Python code and keeping it in line with the JavaScript code manageable. The preferred way of getting new features into GraphQL-core is to propose and discuss them on the `GraphQL.js` issue tracker first, try to get them included into `GraphQL.js`, and from there ported to GraphQL-core.

Having said this, in a few places we allowed the API to be a bit more Pythonic than the direct equivalent would have been. We also added a few features that do not exist in the JavaScript library, mostly to support existing higher level libraries such as `Graphene` and the different naming conventions in Python. The most notable differences are the following:

1.3.1 Direct attribute access in GraphQL types

You can access

- the **fields** of `GraphQLObjectType`, `GraphQLInterfaceType` and `GraphQLInputObjectType`,
- the **interfaces** of `GraphQLObjectType`,
- the **types** of `GraphQLUnionType`,
- the **values** of `GraphQLEnumType` and
- the **query**, **mutation**, **subscription** and **type_map** of `GraphQLSchema`

directly as attributes, instead of using getters.

For example, to get the fields of a `GraphQLObjectType` `obj`, you write `obj.fields` instead of `obj.getFields()`.

1.3.2 Arguments, fields and values are dictionaries

- The **arguments** of GraphQLDirectives and GraphQLFields,
- the **fields** of GraphQLObjectTypes, GraphQLInterfaceTypes and GraphQLInputObjectTypes, and
- the **values** of GraphQLEnumTypes

are always Python dictionaries in GraphQL-core, while they are returned as Arrays in GraphQL.js. Also, the values of these dictionaries do not have name attributes, since the names are already used as the keys of these dictionaries.

1.3.3 Shorthand notation for creating GraphQL types

The following shorthand notations are possible:

- Where you need to pass a GraphQLArgumentMap, i.e. a dictionary with names as keys and GraphQLArguments as values, you can also pass GraphQLInputTypes as values. The GraphQLInputTypes are then automatically wrapped into GraphQLArguments.
- Where you need to pass a GraphQLFieldMap, i.e. a dictionary with names as keys and GraphQLFields as values, you can also pass GraphQLOutputTypes as values. The GraphQLOutputTypes are then automatically wrapped into GraphQLFields.
- Where you need to pass a GraphQLInputFieldMap, i.e. a dictionary with names as keys and GraphQLInputFields as values, you can also pass GraphQLInputTypes as values. The GraphQLInputTypes are then automatically wrapped into GraphQLInputFields.
- Where you need to pass a GraphQLEnumValueMap, i.e. a dictionary with names as keys and GraphQLEnumValues as values, you can pass any other Python objects as values. These will be automatically wrapped into GraphQLEnumValues. You can also pass a Python Enum type as GraphQLEnumValueMap.

1.3.4 Custom output names of arguments and input fields

You can pass a custom `out_name` argument to `GraphQLArgument` and `GraphQLInputField` that allows using JavaScript naming conventions (camelCase) on ingress and Python naming conventions (snake_case) on egress. This feature is used by Graphene.

1.3.5 Custom output types of input object types

You can also pass a custom `out_type` argument to `GraphQLInputObjectType` that allows conversion to any Python type on egress instead of conversion to a dictionary, which is the default. This is used to support the container feature of Graphene InputObjectTypes.

1.3.6 Custom middleware

The `execute()` function takes an additional `middleware` argument which must be a sequence of middleware functions or a `MiddlewareManager` object. This feature is used by Graphene to affect the evaluation of fields using custom middleware. There has been a [request](#) to add this to GraphQL.js as well, but so far this feature only exists in GraphQL-core.

1.3.7 Custom execution context

The `execute()` function takes an additional `execution_context_class` argument which allows specifying a custom execution context class instead of the default `ExecutionContext` used by GraphQL-core.

1.3.8 Registering special types for descriptions

Normally, descriptions for GraphQL types must be strings. However, sometimes you may want to use other kinds of objects which are not strings, but are only resolved to strings at runtime. This is possible if you register the classes of such objects with `pyutils.register_description()`.

If you notice any other important differences, please let us know so that they can be either removed or listed here.

1.4 Reference

GraphQL-core

The primary `graphql` package includes everything you need to define a GraphQL schema and fulfill GraphQL requests.

GraphQL-core provides a reference implementation for the GraphQL specification but is also a useful utility for operating on GraphQL files and building sophisticated tools.

This top-level package exports a general purpose function for fulfilling all steps of the GraphQL specification in a single operation, but also includes utilities for every part of the GraphQL specification:

- Parsing the GraphQL language.
- Building a GraphQL type schema.
- Validating a GraphQL request against a type schema.
- Executing a GraphQL request against a type schema.

This also includes utility functions for operating on GraphQL types and GraphQL documents to facilitate building tools.

You may also import from each sub-package directly. For example, the following two import statements are equivalent:

```
from graphql import parse
from graphql.language import parse
```

The sub-packages of GraphQL-core 3 are:

- `graphql.language`: Parse and operate on the GraphQL language.
- `graphql.type`: Define GraphQL types and schema.
- `graphql.validation`: The Validation phase of fulfilling a GraphQL result.
- `graphql.execution`: The Execution phase of fulfilling a GraphQL request.
- `graphql.error`: Creating and formatting GraphQL errors.
- `graphql.utilities`: Common useful computations upon the GraphQL language and type objects.

1.4.1 Top-Level Functions

```
async graphql.graphql(schema: graphql.type.schema.GraphQLSchema, source: Union[str,  
    graphql.language.source.Source], root_value: Any = None, context_value: Any = None,  
    variable_values: Optional[Dict[str, Any]] = None, operation_name: Optional[str] =  
    None, field_resolver: Optional[Callable[[...], Any]] = None, type_resolver:  
    Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo,  
        GraphQLAbstractType], Optional[Union[Awaitable[Optional[str]], str]]]] = None,  
    middleware: Optional[Union[Tuple, List,  
        graphql.execution.middleware.MiddlewareManager]] = None, execution_context_class:  
    Optional[Type[graphql.execution.execute.ExecutionContext]] = None, is_awaitable:  
    Optional[Callable[[Any], bool]] = None) →  
    graphql.execution.execute.ExecutionResult
```

Execute a GraphQL operation asynchronously.

This is the primary entry point function for fulfilling GraphQL operations by parsing, validating, and executing a GraphQL document along side a GraphQL schema.

More sophisticated GraphQL servers, such as those which persist queries, may wish to separate the validation and execution phases to a static time tooling step, and a server runtime step.

Accepts the following arguments:

Parameters

- **schema** – The GraphQL type system to use when validating and executing a query.
- **source** – A GraphQL language formatted string representing the requested operation.
- **root_value** – The value provided as the first argument to resolver functions on the top level type (e.g. the query object type).
- **context_value** – The context value is provided as an attribute of the second argument (the resolve info) to resolver functions. It is used to pass shared information useful at any point during query execution, for example the currently logged in user and connections to databases or other services.
- **variable_values** – A mapping of variable name to runtime value to use for all variables defined in the request string.
- **operation_name** – The name of the operation to use if request string contains multiple possible operations. Can be omitted if request string contains only one operation.
- **field_resolver** – A resolver function to use when one is not provided by the schema. If not provided, the default field resolver is used (which looks for a value or method on the source value with the field's name).
- **type_resolver** – A type resolver function to use when none is provided by the schema. If not provided, the default type resolver is used (which looks for a __typename field or alternatively calls the `is_type_of()` method).
- **middleware** – The middleware to wrap the resolvers with
- **execution_context_class** – The execution context class to use to build the context
- **is_awaitable** – The predicate to be used for checking whether values are awaitable

```
graphql.graphql_sync(schema: graphql.type.schema.GraphQLSchema, source: Union[str,
    graphql.language.source.Source], root_value: Any = None, context_value: Any = None,
    variable_values: Optional[Dict[str, Any]] = None, operation_name: Optional[str] =
    None, field_resolver: Optional[Callable[..., Any]] = None, type_resolver:
    Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
        GraphQLAbstractType], Optional[Union[Awaitable[Optional[str]], str]]]] = None,
    middleware: Optional[Union[Tuple, List,
        graphql.execution.middleware.MiddlewareManager]] = None, execution_context_class:
    Optional[Type[graphql.execution.execute.ExecutionContext]] = None, check_sync: bool =
    False) → graphql.execution.execute.ExecutionResult
```

Execute a GraphQL operation synchronously.

The `graphql_sync` function also fulfills GraphQL operations by parsing, validating, and executing a GraphQL document along side a GraphQL schema. However, it guarantees to complete synchronously (or throw an error) assuming that all field resolvers are also synchronous.

Set `check_sync` to True to still run checks that no awaitable values are returned.

1.4.2 Sub-Packages

Error

GraphQL Errors

The `graphql.error` package is responsible for creating and formatting GraphQL errors.

```
class graphql.error.GraphQLError(message: str, nodes: Optional[Union[Collection[Node], Node]] = None,
    source: Optional[Source] = None, positions: Optional[Collection[int]] = None, path:
    Optional[Collection[Union[str, int]]] = None, original_error: Optional[Exception] = None, extensions:
    Optional[Dict[str, Any]] = None)
```

Bases: `Exception`

GraphQL Error

A `GraphQLError` describes an Error found during the parse, validate, or execute phases of performing a GraphQL operation. In addition to a message, it also includes information about the locations in a GraphQL document and/or execution result that correspond to the Error.

```
__init__(message: str, nodes: Optional[Union[Collection[Node], Node]] = None, source:
    Optional[Source] = None, positions: Optional[Collection[int]] = None, path:
    Optional[Collection[Union[str, int]]] = None, original_error: Optional[Exception] = None,
    extensions: Optional[Dict[str, Any]] = None) → None
```

args

`extensions: Optional[Dict[str, Any]]`

Extension fields to add to the formatted error

`property formatted: graphql.error.graphql_error.GraphQLFormattedMessage`

Get error formatted according to the specification.

Given a `GraphQLError`, format it according to the rules described by the “Response Format, Errors” section of the GraphQL Specification.

locations: `Optional[List[SourceLocation]]`

Source locations

A list of (line, column) locations within the source GraphQL document which correspond to this error.

Errors during validation often contain multiple locations, for example to point out two things with the same name. Errors during execution include a single location, the field which produced the error.

message: `str`

A message describing the Error for debugging purposes

nodes: `Optional[List[Node]]`

A list of GraphQL AST Nodes corresponding to this error

original_error: `Optional[Exception]`

The original error thrown from a field resolver during execution

path: `Optional[List[Union[str, int]]]`

A list of field names and array indexes describing the JSON-path into the execution response which corresponds to this error.

Only included for errors during execution.

positions: `Optional[Collection[int]]`

Error positions

A list of character offsets within the source GraphQL document which correspond to this error.

source: `Optional[Source]`

The source GraphQL document for the first location of this error

Note that if this Error represents more than one node, the source may not represent nodes after the first node.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

class `graphql.error.GraphQLSyntaxError(source: Source, position: int, description: str)`

Bases: `graphql.error.graphql_error.GraphQLError`

A GraphQLError representing a syntax error.

__init__(source: Source, position: int, description: str) → None

args

extensions: `Optional[Dict[str, Any]]`

Extension fields to add to the formatted error

property formated: `graphql.error.graphql_error.GraphQLFormattedError`

Get error formatted according to the specification.

Given a GraphQLError, format it according to the rules described by the “Response Format, Errors” section of the GraphQL Specification.

locations: `Optional[List[SourceLocation]]`

Source locations

A list of (line, column) locations within the source GraphQL document which correspond to this error.

Errors during validation often contain multiple locations, for example to point out two things with the same name. Errors during execution include a single location, the field which produced the error.

```

message: str
    A message describing the Error for debugging purposes

nodes: Optional[List[Node]]
    A list of GraphQL AST Nodes corresponding to this error

original_error: Optional[Exception]
    The original error thrown from a field resolver during execution

path: Optional[List[Union[str, int]]]
    A list of field names and array indexes describing the JSON-path into the execution response which corresponds to this error.

    Only included for errors during execution.

positions: Optional[Collection[int]]
    Error positions

    A list of character offsets within the source GraphQL document which correspond to this error.

source: Optional[Source]
    The source GraphQL document for the first location of this error

    Note that if this Error represents more than one node, the source may not represent nodes after the first node.

with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

class graphql.error.GraphQLFormattedError
    Bases: TypedDict

    Formatted GraphQL error

extensions: Dict[str, Any]

locations: List[FormattedSourceLocation]

message: str

path: List[Union[str, int]]

graphql.error.located_error(original_error: Exception, nodes: Optional[Union[None, Collection[Node]]] = None, path: Optional[Collection[Union[str, int]]] = None) → graphql.error.graphql_error.GraphQLError
    Located GraphQL Error

    Given an arbitrary Exception, presumably thrown while attempting to execute a GraphQL operation, produce a new GraphQLError aware of the location in the document responsible for the original Exception.

```

Execution

GraphQL Execution

The `graphql.execution` package is responsible for the execution phase of fulfilling a GraphQL request.

```
graphql.execution.execute(schema: graphql.type.schema.GraphQLSchema, document:
    graphql.language.ast.DocumentNode, root_value: Optional[Any] = None,
    context_value: Optional[Any] = None, variable_values: Optional[Dict[str, Any]] =
    None, operation_name: Optional[str] = None, field_resolver:
    Optional[Callable[..., Any]] = None, type_resolver: Optional[Callable[[Any,
        graphql.type.definition.GraphQLResolveInfo,
        Union[graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType]],
        Optional[Union[Awaitable[Optional[str]], str]]]] = None,
    subscribe_field_resolver: Optional[Callable[..., Any]] = None, middleware:
    Optional[Union[Tuple, List, graphql.execution.middleware.MiddlewareManager]] =
    None, execution_context_class:
    Optional[Type[graphql.execution.execute.ExecutionContext]] = None,
    is_awaitable: Optional[Callable[[Any], bool]] = None) →
    Union[Awaitable[graphql.execution.execute.ExecutionResult],
    graphql.execution.execute.ExecutionResult]
```

Execute a GraphQL operation.

Implements the “Executing requests” section of the GraphQL specification.

Returns an `ExecutionResult` (if all encountered resolvers are synchronous), or a coroutine object eventually yielding an `ExecutionResult`.

If the arguments to this function do not result in a legal execution context, a `GraphQLError` will be thrown immediately explaining the invalid input.

```
graphql.execution.execute_sync(schema: graphql.type.schema.GraphQLSchema, document:
    graphql.language.ast.DocumentNode, root_value: Optional[Any] = None,
    context_value: Optional[Any] = None, variable_values: Optional[Dict[str,
        Any]] = None, operation_name: Optional[str] = None, field_resolver:
    Optional[Callable[..., Any]] = None, type_resolver:
    Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
        Union[graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType]],
        Optional[Union[Awaitable[Optional[str]], str]]]] = None, middleware:
    Optional[Union[Tuple, List,
        graphql.execution.middleware.MiddlewareManager]] = None,
    execution_context_class:
    Optional[Type[graphql.execution.execute.ExecutionContext]] = None,
    check_sync: bool = False) → graphql.execution.execute.ExecutionResult
```

Execute a GraphQL operation synchronously.

Also implements the “Executing requests” section of the GraphQL specification.

However, it guarantees to complete synchronously (or throw an error) assuming that all field resolvers are also synchronous.

Set `check_sync` to `True` to still run checks that no awaitable values are returned.

```
graphql.execution.default_field_resolver(source: Any, info:
    graphql.type.definition.GraphQLResolveInfo, **args: Any) →
    Any
```

Default field resolver.

If a resolve function is not given, then a default resolve behavior is used which takes the property of the source object of the same name as the field and returns it as the result, or if it's a function, returns the result of calling that function while passing along args and context.

For dictionaries, the field names are used as keys, for all other objects they are used as attribute names.

```
graphql.execution.default_type_resolver(value: Any, info: graphql.type.definition.GraphQLResolveInfo,
                                         abstract_type:
                                         Union[graphql.type.definition.GraphQLInterfaceType,
                                               graphql.type.definition.GraphQLUnionType]) →
                                         Optional[Union[Awaitable[Optional[str]], str]]
```

Default type resolver function.

If a resolve_type function is not given, then a default resolve behavior is used which attempts two strategies:

First, See if the provided value has a __typename field defined, if so, use that value as name of the resolved type.

Otherwise, test each possible type for the abstract type by calling `is_type_of()` for the object being coerced, returning the first type that matches.

```
class graphql.execution.ExecutionContext(schema: graphql.type.schema.GraphQLSchema, fragments:
                                         Dict[str, graphql.language.ast.FragmentDefinitionNode],
                                         root_value: Any, context_value: Any, operation:
                                         graphql.language.ast.OperationDefinitionNode,
                                         variable_values: Dict[str, Any], field_resolver: Callable[..., Any],
                                         type_resolver: Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
                                                               Union[graphql.type.definition.GraphQLInterfaceType,
                                                               graphql.type.definition.GraphQLUnionType]], Optional[Union[Awaitable[Optional[str]], str]]],
                                         subscribe_field_resolver: Callable[..., Any], errors: List[graphql.error.graphql_error.GraphQLError],
                                         middleware_manager: Optional[graphql.execution.middleware.MiddlewareManager],
                                         is_awaitable: Optional[Callable[[Any], bool]])
```

Bases: `object`

Data that must be available at all points during query execution.

Namely, schema of the type system that is currently executing, and the fragments defined in the query document.

```
__init__(schema: graphql.type.schema.GraphQLSchema, fragments: Dict[str,
                                         graphql.language.ast.FragmentDefinitionNode], root_value: Any, context_value: Any, operation:
                                         graphql.language.ast.OperationDefinitionNode, variable_values: Dict[str, Any], field_resolver:
                                         Callable[..., Any], type_resolver: Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
                                                               Union[graphql.type.definition.GraphQLInterfaceType,
                                                               graphql.type.definition.GraphQLUnionType]], Optional[Union[Awaitable[Optional[str]], str]]],
                                         subscribe_field_resolver: Callable[..., Any], errors: List[graphql.error.graphql_error.GraphQLError],
                                         middleware_manager: Optional[graphql.execution.middleware.MiddlewareManager], is_awaitable:
                                         Optional[Callable[[Any], bool]]) → None
```

```
classmethod build(schema: graphql.type.schema.GraphQLSchema, document:  
    graphql.language.ast.DocumentNode, root_value: Optional[Any] = None,  
    context_value: Optional[Any] = None, raw_variable_values: Optional[Dict[str, Any]]  
    = None, operation_name: Optional[str] = None, field_resolver:  
    Optional[Callable[..., Any]] = None, type_resolver: Optional[Callable[[Any,  
        graphql.type.definition.GraphQLResolveInfo,  
        Union[graphql.type.definition.GraphQLInterfaceType,  
        graphql.type.definition.GraphQLUnionType]],  
        Optional[Union[Awaitable[Optional[str]], str]]]] = None, subscribe_field_resolver:  
    Optional[Callable[..., Any]] = None, middleware: Optional[Union[Tuple, List,  
        graphql.execution.middleware.MiddlewareManager]] = None, is_awaitable:  
    Optional[Callable[[Any], bool]] = None) →  
    Union[List[graphql.error.graphql_error.GraphQLError],  
        graphql.execution.execute.ExecutionContext]
```

Build an execution context

Constructs a ExecutionContext object from the arguments passed to execute, which we will pass throughout the other execution methods.

Throws a GraphQLError if a valid execution context cannot be created.

For internal use only.

```
build_resolve_info(field_def: graphql.type.definition.GraphQLField, field_nodes:  
    List[graphql.language.ast.FieldNode], parent_type:  
    graphql.type.definition.GraphQLObjectType, path: graphql.pyutils.path.Path) →  
    graphql.type.definition.GraphQLResolveInfo
```

Build the GraphQLResolveInfo object.

For internal use only.

```
static build_response(data: Optional[Dict[str, Any]], errors:  
    List[graphql.error.graphql_error.GraphQLError]) →  
    graphql.execution.execute.ExecutionResult
```

Build response.

Given a completed execution context and data, build the (data, errors) response defined by the “Response” section of the GraphQL spec.

```
collect_subfields(return_type: graphql.type.definition.GraphQLObjectType, field_nodes:  
    List[graphql.language.ast.FieldNode]) → Dict[str,  
    List[graphql.language.ast.FieldNode]]
```

Collect subfields.

A cached collection of relevant subfields with regard to the return type is kept in the execution context as `_subfields_cache`. This ensures the subfields are not repeatedly calculated, which saves overhead when resolving lists of values.

```
complete_abstract_value(return_type: Union[graphql.type.definition.GraphQLInterfaceType,  
    graphql.type.definition.GraphQLUnionType], field_nodes:  
    List[graphql.language.ast.FieldNode], info:  
    graphql.type.definition.GraphQLResolveInfo, path: graphql.pyutils.path.Path,  
    result: Any) → Union[Awaitable[Any], Any]
```

Complete an abstract value.

Complete a value of an abstract type by determining the runtime object type of that value, then complete the value for that type.

```
static complete_leaf_value(return_type: Union[graphql.type.definition.GraphQLScalarType, graphql.type.definition.GraphQLEnumType], result: Any) → Any
```

Complete a leaf value.

Complete a Scalar or Enum by serializing to a valid value, returning null if serialization is not possible.

```
complete_list_value(return_type:
```

```
    graphql.type.definition.GraphQLList[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLObjectType,
    graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLWrappingType]], field_nodes:
    List[graphql.language.ast.FieldNode], info:
    graphql.type.definition.GraphQLResolveInfo, path: graphql.pyutils.path.Path, result:
    Union[AsyncIterable[Any], Iterable[Any]]) → Union[Awaitable[List[Any]],
    List[Any]]
```

Complete a list value.

Complete a list value by completing each item in the list with the inner type.

```
complete_object_value(return_type: graphql.type.definition.GraphQLObjectType, field_nodes:
```

```
    List[graphql.language.ast.FieldNode], info:
    graphql.type.definition.GraphQLResolveInfo, path: graphql.pyutils.path.Path,
    result: Any) → Union[Awaitable[Dict[str, Any]], Dict[str, Any]]
```

Complete an Object value by executing all sub-selections.

```
complete_value(return_type: Union[graphql.type.definition.GraphQLScalarType,
```

```
    graphql.type.definition.GraphQLObjectType,
    graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLWrappingType], field_nodes:
    List[graphql.language.ast.FieldNode], info: graphql.type.definition.GraphQLResolveInfo,
    path: graphql.pyutils.path.Path, result: Any) → Union[Awaitable[Any], Any]
```

Complete a value.

Implements the instructions for completeValue as defined in the “Value completion” section of the spec.

If the field type is Non-Null, then this recursively completes the value for the inner type. It throws a field error if that completion returns null, as per the “Nullability” section of the spec.

If the field type is a List, then this recursively completes the value for the inner type on each item in the list.

If the field type is a Scalar or Enum, ensures the completed value is a legal value of the type by calling the `serialize` method of GraphQL type definition.

If the field is an abstract type, determine the runtime type of the value and then complete based on that type.

Otherwise, the field type expects a sub-selection set, and will complete the value by evaluating all sub-selections.

```
context_value: Any
```

```
ensure_valid_runtime_type(runtime_type_name: Any, return_type:
```

```
    Union[graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType], field_nodes:
    List[graphql.language.ast.FieldNode], info:
    graphql.type.definition.GraphQLResolveInfo, result: Any) →
    graphql.type.definition.GraphQLObjectType
```

```
errors: List[graphql.error.graphql_error.GraphQLError]

execute_field(parent_type: graphql.type.definition.GraphQLObjectType, source: Any, field_nodes:
    List[graphql.language.ast.FieldNode], path: graphql.pyutils.path.Path) →
    Union[Awaitable[Any], Any]

Resolve the field on the given source object.

Implements the “Executing fields” section of the spec.

In particular, this method figures out the value that the field returns by calling its resolve function, then calls complete_value to await coroutine objects, serialize scalars, or execute the sub-selection-set for objects.

execute_fields(parent_type: graphql.type.definition.GraphQLObjectType, source_value: Any, path:
    Optional[graphql.pyutils.path.Path], fields: Dict[str,
    List[graphql.language.ast.FieldNode]]) → Union[Awaitable[Dict[str, Any]], Dict[str,
    Any]]

Execute the given fields concurrently.

Implements the “Executing selection sets” section of the spec for fields that may be executed in parallel.

execute_fields_serially(parent_type: graphql.type.definition.GraphQLObjectType, source_value: Any,
    path: Optional[graphql.pyutils.path.Path], fields: Dict[str,
    List[graphql.language.ast.FieldNode]]) → Union[Awaitable[Dict[str, Any]],
    Dict[str, Any]]

Execute the given fields serially.

Implements the “Executing selection sets” section of the spec for fields that must be executed serially.

execute_operation(operation: graphql.language.ast.OperationDefinitionNode, root_value: Any) →
    Optional[Union[Awaitable[Any], Any]]

Execute an operation.

Implements the “Executing operations” section of the spec.

field_resolver: Callable[..., Any]

fragments: Dict[str, graphql.language.ast.FragmentDefinitionNode]

handle_field_error(error: graphql.error.graphql_error.GraphQLError, return_type:
    Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLObjectType,
    graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLWrappingType]) → None

static is_awaitable(value: Any) → bool

Return true if object can be passed to an await expression.

Instead of testing if the object is an instance of abc.Awaitable, it checks the existence of an __await__ attribute. This is much faster.

middleware_manager: Optional[graphql.execution.middleware.MiddlewareManager]

operation: graphql.language.ast.OperationDefinitionNode

root_value: Any
```

```

schema: graphql.type.schema.GraphQLSchema
subscribe_field_resolver: Callable[..., Any]
type_resolver: Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
Union[graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType]], Optional[Union[Awaitable[Optional[str]],
str]]]
variable_values: Dict[str, Any]

class graphql.execution.ExecutionResult(data: Optional[Dict[str, Any]] = None, errors:
Optional[List[graphql.error.graphql_error.GraphQLError]] = None, extensions: Optional[Dict[str, Any]] = None)
Bases: object

The result of GraphQL execution.


- data is the result of a successful execution of the query.
- errors is included when any errors occurred as a non-empty list.
- extensions is reserved for adding non-standard properties.


__init__(data: Optional[Dict[str, Any]] = None, errors:
Optional[List[graphql.error.graphql_error.GraphQLError]] = None, extensions: Optional[Dict[str, Any]] = None)

data: Optional[Dict[str, Any]]
errors: Optional[List[graphql.error.graphql_error.GraphQLError]]
extensions: Optional[Dict[str, Any]]
property formatted: graphql.execution.execute.FormattedExecutionResult
    Get execution result formatted according to the specification.

class graphql.execution.FormattedExecutionResult
Bases: TypedDict

Formatted execution result
data: Optional[Dict[str, Any]]
errors: List[graphql.error.graphql_error.GraphQLFormattedError]
extensions: Dict[str, Any]

async graphql.execution.subscribe(schema: graphql.type.schema.GraphQLSchema, document:
graphql.language.ast.DocumentNode, root_value: Optional[Any] = None, context_value: Optional[Any] = None, variable_values:
Optional[Dict[str, Any]] = None, operation_name: Optional[str] = None, field_resolver: Optional[Callable[..., Any]] = None,
subscribe_field_resolver: Optional[Callable[..., Any]] = None) → Union[AsyncIterator[graphql.execution.execute.ExecutionResult],
graphql.execution.execute.ExecutionResult]

```

Create a GraphQL subscription.

Implements the “Subscribe” algorithm described in the GraphQL spec.

Returns a coroutine object which yields either an AsyncIterator (if successful) or an ExecutionResult (client error). The coroutine will raise an exception if a server error occurs.

If the client-provided arguments to this function do not result in a compliant subscription, a GraphQL Response (ExecutionResult) with descriptive errors and no data will be returned.

If the source stream could not be created due to faulty subscription resolver logic or underlying systems, the coroutine object will yield a single ExecutionResult containing errors and no data.

If the operation succeeded, the coroutine will yield an AsyncIterator, which yields a stream of ExecutionResults representing the response stream.

```
async graphql.execution.create_source_event_stream(schema: graphql.type.schema.GraphQLSchema,  
                                                 document: graphql.language.ast.DocumentNode,  
                                                 root_value: Optional[Any] = None,  
                                                 context_value: Optional[Any] = None,  
                                                 variable_values: Optional[Dict[str, Any]] =  
                                                 None, operation_name: Optional[str] = None,  
                                                 subscribe_field_resolver: Optional[Callable[[...],  
                                                 Any]] = None) → Union[AsyncIterable[Any],  
                               graphql.execution.execute.ExecutionResult]
```

Create source event stream

Implements the “CreateSourceEventStream” algorithm described in the GraphQL specification, resolving the subscription source event stream.

Returns a coroutine that yields an AsyncIterable.

If the client-provided arguments to this function do not result in a compliant subscription, a GraphQL Response (ExecutionResult) with descriptive errors and no data will be returned.

If the source stream could not be created due to faulty subscription resolver logic or underlying systems, the coroutine object will yield a single ExecutionResult containing errors and no data.

A source event stream represents a sequence of events, each of which triggers a GraphQL execution for that event.

This may be useful when hosting the stateful subscription service in a different process or machine than the stateless GraphQL execution engine, or otherwise separating these two steps. For more on this, see the “Supporting Subscriptions at Scale” information in the GraphQL spec.

```
class graphql.execution.MapAsyncIterator(iterator: AsyncIterable, callback: Callable)
```

Bases: object

Map an AsyncIterable over a callback function.

Given an AsyncIterable and a callback function, return an AsyncIterator which produces values mapped via calling the callback function.

When the resulting AsyncIterator is closed, the underlying AsyncIterable will also be closed.

```
__init__(iterator: AsyncIterable, callback: Callable) → None
```

```
async aclose() → None
```

Close the iterator.

```
async athrow(type_: Union[BaseException, Type[BaseException]], value: Optional[BaseException] =  
None, traceback: Optional[types.TracebackType] = None) → None
```

Throw an exception into the asynchronous iterator.

```
property is_closed: bool
```

Check whether the iterator is closed.

graphql.execution.Middlewarealias of `Optional[Union[Tuple, List, graphql.execution.middleware.MiddlewareManager]]`**class graphql.execution.MiddlewareManager(*middlewares: Any)**Bases: `object`

Manager for the middleware chain.

This class helps to wrap resolver functions with the provided middleware functions and/or objects. The functions take the next middleware function as first argument. If middleware is provided as an object, it must provide a method `resolve` that is used as the middleware function.

Note that since resolvers return “`AwaitableOrValue`”’s, all middleware functions must be aware of this and check whether values are awaitable before awaiting them.

`__init__(*middlewares: Any)`**`get_field_resolver(field_resolver: Callable[..., Any]) → Callable[..., Any]`**

Wrap the provided resolver with the middleware.

Returns a function that chains the middleware functions with the provided resolver function.

`middlewares`**graphql.execution.get_directive_values(`directive_def: graphql.type.directives.GraphQLDirective, node: Union[graphql.language.ast.EnumValueDefinitionNode, graphql.language.ast.ExecutableDefinitionNode, graphql.language.ast.FieldDefinitionNode, graphql.language.ast.InputValueDefinitionNode, graphql.language.ast.SelectionNode, graphql.language.ast.SchemaDefinitionNode, graphql.language.ast.TypeDefinitionNode, graphql.language.ast.TypeExtensionNode], variable_values: Optional[Dict[str, Any]] = None`) → Optional[Dict[str, Any]]**

Get coerced argument values based on provided nodes.

Prepares a dict of argument values given a directive definition and an AST node which may contain directives. Optionally also accepts a dict of variable values.

If the directive does not exist on the node, returns `None`.**graphql.execution.get_variable_values(`schema: graphql.type.schema.GraphQLSchema, var_def_nodes: Collection[graphql.language.ast.VariableDefinitionNode], inputs: Dict[str, Any], max_errors: Optional[int] = None`) → Union[List[graphql.error.graphql_error.GraphQLError], Dict[str, Any]]**

Get coerced variable values based on provided definitions.

Prepares a dict of variable values of the correct type based on the provided variable definitions and arbitrary input. If the input cannot be parsed to match the variable definitions, a `GraphQLError` will be raised.

Language

GraphQL Language

The `graphql.language` package is responsible for parsing and operating on the GraphQL language.

AST

```
class graphql.language.Location(start_token: graphql.language.ast.Token, end_token: graphql.language.ast.Token, source: graphql.language.source.Source)
```

Bases: object

AST Location

Contains a range of UTF-8 character offsets and token references that identify the region of the source from which the AST derived.

```
__init__(start_token: graphql.language.ast.Token, end_token: graphql.language.ast.Token, source: graphql.language.source.Source) → None
```

end: int

end_token: graphql.language.ast.Token

source: graphql.language.source.Source

start: int

start_token: graphql.language.ast.Token

```
class graphql.language.Node(**kwargs: Any)
```

Bases: object

AST nodes

```
__init__(**kwargs: Any) → None
```

Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc',)

kind: str = 'ast'

loc: Optional[graphql.language.ast.Location]

```
to_dict(locations: bool = False) → Dict
```

Each kind of AST node has its own class:

```
class graphql.language.ArgumentNode(**kwargs: Any)
```

Bases: graphql.language.ast.Node

```
__init__(**kwargs: Any) → None
```

Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'name', 'value')

kind: str = 'argument'

```
loc: Optional[graphql.language.ast.Location]
```

```

name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict
value: graphql.language.ast.ValueNode

class graphql.language.BooleanValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ValueNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    keys: Tuple[str, ...] = ('loc', 'value')
    kind: str = 'boolean_value'
    loc: Optional[graphql.language.ast.Location]
    to_dict(locations: bool = False) → Dict
    value: bool

class graphql.language.ConstArgumentNode(**kwargs: Any)
    Bases: graphql.language.ast.ArgumentNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    keys: Tuple[str, ...] = ('loc', 'name', 'value', 'name', 'value')
    kind: str = 'argument'
    loc: Optional[graphql.language.ast.Location]
    name: graphql.language.ast.NameNode
    to_dict(locations: bool = False) → Dict
    value: Union[graphql.language.ast.IntValueNode,
                 graphql.language.ast.FloatValueNode, graphql.language.ast.StringValueNode,
                 graphql.language.ast.BooleanValueNode, graphql.language.ast.NullValueNode,
                 graphql.language.ast.EnumValueNode, graphql.language.ast.ConstListNode,
                 graphql.language.ast.ConstObjectValueNode]

class graphql.language.ConstDirectiveNode(**kwargs: Any)
    Bases: graphql.language.ast.DirectiveNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    arguments: Tuple[graphql.language.ast.ConstArgumentNode, ...]
    keys: Tuple[str, ...] = ('loc', 'name', 'arguments', 'name', 'arguments')
    kind: str = 'directive'
    loc: Optional[graphql.language.ast.Location]
    name: graphql.language.ast.NameNode

```

```
to_dict(locations: bool = False) → Dict

class graphql.language.ConstListValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ListValueNode

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

    keys: Tuple[str, ...] = ('loc', 'values', 'values')
    kind: str = 'list_value'
    loc: Optional[graphql.language.ast.Location]
    to_dict(locations: bool = False) → Dict

    values: Tuple[Union[graphql.language.ast.IntValueNode,
                        graphql.language.ast.FloatValueNode, graphql.language.ast.StringValueNode,
                        graphql.language.ast.BooleanValueNode, graphql.language.ast.NullValueNode,
                        graphql.language.ast.EnumValueNode, graphql.language.ast.ConstListNodeNode,
                        graphql.language.ast.ConstObjectValueNode], ...]

class graphql.language.ConstObjectFieldNode(**kwargs: Any)
    Bases: graphql.language.ast.ObjectFieldNode

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

    keys: Tuple[str, ...] = ('loc', 'name', 'value', 'name', 'value')
    kind: str = 'object_field'
    loc: Optional[graphql.language.ast.Location]
    name: graphql.language.ast.NameNode
    to_dict(locations: bool = False) → Dict

    value: Union[graphql.language.ast.IntValueNode,
                 graphql.language.ast.FloatValueNode, graphql.language.ast.StringValueNode,
                 graphql.language.ast.BooleanValueNode, graphql.language.ast.NullValueNode,
                 graphql.language.ast.EnumValueNode, graphql.language.ast.ConstListNodeNode,
                 graphql.language.ast.ConstObjectValueNode]

class graphql.language.ConstObjectValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ObjectValueNode

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

    fields: Tuple[graphql.language.ast.ConstObjectFieldNode, ...]
    keys: Tuple[str, ...] = ('loc', 'fields', 'fields')
    kind: str = 'object_value'
    loc: Optional[graphql.language.ast.Location]
    to_dict(locations: bool = False) → Dict
```

```

graphql.language.ConstValueNode
alias of Union[graphql.language.ast.IntValueNode, graphql.language.ast.FloatValueNode,
graphql.language.ast.StringValueNode, graphql.language.ast.BooleanValueNode, graphql.
language.ast.NullValueNode, graphql.language.ast.EnumValueNode, graphql.language.ast.
ConstListValueNode, graphql.language.ast.ConstObjectValueNode]

class graphql.language.DefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.Node

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc',)
kind: str = 'definition'

loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict

class graphql.language.DirectiveDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeSystemDefinitionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

arguments: Tuple[graphql.language.ast.InputValueDefinitionNode, ...]
description: Optional[graphql.language.ast.StringValueNode]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'arguments', 'repeatable',
'locations')
kind: str = 'directive_definition'
loc: Optional[graphql.language.ast.Location]
locations: Tuple[graphql.language.ast.NameNode, ...]
name: graphql.language.ast.NameNode
repeatable: bool
to_dict(locations: bool = False) → Dict

class graphql.language.DirectiveNode(**kwargs: Any)
Bases: graphql.language.ast.Node

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

arguments: Tuple[graphql.language.ast.ArgumentNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'arguments')
kind: str = 'directive'
loc: Optional[graphql.language.ast.Location]

```

```
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.DocumentNode(**kwargs: Any)
Bases: graphql.language.ast.Node
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
definitions: Tuple[graphql.language.ast.DefinitionNode, ...]
keys: Tuple[str, ...] = ('loc', 'definitions')
kind: str = 'document'
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict

class graphql.language.EnumTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'values')
kind: str = 'enum_type_definition'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict
values: Tuple[graphql.language.ast.EnumValueDefinitionNode, ...]

class graphql.language.EnumTypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeExtensionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'values')
kind: str = 'enum_type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict
```

```

values: Tuple[graphql.language.ast.EnumValueDefinitionNode, ...]

class graphql.language.EnumValueDefinitionNode(**kwargs: Any)
    Bases: graphql.language.ast.DefinitionNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

description: Optional[graphql.language.ast.StringValueNode]

directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]

keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives')

kind: str = 'enum_value_definition'

loc: Optional[graphql.language.ast.Location]

name: graphql.language.ast.NameNode

to_dict(locations: bool = False) → Dict

class graphql.language.EnumValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ValueNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'value')

kind: str = 'enum_value'

loc: Optional[graphql.language.ast.Location]

to_dict(locations: bool = False) → Dict

value: str

class graphql.language.ExecutableDefinitionNode(**kwargs: Any)
    Bases: graphql.language.ast.DefinitionNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

directives: Tuple[graphql.language.ast.DirectiveNode, ...]

keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'variable_definitions', 'selection_set')

kind: str = 'executable_definition'

loc: Optional[graphql.language.ast.Location]

name: Optional[graphql.language.ast.NameNode]

selection_set: graphql.language.ast.SelectionSetNode

to_dict(locations: bool = False) → Dict

variable_definitions: Tuple[graphql.language.ast.VariableDefinitionNode, ...]

```

```
class graphql.language.FieldDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.DefinitionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

arguments: Tuple[graphql.language.ast.InputValueDefinitionNode, ...]

description: Optional[graphql.language.ast.StringValueNode]

directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]

keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'arguments',
'type')

kind: str = 'field_definition'

loc: Optional[graphql.language.ast.Location]

name: graphql.language.ast.NameNode

to_dict(locations: bool = False) → Dict

type: graphql.language.ast.TypeNode

class graphql.language.FieldNode(**kwargs: Any)
Bases: graphql.language.ast.SelectionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

alias: Optional[graphql.language.ast.NameNode]

arguments: Tuple[graphql.language.ast.ArgumentNode, ...]

directives: Tuple[graphql.language.ast.DirectiveNode, ...]

keys: Tuple[str, ...] = ('loc', 'directives', 'alias', 'name', 'arguments',
'selection_set')

kind: str = 'field'

loc: Optional[graphql.language.ast.Location]

name: graphql.language.ast.NameNode

selection_set: Optional[graphql.language.ast.SelectionSetNode]

to_dict(locations: bool = False) → Dict

class graphql.language.FloatValueNode(**kwargs: Any)
Bases: graphql.language.ast.ValueNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'value')

kind: str = 'float_value'
```

```
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict
value: str

class graphql.language.FragmentDefinitionNode(**kwargs: Any)
    Bases: graphql.language.ast.ExecutableDefinitionNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    directives: Tuple[graphql.language.ast.DirectiveNode, ...]
    keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'variable_definitions',
                           'selection_set', 'type_condition')
    kind: str = 'fragment_definition'
    loc: Optional[graphql.language.ast.Location]
    name: graphql.language.ast.NameNode
    selection_set: graphql.language.ast.SelectionSetNode
    to_dict(locations: bool = False) → Dict
    type_condition: graphql.language.ast.NamedTypeNode
    variable_definitions: Tuple[graphql.language.ast.VariableDefinitionNode, ...]

class graphql.language.FragmentSpreadNode(**kwargs: Any)
    Bases: graphql.language.ast.SelectionNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    directives: Tuple[graphql.language.ast.DirectiveNode, ...]
    keys: Tuple[str, ...] = ('loc', 'directives', 'name')
    kind: str = 'fragment_spread'
    loc: Optional[graphql.language.ast.Location]
    name: graphql.language.ast.NameNode
    to_dict(locations: bool = False) → Dict

class graphql.language.InlineFragmentNode(**kwargs: Any)
    Bases: graphql.language.ast.SelectionNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    directives: Tuple[graphql.language.ast.DirectiveNode, ...]
    keys: Tuple[str, ...] = ('loc', 'directives', 'type_condition', 'selection_set')
    kind: str = 'inline_fragment'
```

```
loc: Optional[graphql.language.ast.Location]
selection_set: graphql.language.ast.SelectionSetNode
to_dict(locations: bool = False) → Dict
type_condition: graphql.language.ast.NamedTypeNode

class graphql.language.InputObjectTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
fields: Tuple[graphql.language.ast.InputValueDefinitionNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'fields')
kind: str = 'input_object_type_definition'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.InputObjectTypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeExtensionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
fields: Tuple[graphql.language.ast.InputValueDefinitionNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'fields')
kind: str = 'input_object_type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.InputValueDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.DefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
default_value: Optional[Union[graphql.language.ast.IntValueNode,
graphql.language.ast.FloatValueNode, graphql.language.ast.StringValueNode,
graphql.language.ast.BooleanValueNode, graphql.language.ast.NullValueNode,
graphql.language.ast.EnumValueNode, graphql.language.ast.ConstListValueNode,
graphql.language.ast.ConstObjectValueNode]]
```

```
description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'type',
'default_value')

kind: str = 'input_value_definition'

loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict
type: graphql.language.ast.TypeNode

class graphql.language.IntValueNode(**kwargs: Any)
Bases: graphql.language.ast.ValueNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'value')

kind: str = 'int_value'

loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict
value: str

class graphql.language.InterfaceTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
fields: Tuple[graphql.language.ast.FieldDefinitionNode, ...]
interfaces: Tuple[graphql.language.ast.NamedTypeNode, ...]

keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'fields',
'interfaces')

kind: str = 'interface_type_definition'

loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.InterfaceTypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeExtensionNode
```

```
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
fields: Tuple[graphql.language.ast.FieldDefinitionNode, ...]
interfaces: Tuple[graphql.language.ast.NamedTypeNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'interfaces', 'fields')
kind: str = 'interface_type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode

to_dict(locations: bool = False) → Dict

class graphql.language.ListTypeNode(**kwargs: Any)
    Bases: graphql.language.ast.TypeNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'type')
kind: str = 'list_type'
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict
type: graphql.language.ast.TypeNode

class graphql.language.ListValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ValueNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'values')
kind: str = 'list_value'
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict
values: Tuple[graphql.language.ast.ValueNode, ...]

class graphql.language.NameNode(**kwargs: Any)
    Bases: graphql.language.ast.Node

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'value')
kind: str = 'name'
```

```

loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict
value: str

class graphql.language.NamedTypeNode(**kwargs: Any)
    Bases: graphql.language.ast.TypeNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    keys: Tuple[str, ...] = ('loc', 'name')
    kind: str = 'named_type'
    loc: Optional[graphql.language.ast.Location]
    name: graphql.language.ast.NameNode
    to_dict(locations: bool = False) → Dict

class graphql.language.NonNullTypeNode(**kwargs: Any)
    Bases: graphql.language.ast.TypeNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    keys: Tuple[str, ...] = ('loc', 'type')
    kind: str = 'non_null_type'
    loc: Optional[graphql.language.ast.Location]
    to_dict(locations: bool = False) → Dict
    type: Union[graphql.language.ast.NamedTypeNode, graphql.language.ast.ListTypeNode]

class graphql.language.NullValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ValueNode
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    keys: Tuple[str, ...] = ('loc',)
    kind: str = 'null_value'
    loc: Optional[graphql.language.ast.Location]
    to_dict(locations: bool = False) → Dict

class graphql.language.ObjectFieldNode(**kwargs: Any)
    Bases: graphql.language.ast.Node
    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.
    keys: Tuple[str, ...] = ('loc', 'name', 'value')

```

```
kind: str = 'object_field'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict
value: graphql.language.ast.ValueNode

class graphql.language.ObjectTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
fields: Tuple[graphql.language.ast.FieldDefinitionNode, ...]
interfaces: Tuple[graphql.language.ast.NamedTypeNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'interfaces',
'fields')
kind: str = 'object_type_definition'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.ObjectTypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeExtensionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
fields: Tuple[graphql.language.ast.FieldDefinitionNode, ...]
interfaces: Tuple[graphql.language.ast.NamedTypeNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'interfaces', 'fields')
kind: str = 'object_type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.ObjectValueNode(**kwargs: Any)
Bases: graphql.language.ast.ValueNode
```

```

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

fields: Tuple[graphql.language.ast.ObjectFieldNode, ...]
keys: Tuple[str, ...] = ('loc', 'fields')
kind: str = 'object_value'
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict

class graphql.language.OperationDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.ExecutableDefinitionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

directives: Tuple[graphql.language.ast.DirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'variable_definitions',
'selection_set', 'operation')
kind: str = 'operation_definition'
loc: Optional[graphql.language.ast.Location]
name: Optional[graphql.language.ast.NameNode]
operation: graphql.language.ast.OperationType
selection_set: graphql.language.ast.SelectionSetNode
to_dict(locations: bool = False) → Dict
variable_definitions: Tuple[graphql.language.ast.VariableDefinitionNode, ...]

class graphql.language.OperationType(value)
Bases: enum.Enum

An enumeration.

MUTATION = 'mutation'
QUERY = 'query'
SUBSCRIPTION = 'subscription'

class graphql.language.OperationTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.Node

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'operation', 'type')
kind: str = 'operation_type_definition'
loc: Optional[graphql.language.ast.Location]

```

```
operation: graphql.language.ast.OperationType
to_dict(locations: bool = False) → Dict
type: graphql.language.ast.NamedTypeNode

class graphql.language.ScalarTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives')
kind: str = 'scalar_type_definition'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.ScalarTypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeExtensionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives')
kind: str = 'scalar_type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.SchemaDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeSystemDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'directives', 'operation_types')
kind: str = 'schema_definition'
loc: Optional[graphql.language.ast.Location]
```

```

operation_types: Tuple[graphql.language.ast.OperationTypeDefinitionNode, ...]

to_dict(locations: bool = False) → Dict

class graphql.language.SchemaExtensionNode(**kwargs: Any)
    Bases: graphql.language.ast.Node

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

    directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]

    keys: Tuple[str, ...] = ('loc', 'directives', 'operation_types')

    kind: str = 'schema_extension'

    loc: Optional[graphql.language.ast.Location]

    operation_types: Tuple[graphql.language.ast.OperationTypeDefinitionNode, ...]

    to_dict(locations: bool = False) → Dict

class graphql.language.SelectionNode(**kwargs: Any)
    Bases: graphql.language.ast.Node

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

    directives: Tuple[graphql.language.ast.DirectiveNode, ...]

    keys: Tuple[str, ...] = ('loc', 'directives')

    kind: str = 'selection'

    loc: Optional[graphql.language.ast.Location]

    to_dict(locations: bool = False) → Dict

class graphql.language.SelectionSetNode(**kwargs: Any)
    Bases: graphql.language.ast.Node

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

    keys: Tuple[str, ...] = ('loc', 'selections')

    kind: str = 'selection_set'

    loc: Optional[graphql.language.ast.Location]

    selections: Tuple[graphql.language.ast.SelectionNode, ...]

    to_dict(locations: bool = False) → Dict

class graphql.language.StringValueNode(**kwargs: Any)
    Bases: graphql.language.ast.ValueNode

    __init__(**kwargs: Any) → None
        Initialize the node with the given keyword arguments.

```

```
block: Optional[bool]
keys: Tuple[str, ...] = ('loc', 'value', 'block')
kind: str = 'string_value'
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict
value: str

class graphql.language.TypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeSystemDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.DirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives')
kind: str = 'type_definition'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.TypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeSystemDefinitionNode
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives')
kind: str = 'type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict

class graphql.language.TypeNode(**kwargs: Any)
Bases: graphql.language.ast.Node
__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.
keys: Tuple[str, ...] = ('loc',)
kind: str = 'type'
```

```

loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict

class graphql.language.TypeSystemDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.DefinitionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc',)
kind: str = 'type_system_definition'
loc: Optional[graphql.language.ast.Location]
to_dict(locations: bool = False) → Dict

graphql.language.TypeSystemExtensionNode
alias of Union[graphql.language.ast.SchemaExtensionNode, graphql.language.ast.TypeExtensionNode]

class graphql.language.UnionTypeDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeDefinitionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

description: Optional[graphql.language.ast.StringValueNode]
directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'description', 'name', 'directives', 'types')
kind: str = 'union_type_definition'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode
to_dict(locations: bool = False) → Dict
types: Tuple[graphql.language.ast.NamedTypeNode, ...]

class graphql.language.UnionTypeExtensionNode(**kwargs: Any)
Bases: graphql.language.ast.TypeExtensionNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]
keys: Tuple[str, ...] = ('loc', 'name', 'directives', 'types')
kind: str = 'union_type_extension'
loc: Optional[graphql.language.ast.Location]
name: graphql.language.ast.NameNode

```

```
to_dict(locations: bool = False) → Dict
types: Tuple[graphql.language.ast.NamedTypeNode, ...]

class graphql.language.ValueNode(**kwargs: Any)
Bases: graphql.language.ast.Node

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc',)

kind: str = 'value'

loc: Optional[graphql.language.ast.Location]

to_dict(locations: bool = False) → Dict

class graphql.language.VariableDefinitionNode(**kwargs: Any)
Bases: graphql.language.ast.Node

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

default_value: Optional[Union[graphql.language.ast.IntValueNode,
graphql.language.ast.FloatValueNode, graphql.language.ast.StringValueNode,
graphql.language.ast.BooleanValueNode, graphql.language.ast.NullValueNode,
graphql.language.ast.EnumValueNode, graphql.language.ast.ConstListNodeNode,
graphql.language.ast.ConstObjectValueNode]]]

directives: Tuple[graphql.language.ast.ConstDirectiveNode, ...]

keys: Tuple[str, ...] = ('loc', 'variable', 'type', 'default_value', 'directives')

kind: str = 'variable_definition'

loc: Optional[graphql.language.ast.Location]

to_dict(locations: bool = False) → Dict

type: graphql.language.ast.TypeNode

variable: graphql.language.ast.VariableNode

class graphql.language.VariableNode(**kwargs: Any)
Bases: graphql.language.ast.ValueNode

__init__(**kwargs: Any) → None
    Initialize the node with the given keyword arguments.

keys: Tuple[str, ...] = ('loc', 'name')

kind: str = 'variable'

loc: Optional[graphql.language.ast.Location]

name: graphql.language.ast.NameNode
```

to_dict(*locations*: bool = False) → Dict

Directive locations are specified using the following enumeration:

```
class graphql.language.DirectiveLocation(value)

Bases: enum.Enum

The enum type representing the directive location values.

ARGUMENT_DEFINITION = 'argument definition'
ENUM = 'enum'
ENUM_VALUE = 'enum value'
FIELD = 'field'
FIELD_DEFINITION = 'field definition'
FRAGMENT_DEFINITION = 'fragment definition'
FRAGMENT_SPREAD = 'fragment spread'
INLINE_FRAGMENT = 'inline fragment'
INPUT_FIELD_DEFINITION = 'input field definition'
INPUT_OBJECT = 'input object'
INTERFACE = 'interface'
MUTATION = 'mutation'
OBJECT = 'object'
QUERY = 'query'
SCALAR = 'scalar'
SCHEMA = 'schema'
SUBSCRIPTION = 'subscription'
UNION = 'union'
VARIABLE_DEFINITION = 'variable definition'
```

You can also check the type of nodes with the following predicates:

`graphql.language.is_definition_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a definition.

`graphql.language.is_executable_definition_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents an executable definition.

`graphql.language.is_selection_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a selection.

`graphql.language.is_value_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a value.

`graphql.language.is_const_value_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a constant value.

`graphql.language.is_type_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a type.

`graphql.language.is_type_system_definition_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a type system definition.

`graphql.language.is_type_definition_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a type definition.

`graphql.language.is_type_system_extension_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a type system extension.

`graphql.language.is_type_extension_node(node: graphql.language.ast.Node) → bool`

Check whether the given node represents a type extension.

Lexer

`class graphql.language.Lexer(source: graphql.language.source.Source)`

Bases: `object`

GraphQL Lexer

A Lexer is a stateful stream generator in that every time it is advanced, it returns the next token in the Source. Assuming the source lexes, the final Token emitted by the lexer will be of kind EOF, after which the lexer will repeatedly return the same EOF token whenever called.

`__init__(source: graphql.language.source.Source)`

Given a Source object, initialize a Lexer for that source.

`advance() → graphql.language.ast.Token`

Advance the token stream to the next non-ignored token.

`create_token(kind: graphql.language.token_kind.TokenKind, start: int, end: int, value: Optional[str] = None) → graphql.language.ast.Token`

Create a token with line and column location information.

`lookahead() → graphql.language.ast.Token`

Look ahead and return the next non-ignored token, but do not change state.

`print_code_point_at(location: int) → str`

Print the code point at the given location.

Prints the code point (or end of file reference) at a given location in a source for use in error messages.

Printable ASCII is printed quoted, while other points are printed in Unicode code point form (ie. U+1234).

`read_block_string(start: int) → graphql.language.ast.Token`

Read a block string token from the source file.

`read_comment(start: int) → graphql.language.ast.Token`

Read a comment token from the source file.

`read_digits(start: int, first_char: str) → int`

Return the new position in the source after reading one or more digits.

read escaped character(*position: int*) → graphql.language.lexer.EscapeSequence
read escaped unicode fixed width(*position: int*) → graphql.language.lexer.EscapeSequence
read escaped unicode variable width(*position: int*) → graphql.language.lexer.EscapeSequence

read name(*start: int*) → *graphql.language.ast.Token*

Read an alphanumeric + underscore name from the source.

read next token(*start: int*) → *graphql.language.ast.Token*

Get the next token from the source starting at the given position.

This skips over whitespace until it finds the next lexable token, then lexes punctuators immediately or calls the appropriate helper function for more complicated tokens.

read number(*start: int, first_char: str*) → *graphql.language.ast.Token*

Reads a number token from the source file.

This can be either a `FloatValue` or an `IntValue`, depending on whether a `FractionalPart` or `ExponentPart` is encountered.

read string(*start: int*) → *graphql.language.ast.Token*

Read a single-quote string token from the source file.

class `graphql.language.TokenKind`(*value*)

Bases: `enum.Enum`

The different kinds of tokens that the lexer emits

```
AMP = '&'  
AT = '@'  
BANG = '!'  
BLOCK_STRING = 'BlockString'  
BRACE_L = '{'  
BRACE_R = '}'  
BRACKET_L = '['  
BRACKET_R = ']'  
COLON = ':'  
COMMENT = 'Comment'  
DOLLAR = '$'  
EOF = '<EOF>'  
EQUALS = '='  
FLOAT = 'Float'  
INT = 'Int'  
NAME = 'Name'
```

```
PAREN_L = '('
PAREN_R = ')'
PIPE = '|'
SOF = '<SOF>'
SPREAD = '...'
STRING = 'String'

class graphql.language.Token(kind: graphql.language.token_kind.TokenKind, start: int, end: int, line: int,
                             column: int, value: Optional[str] = None)
Bases: object
AST Token
Represents a range of characters represented by a lexical token within a Source.

__init__(kind: graphql.language.token_kind.TokenKind, start: int, end: int, line: int, column: int, value:
         Optional[str] = None) → None

column: int
property desc: str
    A helper property to describe a token as a string for debugging
end: int
kind: graphql.language.token_kind.TokenKind
line: int
next: Optional[graphql.language.ast.Token]
prev: Optional[graphql.language.ast.Token]
start: int
value: Optional[str]
```

Location

```
graphql.language.get_location(source: Source, position: int) → graphql.language.location.SourceLocation
Get the line and column for a character position in the source.

Takes a Source and a UTF-8 character offset, and returns the corresponding line and column as a SourceLocation.

class graphql.language.SourceLocation(line: int, column: int)
Bases: NamedTuple
Represents a location in a Source.

__init__()
column: int
    Alias for field number 1
```

```

count(value, /)
    Return number of occurrences of value.

property formatted: graphql.language.location.FormattedSourceLocation

index(value, start=0, stop=9223372036854775807, /)
    Return first index of value.
    Raises ValueError if the value is not present.

line: int
    Alias for field number 0

graphql.language.print_location(location: graphql.language.ast.Location) → str
    Render a helpful description of the location in the GraphQL Source document.

class graphql.language.FormattedSourceLocation
    Bases: TypedDict
    Formatted source location

column: int

line: int

```

Parser

```

graphql.language.parse(source: Union[graphql.language.source.Source, str], no_location: bool = False,
    max_tokens: Optional[int] = None, allow_legacy_fragment_variables: bool = False)
    → graphql.language.ast.DocumentNode

```

Given a GraphQL source, parse it into a Document.

Throws GraphQLError if a syntax error is encountered.

By default, the parser creates AST nodes that know the location in the source that they correspond to. Setting the `no_location` parameter to `False` disables that behavior for performance or testing.

Parser CPU and memory usage is linear to the number of tokens in a document, however in extreme cases it becomes quadratic due to memory exhaustion. Parsing happens before validation, so even invalid queries can burn lots of CPU time and memory. To prevent this, you can set a maximum number of tokens allowed within a document using the `max_tokens` parameter.

Legacy feature (will be removed in v3.3):

If `allow_legacy_fragment_variables` is set to `True`, the parser will understand and parse variable definitions contained in a fragment definition. They'll be represented in the `variable_definitions` field of the `FragmentDefinitionNode`.

The syntax is identical to normal, query-defined variables. For example:

```

fragment A($var: Boolean = false) on T {
    ...
}

```

```

graphql.language.parse_type(source: Union[graphql.language.source.Source, str], no_location: bool = False,
    max_tokens: Optional[int] = None, allow_legacy_fragment_variables: bool = False)
    → graphql.language.ast.TypeNode

```

Parse the AST for a given string containing a GraphQL Type.

Throws GraphQLError if a syntax error is encountered.

This is useful within tools that operate upon GraphQL Types directly and in isolation of complete GraphQL documents.

Consider providing the results to the utility function: `value_from_ast()`.

```
graphql.language.parse_value(source: Union[graphql.language.source.Source, str], no_location: bool = False, max_tokens: Optional[int] = None, allow_legacy_fragment_variables: bool = False) → graphql.language.ast.ValueNode
```

Parse the AST for a given string containing a GraphQL value.

Throws GraphQLError if a syntax error is encountered.

This is useful within tools that operate upon GraphQL Values directly and in isolation of complete GraphQL documents.

Consider providing the results to the utility function: `value_from_ast()`.

```
graphql.language.parse_const_value(source: Union[graphql.language.source.Source, str], no_location: bool = False, max_tokens: Optional[int] = None, allow_legacy_fragment_variables: bool = False) → Union[graphql.language.ast.IntValueNode, graphql.language.ast.FloatValueNode, graphql.language.ast.StringValueNode, graphql.language.ast.BooleanValueNode, graphql.language.ast.NullValueNode, graphql.language.ast.EnumValueNode, graphql.language.ast.ConstListNodeNode, graphql.language.ast.ConstObjectValueNode]
```

Parse the AST for a given string containing a GraphQL constant value.

Similar to `parse_value`, but raises a parse error if it encounters a variable. The return type will be a constant value.

Printer

```
graphql.language.print_ast(ast: graphql.language.ast.Node) → str
```

Convert an AST into a string.

The conversion is done using a set of reasonable formatting rules.

Source

```
class graphql.language.Source(body: str, name: str = 'GraphQL request', location_offset: graphql.language.location.SourceLocation = SourceLocation(line=1, column=1))
```

Bases: `object`

A representation of source input to GraphQL.

```
__init__(body: str, name: str = 'GraphQL request', location_offset: graphql.language.location.SourceLocation = SourceLocation(line=1, column=1)) → None
```

Initialize source input.

The `name` and `location_offset` parameters are optional, but they are useful for clients who store GraphQL documents in source files. For example, if the GraphQL input starts at line 40 in a file named `Foo.graphql`, it might be useful for `name` to be `"Foo.graphql"` and `location` to be `(40, 0)`.

The `line` and `column` attributes in `location_offset` are 1-indexed.

```
body
get_location(position: int) → graphql.language.location.SourceLocation
location_offset
name

graphql.language.print_source_location(source: graphql.language.source.Source, source_location:
                                         graphql.language.location.SourceLocation) → str
```

Render a helpful description of the location in the GraphQL Source document.

Visitor

```
graphql.language.visit(root: graphql.language.ast.Node, visitor: graphql.language.visitor.Visitor, visitor_keys:
                           Optional[Dict[str, Tuple[str, ...]]] = None) → Any
```

Visit each node in an AST.

`visit()` will walk through an AST using a depth-first traversal, calling the visitor's enter methods at each node in the traversal, and calling the leave methods after visiting that node and all of its child nodes.

By returning different values from the enter and leave methods, the behavior of the visitor can be altered, including skipping over a sub-tree of the AST (by returning `False`), editing the AST by returning a value or `None` to remove the value, or to stop the whole traversal by returning `BREAK`.

When using `visit()` to edit an AST, the original AST will not be modified, and a new version of the AST with the changes applied will be returned from the visit function.

To customize the node attributes to be used for traversal, you can provide a dictionary `visitor_keys` mapping node kinds to node attributes.

```
class graphql.language.Visitor
```

Bases: `object`

Visitor that walks through an AST.

Visitors can define two generic methods “enter” and “leave”. The former will be called when a node is entered in the traversal, the latter is called after visiting the node and its child nodes. These methods have the following signature:

```
def enter(self, node, key, parent, path, ancestors):
    # The return value has the following meaning:
    # IDLE (None): no action
    # SKIP: skip visiting this node
    # BREAK: stop visiting altogether
    # REMOVE: delete this node
    # any other value: replace this node with the returned value
    return
```

(continues on next page)

(continued from previous page)

```
def leave(self, node, key, parent, path, ancestors):
    # The return value has the following meaning:
    # IDLE (None) or SKIP: no action
    # BREAK: stop visiting altogether
    # REMOVE: delete this node
    # any other value: replace this node with the returned value
    return
```

The parameters have the following meaning:

Parameters

- **node** – The current node being visiting.
- **key** – The index or key to this node from the parent node or Array.
- **parent** – the parent immediately above this node, which may be an Array.
- **path** – The key path to get to this node from the root node.
- **ancestors** – All nodes and Arrays visited before reaching parent of this node. These correspond to array indices in path. Note: ancestors includes arrays which contain the parent of visited node.

You can also define node kind specific methods by suffixing them with an underscore followed by the kind of the node to be visited. For instance, to visit `field` nodes, you would defined the methods `enter_field()` and/or `leave_field()`, with the same signature as above. If no kind specific method has been defined for a given node, the generic method is called.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

`__init__()` → None

`enter_leave_map: Dict[str, graphql.language.visitor.EnterLeaveVisitor]`

`get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor`

Given a node kind, return the EnterLeaveVisitor for that kind.

`get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[...], Optional[graphql.language.visitor.VisitorActionEnum]]]`

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

`class graphql.language.ParallelVisitor(visitors: Collection[graphql.language.visitor.Visitor])`

Bases: `graphql.language.visitor.Visitor`

A Visitor which delegates to many visitors to run in parallel.

Each visitor will be visited for each node before moving on.

If a prior visitor edits a node, no following visitors will see that node.

```
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(visitors: Collection[graphql.language.visitor.Visitor])
    Create a new visitor from the given list of parallel visitors.

enter_leave_map: Dict[str, graphql.language.visitor.EnterLeaveVisitor]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
```

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

The module also exports the following enumeration that can be used as the return type for `Visitor` methods:

```
class graphql.language.visitor.VisitorActionEnum(value)
Bases: enum.Enum
Special return values for the visitor methods.

You can also use the values of this enum directly.

BREAK = True
REMOVE = Ellipsis
SKIP = False
```

The module also exports the values of this enumeration directly. These can be used as return values of `Visitor` methods to signal particular actions:

```
graphql.language.BREAK (same as ``True``)
    This return value signals that no further nodes shall be visited.

graphql.language.SKIP (same as ``False``)
    This return value signals that the current node shall be skipped.

graphql.language.REMOVE (same as ``Ellipsis``)
    This return value signals that the current node shall be deleted.

graphql.language.IDLE = None
    This return value signals that no additional action shall take place.
```

PyUtils

Python Utils

This package contains dependency-free Python utility functions used throughout the codebase.

Each utility should belong in its own file and be the default export.

These functions are not part of the module interface and are subject to change.

`graphql.pyutils.camel_to_snake(s: str) → str`

Convert from CamelCase to snake_case

`graphql.pyutils.snake_to_camel(s: str, upper: bool = True) → str`

Convert from snake_case to CamelCase

If upper is set, then convert to upper CamelCase, otherwise the first character keeps its case.

`graphql.pyutils.cached_property(func)`

`graphql.pyutils.register_description(base: type) → None`

Register a class that shall be accepted as a description.

`graphql.pyutils.unregister_description(base: type) → None`

Unregister a class that shall no more be accepted as a description.

`graphql.pyutils.did_you_mean(suggestions: Sequence[str], sub_message: Optional[str] = None) → str`

Given [A, B, C] return ‘ Did you mean A, B, or C?’

`graphql.pyutils.identity_func(x: graphql.pyutils.identity_func.T = Undefined, *_args: Any) → graphql.pyutils.identity_func.T`

Return the first received argument.

`graphql.pyutils.inspect(value: Any) → str`

Inspect value and return string representation for error messages.

Used to print values in error messages. We do not use repr() in order to not leak too much of the inner Python representation of unknown objects, and we do not use json.dumps() because not all objects can be serialized as JSON and we want to output strings with single quotes like Python repr() does it.

We also restrict the size of the representation by truncating strings and collections and allowing only a maximum recursion depth.

`graphql.pyutils.is_awaitable(value: Any) → bool`

Return true if object can be passed to an `await` expression.

Instead of testing if the object is an instance of abc.Awaitable, it checks the existence of an `__await__` attribute. This is much faster.

`graphql.pyutils.is_collection(value: Any) → bool`

Check if value is a collection, but not a string or a mapping.

`graphql.pyutils.is_iterable(value: Any) → bool`

Check if value is an iterable, but not a string or a mapping.

`graphql.pyutils.natural_comparison_key(key: str) → Tuple`

Comparison key function for sorting strings by natural sort order.

See: https://en.wikipedia.org/wiki/Natural_sort_order

```
graphql.pyutils.AwaitableOrValue
    alias      of      Union[Awaitable[graphql.pyutils.awaitable_or_value.T],      graphql.pyutils.
    awaitable_or_value.T]

graphql.pyutils.suggestion_list(input_: str, options: Collection[str]) → List[str]
    Get list with suggestions for a given input.

    Given an invalid input string and list of valid options, returns a filtered list of valid options sorted based on their similarity with the input.

class graphql.pyutils.FrozenError
    Bases: TypeError
        Error when trying to change a frozen (read only) collection.

class graphql.pyutils.Path(prev: Any, key: Union[str, int], typename: Optional[str])
    Bases: NamedTuple
        A generic path of string or integer indices

    _init_()
        add_key(key: Union[str, int], typename: Optional[str] = None) → graphql.pyutils.path.Path
            Return a new Path containing the given key.

        as_list() → List[Union[str, int]]
            Return a list of the path keys.

        count(value, /)
            Return number of occurrences of value.

        index(value, start=0, stop=9223372036854775807, /)
            Return first index of value.

            Raises ValueError if the value is not present.

        key: Union[str, int]
            current index in the path (string or integer)

        prev: Any
            path with the previous indices

        typename: Optional[str]
            name of the parent type to avoid path ambiguity

graphql.pyutils.print_path_list(path: Collection[Union[str, int]]) → str
    Build a string describing the path.

class graphql.pyutils.SimplePubSub
    Bases: object
        A very simple publish-subscript system.

        Creates an AsyncIterator from an EventEmitter.

        Useful for mocking a PubSub system for tests.

    _init_() → None

    emit(event: Any) → bool
        Emit an event.
```

```
get_subscriber(transform: Optional[Callable] = None) →
    graphql.pyutils.simple_pub_sub.SimplePubSubIterator

subscribers: Set[Callable]

class graphql.pyutils.SimplePubSubIterator(pubsub: graphql.pyutils.simple_pub_sub.SimplePubSub,
                                             transform: Optional[Callable])

Bases: AsyncIterator

__init__(pubsub: graphql.pyutils.simple_pub_sub.SimplePubSub, transform: Optional[Callable]) → None

async aclose() → None

async empty_queue() → None

async push_value(event: Any) → None

graphql.pyutils.Undefined = Undefined

Symbol for undefined values

This singleton object is used to describe undefined or invalid values. It can be used in places where you would
use undefined in GraphQL.js.
```

Type

GraphQL Type System

The `graphql.type` package is responsible for defining GraphQL types and schema.

Definition

Predicates

```
graphql.type.is_composite_type(type_: Any) → bool

graphql.type.is_enum_type(type_: Any) → bool

graphql.type.is_input_object_type(type_: Any) → bool

graphql.type.is_input_type(type_: Any) → bool

graphql.type.is_interface_type(type_: Any) → bool

graphql.type.is_leaf_type(type_: Any) → bool

graphql.type.is_list_type(type_: Any) → bool

graphql.type.is_named_type(type_: Any) → bool

graphql.type.is_non_null_type(type_: Any) → bool

graphql.type.is_nullable_type(type_: Any) → bool

graphql.type.is_object_type(type_: Any) → bool

graphql.type.is_output_type(type_: Any) → bool
```

```
graphql.type.is_scalar_type(type_: Any) → bool
graphql.type.is_type(type_: Any) → bool
graphql.type.is_union_type(type_: Any) → bool
graphql.type.is_wrapping_type(type_: Any) → bool
```

Assertions

```
graphql.type.assert_abstract_type(type_: Any) → Union[graphql.type.definition.GraphQLInterfaceType,
                                                    graphql.type.definition.GraphQLUnionType]

graphql.type.assert_composite_type(type_: Any) → graphql.type.definition.GraphQLType

graphql.type.assert_enum_type(type_: Any) → graphql.type.definition.GraphQLEnumType

graphql.type.assert_input_object_type(type_: Any) → graphql.type.definition.GraphQLInputObjectType

graphql.type.assert_input_type(type_: Any) → Union[graphql.type.definition.GraphQLScalarType,
                                                    graphql.type.definition.GraphQLEnumType,
                                                    graphql.type.definition.GraphQLInputObjectType,
                                                    graphql.type.definition.GraphQLWrappingType]

graphql.type.assert_interface_type(type_: Any) → graphql.type.definition.GraphQLInterfaceType

graphql.type.assert_leaf_type(type_: Any) → Union[graphql.type.definition.GraphQLScalarType,
                                                    graphql.type.definition.GraphQLEnumType]

graphql.type.assert_list_type(type_: Any) → graphql.type.definition.GraphQLList

graphql.type.assert_named_type(type_: Any) → graphql.type.definition.GraphQLNamedType

graphql.type.assert_non_null_type(type_: Any) → graphql.type.definition.GraphQLNonNull

graphql.type.assert_nullable_type(type_: Any) → Union[graphql.type.definition.GraphQLScalarType,
                                                    graphql.type.definition.GraphQLObjectType,
                                                    graphql.type.definition.GraphQLInterfaceType,
                                                    graphql.type.definition.GraphQLUnionType,
                                                    graphql.type.definition.GraphQLEnumType,
                                                    graphql.type.definition.GraphQLInputObjectType,
                                                    graphql.type.definition.GraphQLList]

graphql.type.assert_object_type(type_: Any) → graphql.type.definition.GraphQLObjectType

graphql.type.assert_output_type(type_: Any) → Union[graphql.type.definition.GraphQLScalarType,
                                                    graphql.type.definition.GraphQLObjectType,
                                                    graphql.type.definition.GraphQLInterfaceType,
                                                    graphql.type.definition.GraphQLUnionType,
                                                    graphql.type.definition.GraphQLEnumType,
                                                    graphql.type.definition.GraphQLWrappingType]

graphql.type.assert_scalar_type(type_: Any) → graphql.type.definition.GraphQLScalarType

graphql.type.assert_type(type_: Any) → graphql.type.definition.GraphQLType
```

`graphql.type.assert_union_type(type_: Any) → graphql.type.definition.GraphQLUnionType`

`graphql.type.assert_wrapping_type(type_: Any) → graphql.type.definition.GraphQLWrappingType`

Un-modifiers

`graphql.type.get_nullable_type(type_: None) → None`

`graphql.type.get_nullable_type(type_: Union[graphql.type.definition.GraphQLScalarType,
graphql.type.definition.GraphQLObjectType,
graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType,
graphql.type.definition.GraphQLEnumType,
graphql.type.definition.GraphQLInputObjectType,
graphql.type.definition.GraphQLList]) →
Union[graphql.type.definition.GraphQLScalarType,
graphql.type.definition.GraphQLObjectType,
graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType,
graphql.type.definition.GraphQLEnumType,
graphql.type.definition.GraphQLInputObjectType,
graphql.type.definition.GraphQLList]`

`graphql.type.get_nullable_type(type_: graphql.type.definition.GraphQLNonNull) →
Union[graphql.type.definition.GraphQLScalarType,
graphql.type.definition.GraphQLObjectType,
graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType,
graphql.type.definition.GraphQLEnumType,
graphql.type.definition.GraphQLInputObjectType,
graphql.type.definition.GraphQLList]`

Unwrap possible non-null type

`graphql.type.get_named_type(type_: None) → None`

`graphql.type.get_named_type(type_: graphql.type.definition.GraphQLType) →
graphql.type.definition.GraphQLNamedType`

Unwrap possible wrapping type

Definitions

```
class graphql.type.GraphQLEnumType(name: str, values: Union[Dict[str,  
graphql.type.definition.GraphQLEnumValue], Mapping[str, Any],  
Type[enum.Enum]], names_as_values: Optional[bool] = False,  
description: Optional[str] = None, extensions: Optional[Dict[str,  
Any]] = None, ast_node:  
Optional[graphql.language.ast.EnumTypeDefinitionNode] = None,  
extension_ast_nodes:  
Optional[Collection[graphql.language.ast.EnumTypeExtensionNode]]  
= None)
```

Bases: `graphql.type.definition.GraphQLNamedType`

Enum Type Definition

Some leaf values of requests and input values are Enums. GraphQL serializes Enum values as strings, however internally Enums can be represented by any kind of type, often integers. They can also be provided as a Python Enum. In this case, the flag `names_as_values` determines what will be used as internal representation. The default value of `False` will use the enum values, the value `True` will use the enum names, and the value `None` will use the members themselves.

Example:

```
RGBType = GraphQLEnumType('RGB', {
    'RED': 0,
    'GREEN': 1,
    'BLUE': 2
})
```

Example using a Python Enum:

```
class RGBEnum(enum.Enum):
    RED = 0
    GREEN = 1
    BLUE = 2

RGBType = GraphQLEnumType('RGB', enum.Enum)
```

Instead of raw values, you can also specify GraphQLEnumValue objects with more detail like description or deprecation information.

Note: If a value is not provided in a definition, the name of the enum value will be used as its internal value when the value is serialized.

```
__init__(name: str, values: Union[Dict[str, graphql.type.definition.GraphQLEnumValue], Mapping[str, Any], Type[enum.Enum]], names_as_values: Optional[bool] = False, description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.EnumTypeDefinitionNode] = None, extension_ast_nodes: Optional[Collection[graphql.language.ast.EnumTypeExtensionNode]] = None) → None

ast_node: Optional[graphql.language.ast.EnumTypeDefinitionNode]
description: Optional[str]
extension_ast_nodes: Tuple[graphql.language.ast.EnumTypeExtensionNode, ...]
extensions: Dict[str, Any]
name: str

parse_literal(value_node: graphql.language.ast.ValueNode, _variables: Optional[Dict[str, Any]] = None) → Any

parse_value(input_value: str) → Any
serialize(output_value: Any) → str
to_kwarg() → graphql.type.definition.GraphQLEnumTypeKwargs
values: Dict[str, graphql.type.definition.GraphQLEnumValue]
```

```
class graphql.type.GraphQLOutputObjectType(name: str, fields: Union[Callable[[], Mapping[str, graphql.type.definition.GraphQLOutputField]], Mapping[str, graphql.type.definition.GraphQLOutputField]], description: Optional[str] = None, out_type: Optional[Callable[[Dict[str, Any]], Any]] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.InputObjectTypeDefinitionNode] = None, extension_ast_nodes: Optional[Collection[graphql.language.ast.InputObjectTypeExtensionNode]] = None)
```

Bases: `graphql.type.definition.GraphQLNamedType`

Input Object Type Definition

An input object defines a structured collection of fields which may be supplied to a field argument.

Using `NonNull` will ensure that a value must be provided by the query.

Example:

```
NonNullFloat = GraphQLNonNull(GraphQLFloat())

class GeoPoint(GraphQLOutputObjectType):
    name = 'GeoPoint'
    fields = {
        'lat': GraphQLInputField(NonNullFloat),
        'lon': GraphQLInputField(NonNullFloat),
        'alt': GraphQLInputField(
            GraphQLFloat(), default_value=0)
    }
```

The outbound values will be Python dictionaries by default, but you can have them converted to other types by specifying an `out_type` function or class.

```
__init__(name: str, fields: Union[Callable[[], Mapping[str, graphql.type.definition.GraphQLOutputField]], Mapping[str, graphql.type.definition.GraphQLOutputField]], description: Optional[str] = None, out_type: Optional[Callable[[Dict[str, Any]], Any]] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.InputObjectTypeDefinitionNode] = None, extension_ast_nodes: Optional[Collection[graphql.language.ast.InputObjectTypeExtensionNode]] = None) → None

ast_node: Optional[graphql.language.ast.InputObjectTypeDefinitionNode]
description: Optional[str]
extension_ast_nodes: Tuple[graphql.language.ast.InputObjectTypeExtensionNode, ...]
extensions: Dict[str, Any]

property fields: Dict[str, graphql.type.definition.GraphQLOutputField]
    Get provided fields, wrap them as GraphQLInputField if needed.

name: str

static out_type(value: Dict[str, Any]) → Any
    Transform outbound values (this is an extension of GraphQL.js).
    This default implementation passes values unaltered as dictionaries.
```

`to_kwargs()` → `graphql.type.definition.GraphQLInputObjectTypeKwargs`

```
class graphql.type.GraphQLInterfaceType(name: str, fields: Union[Callable[], Mapping[str,
    graphql.type.definition.GraphQLField]], Mapping[str,
    graphql.type.definition.GraphQLField]], interfaces:
    Optional[Union[Callable[]]],
    Collection[graphql.type.definition.GraphQLInterfaceType]],
    Collection[graphql.type.definition.GraphQLInterfaceType]]] = None,
    resolve_type: Optional[Callable[[Any,
        graphql.type.definition.GraphQLResolveInfo,
        Union[graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType]]],
        Optional[Union[Awaitable[Optional[str]], str]]]]] = None,
    description: Optional[str] = None, extensions:
    Optional[Dict[str, Any]] = None, ast_node:
    Optional[graphql.language.ast.InterfaceTypeDefinitionNode] =
    None, extension_ast_nodes: Optional[Collection[graphql.language.ast.InterfaceTypeExtensionNode]] =
    None)
```

Bases: `graphql.type.definition.GraphQLNamedType`

Interface Type Definition

When a field can return one of a heterogeneous set of types, an Interface type is used to describe what types are possible, what fields are in common across all types, as well as a function to determine which type is actually used when the field is resolved.

Example:

```
EntityType = GraphQLInterfaceType('Entity', {
    'name': GraphQLField(GraphQLString),
})
```

```
__init__(name: str, fields: Union[Callable[], Mapping[str, graphql.type.definition.GraphQLField]],
    Mapping[str, graphql.type.definition.GraphQLField]], interfaces: Optional[Union[Callable[]]],
    Collection[graphql.type.definition.GraphQLInterfaceType]],
    Collection[graphql.type.definition.GraphQLInterfaceType]]] = None, resolve_type:
    Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
        Union[graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType]], Optional[Union[Awaitable[Optional[str]], str]]]]] = None,
    description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node:
    Optional[graphql.language.ast.InterfaceTypeDefinitionNode] = None, extension_ast_nodes:
    Optional[Collection[graphql.language.ast.InterfaceTypeExtensionNode]] = None) → None
```

`ast_node: Optional[graphql.language.ast.InterfaceTypeDefinitionNode]`

`description: Optional[str]`

`extension_ast_nodes: Tuple[graphql.language.ast.InterfaceTypeExtensionNode, ...]`

`extensions: Dict[str, Any]`

`property fields: Dict[str, graphql.type.definition.GraphQLField]`

Get provided fields, wrapping them as GraphQLFields if needed.

`property interfaces: Tuple[graphql.type.definition.GraphQLInterfaceType, ...]`

Get provided interfaces.

```
name: str

resolve_type: Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
Union[graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType]], Optional[Union[Awaitable[Optional[str]],
str]]]]

to_kwarg() → graphql.type.definition.GraphQLInterfaceTypeKwargs

class graphql.type.GraphQLObjectType(name: str, fields: Union[Callable[[], Mapping[str,
graphql.type.definition.GraphQLField]], Mapping[str,
graphql.type.definition.GraphQLField]], interfaces:
Optional[Union[Callable[[], Collection[graphql.type.definition.GraphQLInterfaceType]],
Collection[graphql.type.definition.GraphQLInterfaceType]]] = None, is_type_of: Optional[Callable[[Any,
graphql.type.definition.GraphQLResolveInfo],
Union[Awaitable[bool], bool]]] = None, extensions:
Optional[Dict[str, Any]] = None, description: Optional[str] = None, ast_node:
Optional[graphql.language.ast.ObjectTypeDefinitionNode] = None,
extension_ast_nodes: Optional[Collection[graphql.language.ast.ObjectTypeExtensionNode]] =
None)
```

Bases: `graphql.type.definition.GraphQLNamedType`

Object Type Definition

Almost all the GraphQL types you define will be object types. Object types have a name, but most importantly describe their fields.

Example:

```
AddressType = GraphQLObjectType('Address', {
    'street': GraphQLField(GraphQLString),
    'number': GraphQLField(GraphQLInt),
    'formatted': GraphQLField(GraphQLString,
        lambda obj, info, **args: f'{obj.number} {obj.street}')
})
```

When two types need to refer to each other, or a type needs to refer to itself in a field, you can use a lambda function with no arguments (a so-called “thunk”) to supply the fields lazily.

Example:

```
PersonType = GraphQLObjectType('Person', lambda: {
    'name': GraphQLField(GraphQLString),
    'bestFriend': GraphQLField(PersonType)
})
```

```
__init__(name: str, fields: Union[Callable[], Mapping[str, graphql.type.definition.GraphQLField]],  
        Mapping[str, graphql.type.definition.GraphQLField]], interfaces: Optional[Union[Callable[],  
        Collection[graphql.type.definition.GraphQLInterfaceType]],  
        Collection[graphql.type.definition.GraphQLInterfaceType]]] = None, is_type_of:  
        Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo], Union[Awaitable[bool],  
        bool]]] = None, extensions: Optional[Dict[str, Any]] = None, description: Optional[str] = None,  
        ast_node: Optional[graphql.language.ast.ObjectTypeDefinitionNode] = None,  
        extension_ast_nodes: Optional[Collection[graphql.language.ast.ObjectTypeExtensionNode]] =  
        None) → None

ast_node: Optional[graphql.language.ast.ObjectTypeDefinitionNode]

description: Optional[str]

extension_ast_nodes: Tuple[graphql.language.ast.ObjectTypeExtensionNode, ...]

extensions: Dict[str, Any]

property fields: Dict[str, graphql.type.definition.GraphQLField]  
    Get provided fields, wrapping them as GraphQLFields if needed.

property interfaces: Tuple[graphql.type.definition.GraphQLInterfaceType, ...]  
    Get provided interfaces.

is_type_of: Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo],  
        Union[Awaitable[bool], bool]]]

name: str

to_kwargs() → graphql.type.definition.GraphQLObjectTypeKwargs

class graphql.type.GraphQLScalarType(name: str, serialize: Optional[Callable[[Any], Any]] = None,  
        parse_value: Optional[Callable[[Any], Any]] = None,  
        parse_literal: Optional[Callable[[graphql.language.ast.ValueNode,  
        Optional[Dict[str, Any]]], Any]] = None, description: Optional[str] = None,  
        specified_by_url: Optional[str] = None, extensions:  
        Optional[Dict[str, Any]] = None, ast_node:  
        Optional[graphql.language.ast.ScalarTypeDefinitionNode] = None,  
        extension_ast_nodes: Optional[Collection[graphql.language.ast.ScalarTypeExtensionNode]] =  
        None)
```

Bases: `graphql.type.definition.GraphQLNamedType`

Scalar Type Definition

The leaf values of any request and input values to arguments are Scalars (or Enums) and are defined with a name and a series of functions used to parse input from ast or variables and to ensure validity.

If a type's serialize function returns `None`, then an error will be raised and a `None` value will be returned in the response. It is always better to validate.

Example:

```
def serialize_odd(value: Any) -> int:  
    try:  
        value = int(value)  
    except ValueError:
```

(continues on next page)

(continued from previous page)

```

raise GraphQLError(
    f"Scalar 'Odd' cannot represent '{value}'"
    " since it is not an integer.")
if not value % 2:
    raise GraphQLError(
        f"Scalar 'Odd' cannot represent '{value}' since it is even.")
return value

odd_type = GraphQLScalarType('Odd', serialize=serialize_odd)

```

__init__(name: str, serialize: Optional[Callable[[Any], Any]] = None, parse_value: Optional[Callable[[Any], Any]] = None, parse_literal: Optional[Callable[[graphql.language.ast.ValueNode, Optional[Dict[str, Any]]], Any]] = None, description: Optional[str] = None, specified_by_url: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.ScalarTypeDefinitionNode] = None, extension_ast_nodes: Optional[Collection[graphql.language.ast.ScalarTypeExtensionNode]] = None) → None

ast_node: Optional[graphql.language.ast.ScalarTypeDefinitionNode]

description: Optional[str]

extension_ast_nodes: Tuple[graphql.language.ast.ScalarTypeExtensionNode, ...]

extensions: Dict[str, Any]

name: str

parse_literal(node: graphql.language.ast.ValueNode, variables: Optional[Dict[str, Any]] = None) → Any
 Parses an externally provided literal value to use as an input.
 This default method uses the parse_value method and should be replaced with a more specific version when creating a scalar type.

static parse_value(value: Any) → Any
 Parses an externally provided value to use as an input.
 This default method just passes the value through and should be replaced with a more specific version when creating a scalar type.

static serialize(value: Any) → Any
 Serializes an internal value to include in a response.
 This default method just passes the value through and should be replaced with a more specific version when creating a scalar type.

specified_by_url: Optional[str]

to_kwargs() → graphql.type.definition.GraphQLScalarTypeKwargs

```
class graphql.type.GraphQLUnionType(name: str, types: Union[Callable[],
    Collection[graphql.type.definition.GraphQLObjectType]],
    Collection[graphql.type.definition.GraphQLObjectType]),
    resolve_type: Optional[Callable[[Any,
        graphql.type.definition.GraphQLResolveInfo,
        Union[graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType]],
    Optional[Union[Awaitable[Optional[str]], str]]]] = None,
    description: Optional[str] = None, extensions: Optional[Dict[str,
    Any]] = None, ast_node:
    Optional[graphql.language.ast.UnionTypeDefinitionNode] = None,
    extension_ast_nodes: Optional[Collection[graphql.language.ast.UnionTypeExtensionNode]] =
    None)
```

Bases: `graphql.type.definition.GraphQLNamedType`

Union Type Definition

When a field can return one of a heterogeneous set of types, a Union type is used to describe what types are possible as well as providing a function to determine which type is actually used when the field is resolved.

Example:

```
def resolve_type(obj, _info, _type):
    if isinstance(obj, Dog):
        return DogType()
    if isinstance(obj, Cat):
        return CatType()

PetType = GraphQLUnionType('Pet', [DogType, CatType], resolve_type)
```

```
__init__(name: str, types: Union[Callable[], Collection[graphql.type.definition.GraphQLObjectType]],
    Collection[graphql.type.definition.GraphQLObjectType]], resolve_type: Optional[Callable[[Any,
        graphql.type.definition.GraphQLResolveInfo,
        Union[graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType]],
    Optional[Union[Awaitable[Optional[str]], str]]]] = None,
    description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node:
    Optional[graphql.language.ast.UnionTypeDefinitionNode] = None, extension_ast_nodes:
    Optional[Collection[graphql.language.ast.UnionTypeExtensionNode]] = None) → None

ast_node: Optional[graphql.language.ast.UnionTypeDefinitionNode]
description: Optional[str]
extension_ast_nodes: Tuple[graphql.language.ast.UnionTypeExtensionNode, ...]
extensions: Dict[str, Any]
name: str
resolve_type: Optional[Callable[[Any, graphql.type.definition.GraphQLResolveInfo,
    Union[graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType]], Optional[Union[Awaitable[Optional[str]], str]]]]
to_kwargs() → graphql.type.definition.GraphQLUnionTypeKwargs
```

```
property types: Tuple[graphql.type.definition.GraphQLObjectType, ...]
```

Get provided types.

Type Wrappers

```
class graphql.type.GraphQLList(type_: graphql.type.definition.GT)
```

Bases: Generic[graphql.type.definition.GT], graphql.type.definition.GraphQLWrappingType[graphql.type.definition.GT]

List Type Wrapper

A list is a wrapping type which points to another type. Lists are often created within the context of defining the fields of an object type.

Example:

```
class PersonType(GraphQLObjectType):
    name = 'Person'

    @property
    def fields(self):
        return {
            'parents': GraphQLField(GraphQLList(PersonType())),
            'children': GraphQLField(GraphQLList(PersonType())),
        }
```

```
__init__(type_: graphql.type.definition.GT) → None
```

```
of_type: graphql.type.definition.GT
```

```
class graphql.type.GraphQLNonNull(type_: graphql.type.definition.GNT)
```

Bases: graphql.type.definition.GraphQLWrappingType[graphql.type.definition.GNT], Generic[graphql.type.definition.GNT]

Non-Null Type Wrapper

A non-null is a wrapping type which points to another type. Non-null types enforce that their values are never null and can ensure an error is raised if this ever occurs during a request. It is useful for fields which you can make a strong guarantee on non-nullability, for example usually the id field of a database row will never be null.

Example:

```
class RowType(GraphQLObjectType):
    name = 'Row'
    fields = {
        'id': GraphQLField(GraphQLNonNull(GraphQLString()))
    }
```

Note: the enforcement of non-nullability occurs within the executor.

```
__init__(type_: graphql.type.definition.GNT)
```

```
of_type: graphql.type.definition.GT
```

Types

```
graphql.type.GraphQLAbstractType
    alias of Union[graphql.type.definition.GraphQLInterfaceType, graphql.type.definition.GraphQLUnionType]

class graphql.type.GraphQLArgument(type_: Union[graphql.type.definition.GraphQLScalarType,
                                                graphql.type.definition.GraphQLEnumType,
                                                graphql.type.definition.GraphQLInputObjectType,
                                                graphql.type.definition.GraphQLWrappingType], default_value: Any = Undefined, description: Optional[str] = None, deprecation_reason: Optional[str] = None, out_name: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.InputValueDefinitionNode] = None)

Bases: object

Definition of a GraphQL argument

__init__(type_: Union[graphql.type.definition.GraphQLScalarType,
                      graphql.type.definition.GraphQLEnumType, graphql.type.definition.GraphQLInputObjectType,
                      graphql.type.definition.GraphQLWrappingType], default_value: Any = Undefined, description: Optional[str] = None, deprecation_reason: Optional[str] = None, out_name: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.InputValueDefinitionNode] = None) → None

ast_node: Optional[graphql.language.ast.InputValueDefinitionNode]
default_value: Any
deprecation_reason: Optional[str]
description: Optional[str]
extensions: Dict[str, Any]
out_name: Optional[str]
to_kwarg() → graphql.type.definition.GraphQLArgumentKwargs

type: Union[graphql.type.definition.GraphQLScalarType,
            graphql.type.definition.GraphQLEnumType,
            graphql.type.definition.GraphQLInputObjectType,
            graphql.type.definition.GraphQLWrappingType]

graphql.type.GraphQLArgumentMap
alias of Dict[str, GraphQLArgument]

graphql.type.GraphQLCompositeType
alias of Union[graphql.type.definition.GraphQLObjectType, graphql.type.definition.GraphQLInterfaceType, graphql.type.definition.GraphQLUnionType]

class graphql.type.GraphQLEnumValue(value: Optional[Any] = None, description: Optional[str] = None, deprecation_reason: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.EnumValueDefinitionNode] = None)

Bases: object
```

```
__init__(value: Optional[Any] = None, description: Optional[str] = None, deprecation_reason: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.EnumValueDefinitionNode] = None) → None

ast_node: Optional[graphql.language.ast.EnumValueDefinitionNode]
deprecation_reason: Optional[str]
description: Optional[str]
extensions: Dict[str, Any]
to_kwargs() → graphql.type.definition.GraphQLEnumValueKwargs
value: Any

graphql.type.GraphQLEnumValueMap
alias of Dict[str, GraphQLEnumValue]

class graphql.type.GraphQLField(type_: Union[graphql.type.definition.GraphQLScalarType,
                                graphql.type.definition.GraphQLObjectType,
                                graphql.type.definition.GraphQLInterfaceType,
                                graphql.type.definition.GraphQLUnionType,
                                graphql.type.definition.GraphQLEnumType,
                                graphql.type.definition.GraphQLWrappingType], args: Optional[Dict[str,
                                graphql.type.definition.GraphQLArgument]] = None, resolve:
                                Optional[Callable[..., Any]] = None, subscribe: Optional[Callable[..., Any]] =
                                None, description: Optional[str] = None, deprecation_reason:
                                Optional[str] = None, extensions: Optional[Dict[str, Any]] = None,
                                ast_node: Optional[graphql.language.ast.FieldDefinitionNode] = None)
```

Bases: object

Definition of a GraphQL field

```
__init__(type_: Union[graphql.type.definition.GraphQLScalarType,
        graphql.type.definition.GraphQLObjectType, graphql.type.definition.GraphQLInterfaceType,
        graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType,
        graphql.type.definition.GraphQLWrappingType], args: Optional[Dict[str,
                    graphql.type.definition.GraphQLArgument]] = None, resolve: Optional[Callable[..., Any]] =
                    None, subscribe: Optional[Callable[..., Any]] = None, description: Optional[str] = None,
                    deprecation_reason: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None,
                    ast_node: Optional[graphql.language.ast.FieldDefinitionNode] = None) → None

args: Dict[str, graphql.type.definition.GraphQLArgument]
ast_node: Optional[graphql.language.ast.FieldDefinitionNode]
deprecation_reason: Optional[str]
description: Optional[str]
extensions: Dict[str, Any]
resolve: Optional[Callable[..., Any]]
subscribe: Optional[Callable[..., Any]]
to_kwargs() → graphql.type.definition.GraphQLFieldKwargs
```

```

type: Union[graphql.type.definition.GraphQLScalarType,
graphql.type.definition.GraphQLObjectType,
graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType,
graphql.type.definition.GraphQLWrappingType]

graphql.type.GraphQLFieldMap
alias of Dict[str, graphql.type.definition.GraphQLField]

class graphql.type.GraphQLInputField(type_: Union[graphql.type.definition.GraphQLScalarType,
                                                 graphql.type.definition.GraphQLEnumType,
                                                 graphql.type.definition.GraphQLInputObjectType,
                                                 graphql.type.definition.GraphQLWrappingType], default_value: Any
= Undefined, description: Optional[str] = None,
deprecation_reason: Optional[str] = None, out_name:
Optional[str] = None, extensions: Optional[Dict[str, Any]] = None,
ast_node:
Optional[graphql.language.ast.InputValueDefinitionNode] = None)

```

Bases: object

Definition of a GraphQL input field

```

__init__(type_: Union[graphql.type.definition.GraphQLScalarType,
                     graphql.type.definition.GraphQLEnumType, graphql.type.definition.GraphQLInputObjectType,
                     graphql.type.definition.GraphQLWrappingType], default_value: Any = Undefined, description:
Optional[str] = None, deprecation_reason: Optional[str] = None, out_name: Optional[str] =
None, extensions: Optional[Dict[str, Any]] = None, ast_node:
Optional[graphql.language.ast.InputValueDefinitionNode] = None) → None

```

ast_node: Optional[graphql.language.ast.InputValueDefinitionNode]

default_value: Any

deprecation_reason: Optional[str]

description: Optional[str]

extensions: Dict[str, Any]

out_name: Optional[str]

to_kwargs() → graphql.type.definition.GraphQLInputFieldKwargs

```

type: Union[graphql.type.definition.GraphQLScalarType,
graphql.type.definition.GraphQLEnumType,
graphql.type.definition.GraphQLInputObjectType,
graphql.type.definition.GraphQLWrappingType]

```

graphql.type.GraphQLInputFieldMap

alias of Dict[str, GraphQLInputField]

graphql.type.GraphQLInputType

```

alias of Union[graphql.type.definition.GraphQLScalarType, graphql.type.definition.
GraphQLEnumType, graphql.type.definition.GraphQLInputObjectType, graphql.type.
definition.GraphQLWrappingType]

```

```
graphql.type.GraphQLLeafType
alias of Union[graphql.type.definition.GraphQLScalarType, graphql.type.definition.GraphQLEnumType]

class graphql.type.GraphQLNamedType(name: str, description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.TypeDefinitionNode] = None, extension_ast_nodes: Optional[Collection[graphql.language.ast.TypeExtensionNode]] = None)

Bases: graphql.type.definition.GraphQLType
Base class for all GraphQL named types

__init__(name: str, description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.TypeDefinitionNode] = None, extension_ast_nodes: Optional[Collection[graphql.language.ast.TypeExtensionNode]] = None) → None

ast_node: Optional[graphql.language.ast.TypeDefinitionNode]
description: Optional[str]
extension_ast_nodes: Tuple[graphql.language.ast.TypeExtensionNode, ...]
extensions: Dict[str, Any]
name: str

to_kwargs() → graphql.type.definition.GraphQLNamedTypeKwargs

graphql.type.GraphQLNullableType
alias of Union[graphql.type.definition.GraphQLScalarType, graphql.type.definition.GraphQLObjectType, graphql.type.definition.GraphQLInterfaceType, graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType, graphql.type.definition.GraphQLInputObjectType, graphql.type.definition.GraphQLList]

graphql.type.GraphQLOutputType
alias of Union[graphql.type.definition.GraphQLScalarType, graphql.type.definition.GraphQLObjectType, graphql.type.definition.GraphQLInterfaceType, graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType, graphql.type.definition.GraphQLWrappingType]

class graphql.type.GraphQLType
Bases: object
Base class for all GraphQL types

__init__()

class graphql.type.GraphQLWrappingType(type_: graphql.type.definition.GT)
Bases: graphql.type.definition.GraphQLType, Generic[graphql.type.definition.GT]
Base class for all GraphQL wrapping types

__init__(type_: graphql.type.definition.GT) → None
of_type: graphql.type.definition.GT
```

```
graphql.type.Thunk
    alias of Union[Callable[], graphql.type.definition.T], graphql.type.definition.T]

graphql.type.ThunkCollection
    alias of Union[Callable[], Collection[graphql.type.definition.T]], Collection[graphql.type.definition.T]

graphql.type.ThunkMapping
    alias of Union[Callable[], Mapping[str, graphql.type.definition.T]], Mapping[str, graphql.type.definition.T]]
```

Resolvers

```
graphql.type.GraphQLFieldResolver
    alias of Callable[..., Any]

graphql.type.GraphQLIsTypeOfFn
    alias of Callable[[Any, graphql.type.definition.GraphQLResolveInfo], Union[Awaitable[bool], bool]]

class graphql.type.GraphQLResolveInfo(field_name: str, field_nodes: List[graphql.language.ast.FieldNode],
                                       return_type: GraphQLObjectType, parent_type: GraphQLObjectType,
                                       path: graphql.pyutils.path.Path, schema: GraphQLSchema,
                                       fragments: Dict[str, graphql.language.ast.FragmentDefinitionNode],
                                       root_value: Any, operation: graphql.language.ast.OperationDefinitionNode,
                                       variable_values: Dict[str, Any], context: Any, is_awaitable: Callable[[Any], bool])
```

Bases: `NamedTuple`

Collection of information passed to the resolvers.

This is always passed as the first argument to the resolvers.

Note that contrary to the JavaScript implementation, the context (commonly used to represent an authenticated user, or request-specific caches) is included here and not passed as an additional argument.

`__init__()`

`context: Any`

Alias for field number 10

`count(value, /)`

Return number of occurrences of value.

`field_name: str`

Alias for field number 0

`field_nodes: List[graphql.language.ast.FieldNode]`

Alias for field number 1

`fragments: Dict[str, graphql.language.ast.FragmentDefinitionNode]`

Alias for field number 6

```
index(value, start=0, stop=9223372036854775807, /)
    Return first index of value.

    Raises ValueError if the value is not present.

is_awaitable: Callable[[Any], bool]
    Alias for field number 11

operation: graphql.language.ast.OperationDefinitionNode
    Alias for field number 8

parent_type: GraphQLObjectType
    Alias for field number 3

path: graphql.pyutils.path.Path
    Alias for field number 4

return_type: GraphQLOutputType
    Alias for field number 2

root_value: Any
    Alias for field number 7

schema: GraphQLSchema
    Alias for field number 5

variable_values: Dict[str, Any]
    Alias for field number 9

graphql.type.GraphQLTypeResolver
    alias of Callable[[Any, graphql.type.definition.GraphQLResolveInfo, GraphQLAbstractType], Optional[Union[Awaitable[Optional[str]], str]]]
```

Directives

Predicates

```
graphql.type.is_directive(directive: Any) → bool
```

Test if the given value is a GraphQL directive.

```
graphql.type.is_specified_directive(directive: graphql.type.directives.GraphQDirective) → bool
```

Check whether the given directive is one of the specified directives.

Definitions

```
class graphql.type.GraphQDirective(name: str, locations:
    Collection[graphql.language.directive_locations.DirectiveLocation], args: Optional[Dict[str, graphql.type.definition.GraphQLArgument]] = None, is_repeatable: bool = False, description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.DirectiveDefinitionNode] = None)
```

Bases: object

GraphQL Directive

Directives are used by the GraphQL runtime as a way of modifying execution behavior. Type system creators will usually not create these directly.

```
__init__(name: str, locations: Collection[graphql.language.directive_locations.DirectiveLocation], args: Optional[Dict[str, graphql.type.definition.GraphQLArgument]] = None, is_repeatable: bool = False, description: Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node: Optional[graphql.language.ast.DirectiveDefinitionNode] = None) → None

args: Dict[str, graphql.type.definition.GraphQLArgument]
ast_node: Optional[graphql.language.ast.DirectiveDefinitionNode]
description: Optional[str]
extensions: Dict[str, Any]
is_repeatable: bool
locations: Tuple[graphql.language.directive_locations.DirectiveLocation, ...]
name: str
to_kwargs() → graphql.type.directives.GraphQLDirectiveKwargs

graphql.type.GraphQLIncludeDirective
    alias of <GraphQLDirective(@include)>
graphql.type.GraphQLSkipDirective
    alias of <GraphQLDirective(@skip)>
graphql.type.GraphQDDeprecatedDirective
    alias of <GraphQLDirective(@deprecated)>
graphql.type.specified_directives
    A tuple with all directives from the GraphQL specification
graphql.type.DEFAULT_DEPRECATION_REASON = 'No longer supported'
    String constant that can be used as the default value for deprecation_reason.
```

Introspection

Predicates

```
graphql.type.is_introspection_type(type_: graphql.type.definition.GraphQLNamedType) → bool
    Check whether the given named GraphQL type is an introspection type.
```

Definitions

```
class graphql.type.TypeKind(value)
    Bases: enum.Enum
    An enumeration.
    ENUM = 'enum'
```

```
INPUT_OBJECT = 'input object'
INTERFACE = 'interface'
LIST = 'list'
NON_NULL = 'non-null'
OBJECT = 'object'
SCALAR = 'scalar'
UNION = 'union'

graphql.type.TypeMetaFieldDef
    alias of <GraphQLField <GraphQLObjectType '__Type'>>
graphql.type.TypeNameMetaFieldDef
    alias of <GraphQLField <GraphQLNonNull <GraphQLScalarType 'String'>>>
graphql.type.SchemaMetaFieldDef
    alias of <GraphQLField <GraphQLNonNull <GraphQLObjectType '__Schema'>>>
graphql.type.introspection_types
    This is a mapping containing all introspection types with their names as keys
```

Scalars

Predicates

```
graphql.type.is_specified_scalar_type(type_: graphql.type.definition.GraphQLNamedType) → bool
    Check whether the given named GraphQL type is a specified scalar type.
```

Definitions

```
graphql.type.GraphQLBoolean
    alias of <GraphQLScalarType 'Boolean'>
graphql.type.GraphQLFloat
    alias of <GraphQLScalarType 'Float'>
graphql.type.GraphQLID
    alias of <GraphQLScalarType 'ID'>
graphql.type.GraphQLInt
    alias of <GraphQLScalarType 'Int'>
graphql.type.GraphQLString
    alias of <GraphQLScalarType 'String'>
graphql.type.GRAPHQL_MAX_INT
    Maximum possible Int value as per GraphQL Spec (32-bit signed integer)
graphql.type.GRAPHQL_MIN_INT
    Minimum possible Int value as per GraphQL Spec (32-bit signed integer)
```

Schema

Predicates

`graphql.type.is_schema(schema: Any) → bool`

Test if the given value is a GraphQL schema.

Definitions

```
class graphql.type.GraphQLSchema(query: Optional[graphql.type.definition.GraphQLObjectType] = None,
                                    mutation: Optional[graphql.type.definition.GraphQLObjectType] = None,
                                    subscription: Optional[graphql.type.definition.GraphQLObjectType] = None,
                                    types: Optional[Collection[graphql.type.definition.GraphQLNamedType]] = None,
                                    directives: Optional[Collection[graphql.type.directives.GraphQDirective]] = None,
                                    description: Optional[str] = None,
                                    extensions: Optional[Dict[str, Any]] = None,
                                    ast_node: Optional[graphql.language.ast.SchemaDefinitionNode] = None,
                                    extension_ast_nodes: Optional[Collection[graphql.language.ast.SchemaExtensionNode]] = None,
                                    assume_valid: bool = False)
```

Bases: `object`

Schema Definition

A Schema is created by supplying the root types of each type of operation, query and mutation (optional). A schema definition is then supplied to the validator and executor.

Schemas should be considered immutable once they are created. If you want to modify a schema, modify the result of the `to_kwargs()` method and recreate the schema.

Example:

```
MyAppSchema = GraphQLSchema(
    query=MyAppQueryRootType,
    mutation=MyAppMutationRootType)
```

Note: When the schema is constructed, by default only the types that are reachable by traversing the root types are included, other types must be explicitly referenced.

Example:

```
character_interface = GraphQLInterfaceType('Character', ...)
human_type = GraphQLObjectType('Human', interfaces=[character_interface], ...)
droid_type = GraphQLObjectType('Droid', interfaces: [character_interface], ...)
schema = GraphQLSchema(
    query=GraphQLObjectType('Query',
        fields={'hero': GraphQLField(character_interface, ...)}),
```

(continues on next page)

(continued from previous page)

```
...
# Since this schema references only the `Character` interface it's
# necessary to explicitly list the types that implement it if
# you want them to be included in the final schema.
types=[human_type, droid_type])
```

Note: If a list of directives is provided to GraphQLSchema, that will be the exact list of directives represented and allowed. If directives is not provided, then a default set of the specified directives (e.g. @include and @skip) will be used. If you wish to provide *additional* directives to these specified directives, you must explicitly declare them. Example:

```
MyAppSchema = GraphQLSchema(
    ...
    directives=specified_directives + [my_custom_directive])
```

```
__init__(query: Optional[graphql.type.definition.GraphQLObjectType] = None, mutation:
Optional[graphql.type.definition.GraphQLObjectType] = None, subscription:
Optional[graphql.type.definition.GraphQLObjectType] = None, types:
Optional[Collection[graphql.type.definition.GraphQLNamedType]] = None, directives:
Optional[Collection[graphql.type.directives.GraphQLDirective]] = None, description:
Optional[str] = None, extensions: Optional[Dict[str, Any]] = None, ast_node:
Optional[graphql.language.ast.SchemaDefinitionNode] = None, extension_ast_nodes:
Optional[Collection[graphql.language.ast.SchemaExtensionNode]] = None, assume_valid: bool =
False) → None
```

Initialize GraphQL schema.

If this schema was built from a source known to be valid, then it may be marked with assume_valid to avoid an additional type system validation.

```
ast_node: Optional[graphql.language.ast.SchemaDefinitionNode]
description: Optional[str]
directives: Tuple[graphql.type.directives.GraphQLDirective, ...]
extension_ast_nodes: Tuple[graphql.language.ast.SchemaExtensionNode, ...]
extensions: Dict[str, Any]
```

```
get_directive(name: str) → Optional[graphql.type.directives.GraphQLDirective]
```

```
get_implementations(interface_type: graphql.type.definition.GraphQLInterfaceType) →
graphql.type.schema.InterfaceImplementations
```

```
get_possible_types(abstract_type: Union[graphql.type.definition.GraphQLInterfaceType,
graphql.type.definition.GraphQLUnionType]) →
List[graphql.type.definition.GraphQLObjectType]
```

Get list of all possible concrete types for given abstract type.

```
get_root_type(operation: graphql.language.ast.OperationType) →
Optional[graphql.type.definition.GraphQLObjectType]
```

```
get_type(name: str) → Optional[graphql.type.definition.GraphQLNamedType]
```

```
is_sub_type(abstract_type: Union[graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType], maybe_sub_type:
    graphql.type.definition.GraphQLNamedType) → bool

Check whether a type is a subtype of a given abstract type.

mutation_type: Optional[graphql.type.definition.GraphQLObjectType]
query_type: Optional[graphql.type.definition.GraphQLObjectType]
subscription_type: Optional[graphql.type.definition.GraphQLObjectType]
to_kwargs() → graphql.type.schema.GraphQLSchemaKwargs
type_map: Dict[str, graphql.type.definition.GraphQLNamedType]
property validation_errors:
Optional[List[graphql.error.graphql_error.GraphQLError]]
```

Validate

Functions

```
graphql.type.validate_schema(schema: graphql.type.schema.GraphQLSchema) →
List[graphql.error.graphql_error.GraphQLError]
```

Validate a GraphQL schema.

Implements the “Type Validation” sub-sections of the specification’s “Type System” section.

Validation runs synchronously, returning a list of encountered errors, or an empty list if no errors were encountered and the Schema is valid.

Assertions

```
graphql.type.assert_valid_schema(schema: graphql.type.schema.GraphQLSchema) → None
```

Utility function which asserts a schema is valid.

Throws a TypeError if the schema is invalid.

Other

Thunk Handling

```
graphql.type.resolve_thunk(thunk: Union[Callable[], graphql.type.definition.T], graphql.type.definition.T] →
graphql.type.definition.T)
```

Resolve the given thunk.

Used while defining GraphQL types to allow for circular references in otherwise immutable type definitions.

Assertions

```
graphql.type.assert_name(name: str) → str
```

Uphold the spec rules about naming.

```
graphql.type.assert_enum_value_name(name: str) → str
```

Uphold the spec rules about naming enum values.

Utilities

GraphQL Utilities

The `graphql.utilities` package contains common useful computations to use with the GraphQL language and type objects.

The GraphQL query recommended for a full schema introspection:

```
graphql.utilities.get_introspection_query(descriptions: bool = True, specified_by_url: bool = False,  
                                         directive_is_repeatable: bool = False, schema_description:  
                                         bool = False, input_value_deprecation: bool = False) → str
```

Get a query for introspection.

Optionally, you can exclude descriptions, include specification URLs, include repeatability of directives, and specify whether to include the schema description as well.

```
class graphql.utilities.IntrospectionQuery
```

Bases: `TypedDict`

The root typed dictionary for schema introspections.

Get the target Operation from a Document:

```
graphql.utilities.get_operation_ast(document_ast: graphql.language.ast.DocumentNode,  
                                     operation_name: Optional[str] = None) →  
                                     Optional[graphql.language.ast.OperationDefinitionNode]
```

Get operation AST node.

Returns an operation AST given a document AST and optionally an operation name. If a name is not provided, an operation is only returned if only one is provided in the document.

Get the Type for the target Operation AST:

```
graphql.utilities.get_operation_root_type(schema: graphql.type.schema.GraphQLSchema, operation:  
                                         Union[graphql.language.ast.OperationDefinitionNode,  
                                               graphql.language.ast.OperationTypeDefinitionNode]) →  
                                         graphql.type.definition.GraphQLObjectType
```

Extract the root type of the operation from the schema.

Deprecated since version 3.2: Please use `GraphQLSchema.getRootType` instead. Will be removed in v3.3.

Convert a `GraphQLSchema` to an `IntrospectionQuery`:

```
graphql.utilities.introspection_from_schema(schema: graphql.type.schema.GraphQLSchema,  
                                             descriptions: bool = True, specified_by_url: bool = True,  
                                             directive_is_repeatable: bool = True, schema_description:  
                                             bool = True, input_value_deprecation: bool = True) →  
                                             graphql.utilities.get_introspection_query.IntrospectionQuery
```

Build an IntrospectionQuery from a GraphQLSchema

IntrospectionQuery is useful for utilities that care about type and field relationships, but do not need to traverse through those relationships.

This is the inverse of build_client_schema. The primary use case is outside of the server context, for instance when doing schema comparisons.

Build a GraphQLSchema from an introspection result:

```
graphql.utilities.build_client_schema(introspection:  
                                      graphql.utilities.get_introspection_query.IntrospectionQuery,  
                                      assume_valid: bool = False) →  
                                      graphql.type.schema.GraphQLSchema
```

Build a GraphQLSchema for use by client tools.

Given the result of a client running the introspection query, creates and returns a GraphQLSchema instance which can be then used with all GraphQL-core 3 tools, but cannot be used to execute a query, as introspection does not represent the “resolver”, “parse” or “serialize” functions or any other server-internal mechanisms.

This function expects a complete introspection result. Don’t forget to check the “errors” field of a server response before calling this function.

Build a GraphQLSchema from GraphQL Schema language:

```
graphql.utilities.build_ast_schema(document_ast: graphql.language.ast.DocumentNode, assume_valid:  
                                    bool = False, assume_valid_sdl: bool = False) →  
                                    graphql.type.schema.GraphQLSchema
```

Build a GraphQL Schema from a given AST.

This takes the ast of a schema document produced by the parse function in src/language/parser.py.

If no schema definition is provided, then it will look for types named Query, Mutation and Subscription.

Given that AST it constructs a GraphQLSchema. The resulting schema has no resolve methods, so execution will use default resolvers.

When building a schema from a GraphQL service’s introspection result, it might be safe to assume the schema is valid. Set assume_valid to True to assume the produced schema is valid. Set assume_valid_sdl to True to assume it is already a valid SDL document.

```
graphql.utilities.build_schema(source: Union[str, graphql.language.source.Source], assume_valid: bool =  
                               False, assume_valid_sdl: bool = False, no_location: bool = False,  
                               allow_legacy_fragment_variables: bool = False) →  
                               graphql.type.schema.GraphQLSchema
```

Build a GraphQLSchema directly from a source document.

Extend an existing GraphQLSchema from a parsed GraphQL Schema language AST:

```
graphql.utilities.extend_schema(schema: graphql.type.schema.GraphQLSchema, document_ast:  
                                 graphql.language.ast.DocumentNode, assume_valid: bool = False,  
                                 assume_valid_sdl: bool = False) →  
                                 graphql.type.schema.GraphQLSchema
```

Extend the schema with extensions from a given document.

Produces a new schema given an existing schema and a document which may contain GraphQL type extensions and definitions. The original schema will remain unaltered.

Because a schema represents a graph of references, a schema cannot be extended without effectively making an entire copy. We do not know until it’s too late if subgraphs remain unchanged.

This algorithm copies the provided schema, applying extensions while producing the copy. The original schema remains unaltered.

When extending a schema with a known valid extension, it might be safe to assume the schema is valid. Set `assume_valid` to `True` to assume the produced schema is valid. Set `assume_valid_sdl` to `True` to assume it is already a valid SDL document.

Sort a GraphQLSchema:

```
graphql.utilities.lexicographic_sort_schema(schema: graphql.type.schema.GraphQLSchema) →
    graphql.type.schema.GraphQLSchema
```

Sort GraphQLSchema.

This function returns a sorted copy of the given GraphQLSchema.

Print a GraphQLSchema to GraphQL Schema language:

```
graphql.utilities.print_introspection_schema(schema: graphql.type.schema.GraphQLSchema) → str
```

```
graphql.utilities.print_schema(schema: graphql.type.schema.GraphQLSchema) → str
```

```
graphql.utilities.print_type(type_: graphql.type.definition.GraphQLNamedType) → str
```

Create a GraphQLType from a GraphQL language AST:

```
graphql.utilities.type_from_ast(schema: graphql.type.schema.GraphQLSchema, type_node:
    graphql.language.ast.NamedTypeNode) →
    Optional[graphql.type.definition.GraphQLNamedType]
```

```
graphql.utilities.type_from_ast(schema: graphql.type.schema.GraphQLSchema, type_node:
    graphql.language.ast.ListTypeNode) →
    Optional[graphql.type.definition.GraphQLList]
```

```
graphql.utilities.type_from_ast(schema: graphql.type.schema.GraphQLSchema, type_node:
    graphql.language.ast.NonNullTypeNode) →
    Optional[graphql.type.definition.GraphQLNonNull]
```

```
graphql.utilities.type_from_ast(schema: graphql.type.schema.GraphQLSchema, type_node:
    graphql.language.ast.TypeNode) →
    Optional[graphql.type.definition.GraphQLType]
```

Get the GraphQL type definition from an AST node.

Given a Schema and an AST node describing a type, return a GraphQLType definition which applies to that type. For example, if provided the parsed AST node for [User], a GraphQLList instance will be returned, containing the type called “User” found in the schema. If a type called “User” is not found in the schema, then None will be returned.

Convert a language AST to a dictionary:

```
graphql.utilities.ast_to_dict(node: graphql.language.ast.Node, locations: bool = False, cache:
    Optional[Dict[graphql.language.ast.Node, Any]] = None) → Dict
```

```
graphql.utilities.ast_to_dict(node: Collection[graphql.language.ast.Node], locations: bool = False, cache:
    Optional[Dict[graphql.language.ast.Node, Any]] = None) →
    List[graphql.language.ast.Node]
```

```
graphql.utilities.ast_to_dict(node: graphql.language.ast.OperationType, locations: bool = False, cache:
    Optional[Dict[graphql.language.ast.Node, Any]] = None) → str
```

Convert a language AST to a nested Python dictionary.

Set `location` to `True` in order to get the locations as well.

Create a Python value from a GraphQL language AST with a type:

```
graphql.utilities.value_from_ast(value_node: Optional[graphql.language.ast.ValueNode], type_:
    Union[graphql.type.definition.GraphQLScalarType,
        graphql.type.definition.GraphQLEnumType,
        graphql.type.definition.GraphQLInputObjectType,
        graphql.type.definition.GraphQLWrappingType], variables:
    Optional[Dict[str, Any]] = None) → Any
```

Produce a Python value given a GraphQL Value AST.

A GraphQL type must be provided, which will be used to interpret different GraphQL Value literals.

Returns `Undefined` when the value could not be validly coerced according to the provided type.

GraphQL Value	JSON Value	Python Value
Input Object	Object	dict
List	Array	list
Boolean	Boolean	bool
String	String	str
Int / Float	Number	int / float
Enum Value	Mixed	Any
NullValue	null	None

Create a Python value from a GraphQL language AST without a type:

```
graphql.utilities.value_from_ast_untyped(value_node: graphql.language.ast.ValueNode, variables:
    Optional[Dict[str, Any]] = None) → Any
```

Produce a Python value given a GraphQL Value AST.

Unlike `value_from_ast()`, no type is provided. The resulting Python value will reflect the provided GraphQL value AST.

GraphQL Value	JSON Value	Python Value
Input Object	Object	dict
List	Array	list
Boolean	Boolean	bool
String / Enum	String	str
Int / Float	Number	int / float
Null	null	None

Create a GraphQL language AST from a Python value:

```
graphql.utilities.ast_from_value(value: Any, type_: Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLInputObjectType,
    graphql.type.definition.GraphQLWrappingType]) →
Optional[graphql.language.ast.ValueNode]
```

Produce a GraphQL Value AST given a Python object.

This function will match Python/JSON values to GraphQL AST schema format by using the suggested GraphQLInputType. For example:

```
ast_from_value('value', GraphQLString)
```

A GraphQL type must be provided, which will be used to interpret different Python values.

JSON Value	GraphQL Value
Object	Input Object
Array	List
Boolean	Boolean
String	String / Enum Value
Number	Int / Float
Mixed	Enum Value
null	NullValue

A helper to use within recursive-descent visitors which need to be aware of the GraphQL type system:

```
class graphql.utilities.TypeInfo(schema: graphql.type.schema.GraphQLSchema, initial_type:  
    Optional[graphql.type.definition.GraphQLType] = None,  
    get_field_def_fn:  
    Optional[Callable[[graphql.type.schema.GraphQLSchema,  
        graphql.type.definition.GraphQLType, graphql.language.ast.FieldNode],  
        Optional[graphql.type.definition.GraphQLField]]] = None)
```

Bases: object

Utility class for keeping track of type definitions.

TypeInfo is a utility class which, given a GraphQL schema, can keep track of the current field and type definitions at any point in a GraphQL document AST during a recursive descent by calling `enter(node)` and `leave(node)`.

```
__init__(schema: graphql.type.schema.GraphQLSchema, initial_type:  
    Optional[graphql.type.definition.GraphQLType] = None, get_field_def_fn:  
    Optional[Callable[[graphql.type.schema.GraphQLSchema, graphql.type.definition.GraphQLType,  
        graphql.language.ast.FieldNode], Optional[graphql.type.definition.GraphQLField]]] = None) →  
    None
```

Initialize the TypeInfo for the given GraphQL schema.

Initial type may be provided in rare cases to facilitate traversals beginning somewhere other than documents.

The optional last parameter is deprecated and will be removed in v3.3.

```
enter(node: graphql.language.ast.Node) → None
```

```
enter_argument(node: graphql.language.ast.ArgumentNode) → None
```

```
enter_directive(node: graphql.language.ast.DirectiveNode) → None
```

```
enter_enum_value(node: graphql.language.ast.EnumValueNode) → None
```

```
enter_field(node: graphql.language.ast.FieldNode) → None
```

```
enter_fragment_definition(node: graphql.language.ast.InlineFragmentNode) → None
```

```
enter_inline_fragment(node: graphql.language.ast.InlineFragmentNode) → None
```

```
enter_list_value(node: graphql.language.ast.ListValueNode) → None
```

```
enter_object_field(node: graphql.language.ast.ObjectFieldNode) → None
```

```
enter_operation_definition(node: graphql.language.ast.OperationDefinitionNode) → None
```

```
enter_selection_set(node: graphql.language.ast.SelectionSetNode) → None
```

```

enter_variable_definition(node: graphql.language.ast.VariableDefinitionNode) → None
get_argument() → Optional[graphql.type.definition.GraphQLArgument]
get_default_value() → Any
get_directive() → Optional[graphql.type.directives.GraphQLDirective]
get_enum_value() → Optional[graphql.type.definition.GraphQLEnumValue]
get_field_def() → Optional[graphql.type.definition.GraphQLField]
get_input_type() → Optional[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLInputObjectType,
    graphql.type.definition.GraphQLWrappingType]]
get_parent_input_type() → Optional[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLInputObjectType,
    graphql.type.definition.GraphQLWrappingType]]
get_parent_type() → Optional[Union[graphql.type.definition.GraphQLObjectType,
    graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType]]
get_type() → Optional[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLObjectType, graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLWrappingType]]

leave(node: graphql.language.ast.Node) → None
leave_argument() → None
leave_directive() → None
leave_enum_value() → None
leave_field() → None
leave_fragment_definition() → None
leave_inline_fragment() → None
leave_list_value() → None
leave_object_field() → None
leave_operation_definition() → None
leave_selection_set() → None
leave_variable_definition() → None

class graphql.utilities.TypeInfoVisitor(type_info: graphql.utilities.type_info.TypeInfo, visitor:
    graphql.language.visitor.Visitor)

```

Bases: *graphql.language.visitor.Visitor*

A visitor which maintains a provided TypeInfo.

BREAK = `True`
IDLE = `None`
REMOVE = `Ellipsis`
SKIP = `False`

`__init__(type_info: graphql.utilities.type_info.TypeInfo, visitor: graphql.language.visitor.Visitor)`

`enter(node: graphql.language.ast.Node, *args: Any) → Any`

`enter_leave_map: Dict[str, graphql.language.visitor.EnterLeaveVisitor]`

`get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor`

Given a node kind, return the EnterLeaveVisitor for that kind.

`get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]`

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

`leave(node: graphql.language.ast.Node, *args: Any) → Any`

Coerce a Python value to a GraphQL type, or produce errors:

`graphql.utilities.coerce_input_value(input_value: typing.Any, type_: typing.Union[graphql.type.definition.GraphQLScalarType, graphql.type.definition.GraphQLEnumType, graphql.type.definition.GraphQLInputObjectType, graphql.type.definition.GraphQLWrappingType], on_error: typing.Callable[[typing.List[typing.Union[str, int]], typing.Any, graphql.error.graphql_error.GraphQLError], None] = <function default_on_error>, path: typing.Optional[graphql.pyutils.path.Path] = None) → Any`

Coerce a Python value given a GraphQL Input Type.

Concatenate multiple ASTs together:

`graphql.utilities.concat_ast(asts: Collection[graphql.language.ast.DocumentNode]) → graphql.language.ast.DocumentNode`

Concat ASTs.

Provided a collection of ASTs, presumably each from different files, concatenate the ASTs together into batched AST, useful for validating many GraphQL source files which together represent one conceptual application.

Separate an AST into an AST per Operation:

`graphql.utilities.separate_operations(document_ast: graphql.language.ast.DocumentNode) → Dict[str, graphql.language.ast.DocumentNode]`

Separate operations in a given AST document.

This function accepts a single AST document which may contain many operations and fragments and returns a collection of AST documents each of which contains a single operation as well the fragment definitions it refers to.

Strip characters that are not significant to the validity or execution of a GraphQL document:

`graphql.utilities.strip_ignored_characters(source: Union[str, graphql.language.source.Source]) → str`

Strip characters that are ignored anyway.

Strips characters that are not significant to the validity or execution of a GraphQL document:

- UnicodeBOM
- WhiteSpace
- LineTerminator
- Comment
- Comma
- BlockString indentation

Note: It is required to have a delimiter character between neighboring non-punctuator tokens and this function always uses single space as delimiter.

It is guaranteed that both input and output documents if parsed would result in the exact same AST except for nodes location.

Warning: It is guaranteed that this function will always produce stable results. However, it's not guaranteed that it will stay the same between different releases due to bugfixes or changes in the GraphQL specification.

Query example:

```
query SomeQuery($foo: String!, $bar: String) {
  someField(foo: $foo, bar: $bar) {
    a
    b {
      c
      d
    }
  }
}
```

Becomes:

```
query SomeQuery($foo:String!$bar:String){someField(foo:$foo bar:$bar){a b{c d}}}
```

SDL example:

```
"""
Type description
"""

type Foo {
  """
  Field description
  """

  bar: String
}
```

Becomes:

```
"""Type description""" type Foo{"""Field description"""\n  bar:String}
```

Comparators for types:

```
graphql.utilities.is_equal_type(type_a: graphql.type.definition.GraphQLType, type_b:  
    graphql.type.definition.GraphQLType) → bool
```

Check whether two types are equal.

Provided two types, return true if the types are equal (invariant).

```
graphql.utilities.is_type_sub_type_of(schema: graphql.type.schema.GraphQLSchema, maybe_subtype:  
    graphql.type.definition.GraphQLType, super_type:  
    graphql.type.definition.GraphQLType) → bool
```

Check whether a type is subtype of another type in a given schema.

Provided a type and a super type, return true if the first type is either equal or a subset of the second super type (covariant).

```
graphql.utilities.do_types_overlap(schema: graphql.type.schema.GraphQLSchema, type_a:  
    Union[graphql.type.definition.GraphQLObjectType,  
        graphql.type.definition.GraphQLInterfaceType,  
        graphql.type.definition.GraphQLUnionType], type_b:  
    Union[graphql.type.definition.GraphQLObjectType,  
        graphql.type.definition.GraphQLInterfaceType,  
        graphql.type.definition.GraphQLUnionType]) → bool
```

Check whether two types overlap in a given schema.

Provided two composite types, determine if they “overlap”. Two composite types overlap when the Sets of possible concrete types for each intersect.

This is often used to determine if a fragment of a given type could possibly be visited in a context of another type.

This function is commutative.

Assert that a string is a valid GraphQL name:

```
graphql.utilities.assert_valid_name(name: str) → str
```

Uphold the spec rules about naming.

Deprecated since version 3.2: Please use `assert_name` instead. Will be removed in v3.3.

```
graphql.utilities.is_valid_name_error(name: str) →  
    Optional[graphql.error.graphql_error.GraphQLError]
```

Return an Error if a name is invalid.

Deprecated since version 3.2: Please use `assert_name` instead. Will be removed in v3.3.

Compare two GraphQLSchemas and detect breaking changes:

```
graphql.utilities.find_breaking_changes(old_schema: graphql.type.schema.GraphQLSchema,  
    new_schema: graphql.type.schema.GraphQLSchema) →  
    List[graphql.utilities.find_breaking_changes.BreakingChange]
```

Find breaking changes.

Given two schemas, returns a list containing descriptions of all the types of breaking changes covered by the other functions down below.

```
graphql.utilities.find_dangerous_changes(old_schema: graphql.type.schema.GraphQLSchema,  
    new_schema: graphql.type.schema.GraphQLSchema) →  
    List[graphql.utilities.find_breaking_changes.DangerousChange]
```

Find dangerous changes.

Given two schemas, returns a list containing descriptions of all the types of potentially dangerous changes covered by the other functions down below.

```
class graphql.utilities.BreakingChange(type, description)
Bases: NamedTuple

__init__()

count(value, /)
    Return number of occurrences of value.

description: str
    Alias for field number 1

index(value, start=0, stop=9223372036854775807, /)
    Return first index of value.
    Raises ValueError if the value is not present.

type: graphql.utilities.find_breaking_changes.BreakingChangeType
    Alias for field number 0

class graphql.utilities.BreakingChangeType(value)
Bases: enum.Enum

An enumeration.

ARG_CHANGED_KIND = 42
ARG_REMOVED = 41
DIRECTIVE_ARG_REMOVED = 51
DIRECTIVE_LOCATION_REMOVED = 54
DIRECTIVE_REMOVED = 50
DIRECTIVE_REPEATABLE_REMOVED = 53
FIELD_CHANGED_KIND = 31
FIELD_REMOVED = 30
IMPLEMENTED_INTERFACE_REMOVED = 23
REQUIRED_ARG_ADDED = 40
REQUIRED_DIRECTIVE_ARG_ADDED = 52
REQUIRED_INPUT_FIELD_ADDED = 22
TYPE_CHANGED_KIND = 11
TYPE_REMOVED = 10
TYPE_REMOVED_FROM_UNION = 20
VALUE_REMOVED_FROM_ENUM = 21

class graphql.utilities.DangerousChange(type, description)
Bases: NamedTuple

__init__()
```

```
count(value, /)
    Return number of occurrences of value.

description: str
    Alias for field number 1

index(value, start=0, stop=9223372036854775807, /)
    Return first index of value.
    Raises ValueError if the value is not present.

type: graphql.utilities.find_breaking_changes.DangerousChangeType
    Alias for field number 0

class graphql.utilities.DangerousChangeType(value)
    Bases: enum.Enum

    An enumeration.

    ARG_DEFAULT_VALUE_CHANGE = 65
    IMPLEMENTED_INTERFACE_ADDED = 64
    OPTIONAL_ARG_ADDED = 63
    OPTIONAL_INPUT_FIELD_ADDED = 62
    TYPE_ADDED_TO_UNION = 61
    VALUE_ADDED_TO_ENUM = 60
```

Validation

GraphQL Validation

The `graphql.validation` package fulfills the Validation phase of fulfilling a GraphQL result.

```
graphql.validation.validate(schema: graphql.type.schema.GraphQLSchema, document_ast:
    graphql.language.ast.DocumentNode, rules:
        Optional[Collection[Type[graphql.validation.rules.ASTValidationRule]]] =
        None, max_errors: Optional[int] = None, type_info:
        Optional[graphql.utilities.type_info.TypeInfo] = None) →
    List[graphql.error.graphql_error.GraphQLError]
```

Implements the “Validation” section of the spec.

Validation runs synchronously, returning a list of encountered errors, or an empty list if no errors were encountered and the document is valid.

A list of specific validation rules may be provided. If not provided, the default list of rules defined by the GraphQL specification will be used.

Each validation rule is a `ValidationRule` object which is a visitor object that holds a `ValidationContext` (see the language/visitor API). Visitor methods are expected to return `GraphQLErrors`, or lists of `GraphQLErrors` when invalid.

Validate will stop validation after a `max_errors` limit has been reached. Attackers can send pathologically invalid queries to induce a DoS attack, so by default `max_errors` set to 100 errors.

Providing a custom `TypeInfo` instance is deprecated and will be removed in v3.3.

```
class graphql.validation.ASTValidationContext(ast: graphql.language.ast.DocumentNode, on_error:
                                              Callable[[graphql.error.graphql_error.GraphQLError], None])
```

Bases: `object`

Utility class providing a context for validation of an AST.

An instance of this class is passed as the `context` attribute to all Validators, allowing access to commonly useful contextual information from within a validation rule.

```
__init__(ast: graphql.language.ast.DocumentNode, on_error:
        Callable[[graphql.error.graphql_error.GraphQLError], None]) → None
```

```
document: graphql.language.ast.DocumentNode
```

```
get_fragment(name: str) → Optional[graphql.language.ast.FragmentDefinitionNode]
```

```
get_fragment_spreads(node: graphql.language.ast.SelectionSetNode) →
    List[graphql.language.ast.FragmentSpreadNode]
```

```
get_recursively_referenced_fragments(operation: graphql.language.ast.OperationDefinitionNode) →
    List[graphql.language.ast.FragmentDefinitionNode]
```

```
on_error(error: graphql.error.graphql_error.GraphQLError) → None
```

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

```
class graphql.validation.ASTValidationRule(context:
                                             graphql.validation.validation_context.ASTValidationContext)
```

Bases: `graphql.language.visitor.Visitor`

Visitor for validation of an AST.

```
BREAK = True
```

```
IDLE = None
```

```
REMOVE = Ellipsis
```

```
SKIP = False
```

```
__init__(context: graphql.validation.validation_context.ASTValidationContext)
```

```
context: graphql.validation.validation_context.ASTValidationContext
```

```
enter_leave_map: Dict[str, EnterLeaveVisitor]
```

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the `EnterLeaveVisitor` for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

```
class graphql.validation.SDLValidationContext(ast: graphql.language.ast.DocumentNode, schema: Optional[graphql.type.schema.GraphQLSchema], on_error: Callable[[graphql.error.graphql_error.GraphQLError], None])
```

Bases: *graphql.validation.validation_context.ASTValidationContext*

Utility class providing a context for validation of an SDL AST.

An instance of this class is passed as the context attribute to all Validators, allowing access to commonly useful contextual information from within a validation rule.

```
__init__(ast: graphql.language.ast.DocumentNode, schema: Optional[graphql.type.schema.GraphQLSchema], on_error: Callable[[graphql.error.graphql_error.GraphQLError], None]) → None
```

document: *graphql.language.ast.DocumentNode*

```
get_fragment(name: str) → Optional[graphql.language.ast.FragmentDefinitionNode]
```

```
get_fragment_spreads(node: graphql.language.ast.SelectionSetNode) → List[graphql.language.ast.FragmentSpreadNode]
```

```
get_recursively_referenced_fragments(operation: graphql.language.ast.OperationDefinitionNode) → List[graphql.language.ast.FragmentDefinitionNode]
```

```
on_error(error: graphql.error.graphql_error.GraphQLError) → None
```

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

schema: *Optional[graphql.type.schema.GraphQLSchema]*

```
class graphql.validation.SDLValidationRule(context: graphql.validation.validation_context(SDLValidationContext))
```

Bases: *graphql.validation.rules.ASTValidationRule*

Visitor for validation of an SDL AST.

BREAK = `True`

IDLE = `None`

REMOVE = `Ellipsis`

SKIP = `False`

```
__init__(context: graphql.validation.validation_context(SDLValidationContext)) → None
```

context: *graphql.validation.validation_context(SDLValidationContext)*

enter_leave_map: *Dict[str, EnterLeaveVisitor]*

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the EnterLeaveVisitor for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```

report_error(error: graphql.error.graphql_error.GraphQLError) → None

class graphql.validation.ValidationContext(schema: graphql.type.schema.GraphQLSchema, ast:
    graphql.language.ast.DocumentNode, type_info:
        graphql.utilities.type_info.TypeInfo, on_error:
            Callable[[graphql.error.graphql_error.GraphQLError], None])
Bases: graphql.validation.validation_context.ASTValidationContext

Utility class providing a context for validation using a GraphQL schema.

An instance of this class is passed as the context attribute to all Validators, allowing access to commonly useful
contextual information from within a validation rule.

__init__(schema: graphql.type.schema.GraphQLSchema, ast: graphql.language.ast.DocumentNode,
    type_info: graphql.utilities.type_info.TypeInfo, on_error:
        Callable[[graphql.error.graphql_error.GraphQLError], None]) → None

document: graphql.language.ast.DocumentNode

get_argument() → Optional[graphql.type.definition.GraphQLArgument]

get_directive() → Optional[graphql.type.directives.GraphQLDirective]

get_enum_value() → Optional[graphql.type.definition.GraphQLEnumValue]

get_field_def() → Optional[graphql.type.definition.GraphQLField]

get_fragment(name: str) → Optional[graphql.language.ast.FragmentDefinitionNode]

get_fragment_spreads(node: graphql.language.ast.SelectionSetNode) →
    List[graphql.language.ast.FragmentSpreadNode]

get_input_type() → Optional[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLInputObjectType,
    graphql.type.definition.GraphQLWrappingType]]

get_parent_input_type() → Optional[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLInputObjectType,
    graphql.type.definition.GraphQLWrappingType]]

get_parent_type() → Optional[Union[graphql.type.definition.GraphQLObjectType,
    graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType]]

get_recursive_variable_usages(operation: graphql.language.ast.OperationDefinitionNode) →
    List[graphql.validation.validation_context.VariableUsage]

get_recursively_referenced_fragments(operation: graphql.language.ast.OperationDefinitionNode) →
    List[graphql.language.ast.FragmentDefinitionNode]

get_type() → Optional[Union[graphql.type.definition.GraphQLScalarType,
    graphql.type.definition.GraphQLObjectType, graphql.type.definition.GraphQLInterfaceType,
    graphql.type.definition.GraphQLUnionType, graphql.type.definition.GraphQLEnumType,
    graphql.type.definition.GraphQLWrappingType]]

```

```
get_variable_usages(node: Union[graphql.language.ast.OperationDefinitionNode,
                                graphql.language.ast.FragmentDefinitionNode]) →
    List[graphql.validation.validation_context.VariableUsage]

on_error(error: graphql.error.graphql_error.GraphQLError) → None

report_error(error: graphql.error.graphql_error.GraphQLError) → None

schema: graphql.type.schema.GraphQLSchema

class graphql.validation.ValidationRule(context:
                                         graphql.validation.validation_context.ValidationContext)
    Bases: graphql.validation.rules.ASTValidationRule
    Visitor for validation using a GraphQL schema.

    BREAK = True
    IDLE = None
    REMOVE = Ellipsis
    SKIP = False

    __init__(context: graphql.validation.validation_context.ValidationContext) → None
    context: graphql.validation.validation_context.ValidationContext
    enter_leave_map: Dict[str, EnterLeaveVisitor]
    get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
        Given a node kind, return the EnterLeaveVisitor for that kind.

    get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., ...
        Optional[graphql.language.visitor.VisitorActionEnum]]]
        Get the visit function for the given node kind and direction.
        Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

    report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Rules

graphql.validation.specified_rules

A tuple with all validation rules defined by the GraphQL specification

Spec Section: “Executable Definitions”

```
class graphql.validation.ExecutableDefinitionsRule(context:
                                                 graphql.validation.validation_context.ASTValidationContext)
    Bases: graphql.validation.rules.ASTValidationRule
    Executable definitions
    A GraphQL document is only valid for execution if all definitions are either operation or fragment definitions.
    See https://spec.graphql.org/draft/#sec-Executable-Definitions

    BREAK = True
```

```

IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ASTValidationContext)
context: graphql.validation.validation_context.ASTValidationContext

enter_document(node: graphql.language.ast.DocumentNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_leave_map: Dict[str, EnterLeaveVisitor]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[],
    Optional[graphql.language.visitor.VisitorActionEnum]]]

    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

report_error(error: graphql.error.graphql_error.GraphQLError) → None

```

Spec Section: “Field Selections on Objects, Interfaces, and Unions Types”

```

class graphql.validation.FieldsOnCorrectTypeRule(context:
    graphql.validation.validation_context.ValidationContext)

Bases: graphql.validation.rules.ValidationRule

Fields on correct type

A GraphQL document is only valid if all fields selected are defined by the parent type, or are an allowed meta field such as __typename.

See https://spec.graphql.org/draft/#sec-Field-Selections

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext) → None
context: graphql.validation.validation_context.ValidationContext

enter_field(node: graphql.language.ast.FieldNode, *_args: Any) → None

enter_leave_map: Dict[str, EnterLeaveVisitor]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

```

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,  
    Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Fragments on Composite Types”

```
class graphql.validation.FragmentsOnCompositeTypesRule(context:  
    graphql.validation.validation_context.ValidationContext)
```

Bases: `graphql.validation.rules.ValidationRule`

Fragments on composite type

Fragments use a type condition to determine if they apply, since fragments can only be spread into a composite type (object, interface, or union), the type condition must also be a composite type.

See <https://spec.graphql.org/draft/#sec-Fragments-On-Composite-Types>

`BREAK = True`

`IDLE = None`

`REMOVE = Ellipsis`

`SKIP = False`

```
__init__(context: graphql.validation.validation_context.ValidationContext) → None
```

```
context: graphql.validation.validation_context.ValidationContext
```

```
enter_fragment_definition(node: graphql.language.ast.FragmentDefinitionNode, *_args: Any) → None
```

```
enter_inline_fragment(node: graphql.language.ast.InlineFragmentNode, *_args: Any) → None
```

`enter_leave_map: Dict[str, EnterLeaveVisitor]`

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the EnterLeaveVisitor for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,  
    Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Argument Names”

```
class graphql.validation.KnownArgumentNamesRule(context:  
    graphql.validation.validation_context.ValidationContext)
```

Bases: `graphql.validation.rules.known_argument_names.KnownArgumentNamesOnDirectivesRule`

Known argument names

A GraphQL field is only valid if all supplied arguments are defined by that field.

See <https://spec.graphql.org/draft/#sec-Argument-Names> See <https://spec.graphql.org/draft/#sec-Directives-Are-In-Valid-Locations>

```

BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext)
context: graphql.validation.validation_context.ValidationContext
enter_argument(arg_node: graphql.language.ast.ArgumentNode, *args: Any) → None
enter_directive(directive_node: graphql.language.ast.DirectiveNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_leave_map: Dict[str, EnterLeaveVisitor]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]}}
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
report_error(error: graphql.error.graphql_error.GraphQLError) → None

```

Spec Section: “Directives Are Defined”

```

class graphql.validation.KnownDirectivesRule(context:
                                              Union[graphql.validation.validation_context.ValidationContext,
                                                    graphql.validation.validation_context.SDLValidationContext])
Bases: graphql.validation.rules.ASTValidationRule
Known directives
A GraphQL document is only valid if all @directives are known by the schema and legally positioned.
See https://spec.graphql.org/draft/#sec-Directives-Are-Defined
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: Union[graphql.validation.validation_context.ValidationContext,
                      graphql.validation.validation_context.SDLValidationContext])
context: Union[graphql.validation.validation_context.ValidationContext,
              graphql.validation.validation_context.SDLValidationContext]
enter_directive(node: graphql.language.ast.DirectiveNode, _key: Any, _parent: Any, _path: Any,
                ancestors: List[graphql.language.ast.Node]) → None

```

`enter_leave_map: Dict[str, EnterLeaveVisitor]`

`get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor`

Given a node kind, return the EnterLeaveVisitor for that kind.

`get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]`

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

`report_error(error: graphql.error.graphql_error.GraphQLError) → None`

Spec Section: “Fragment spread target defined”

`class graphql.validation.KnownFragmentNamesRule(context: graphql.validation.validation_context.ValidationContext)`

Bases: `graphql.validation.rules.ValidationRule`

Known fragment names

A GraphQL document is only valid if all ...`Fragment` fragment spreads refer to fragments defined in the same document.

See <https://spec.graphql.org/draft/#sec-Fragment-spread-target-defined>

`BREAK = True`

`IDLE = None`

`REMOVE = Ellipsis`

`SKIP = False`

`__init__(context: graphql.validation.validation_context.ValidationContext) → None`

`context: graphql.validation.validation_context.ValidationContext`

`enter_fragment_spread(node: graphql.language.ast.FragmentSpreadNode, *_args: Any) → None`

`enter_leave_map: Dict[str, EnterLeaveVisitor]`

`get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor`

Given a node kind, return the EnterLeaveVisitor for that kind.

`get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]`

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

`report_error(error: graphql.error.graphql_error.GraphQLError) → None`

Spec Section: “Fragment Spread Type Existence”

`class graphql.validation.KnownTypeNamesRule(context: Union[graphql.validation.validation_context.ValidationContext, graphql.validation.validation_context.SDLValidationContext])`

Bases: `graphql.validation.rules.ASTValidationRule`

Known type names

A GraphQL document is only valid if referenced types (specifically variable definitions and fragment conditions) are defined by the type schema.

See <https://spec.graphql.org/draft/#sec-Fragment-Spread-Type-Existence>

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

**__init__(context: Union[graphql.validation.validation_context.ValidationContext,
graphql.validation.validation_context.SDLValidationContext])**

context: graphql.validation.validation_context.ASTValidationContext

enter_leave_map: Dict[str, EnterLeaveVisitor]

**enter_named_type(node: graphql.language.ast.NamedTypeNode, _key: Any, parent:
graphql.language.ast.Node, _path: Any, ancestors: List[graphql.language.ast.Node]) →
None**

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor

Given a node kind, return the EnterLeaveVisitor for that kind.

**get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,
Optional[graphql.language.visitor.VisitorActionEnum]]]**

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

report_error(error: graphql.error.graphql_error.GraphQLError) → None

Spec Section: “Lone Anonymous Operation”

**class graphql.validation.LoneAnonymousOperationRule(context:
graphql.validation.validation_context.ASTValidationContext)**

Bases: `graphql.validation.rules.ASTValidationRule`

Lone anonymous operation

A GraphQL document is only valid if when it contains an anonymous operation (the query short-hand) that it contains only that one operation definition.

See <https://spec.graphql.org/draft/#sec-Lone-Anonymous-Operation>

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context.ASTValidationContext)

context: graphql.validation.validation_context.ASTValidationContext

enter_document(node: graphql.language.ast.DocumentNode, *_args: Any) → None

```
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_operation_definition(node: graphql.language.ast.OperationDefinitionNode, *_args: Any) →
    None
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., ...],
    Optional[graphql.language.visitor.VisitorActionEnum]]]
Get the visit function for the given node kind and direction.
Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Fragments must not form cycles”

```
class graphql.validation.NoFragmentCyclesRule(context:
    graphql.validation.validation_context.ASTValidationContext)
Bases: graphql.validation.rules.ASTValidationRule
No fragment cycles
The graph of fragment spreads must not form any cycles including spreading itself. Otherwise an operation could
infinitely spread or infinitely execute on cycles in the underlying data.
See https://spec.graphql.org/draft/#sec-Fragment-spreads-must-not-form-cycles
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False
__init__(context: graphql.validation.validation_context.ASTValidationContext)
context: graphql.validation.validation_context.ASTValidationContext
detect_cycle_recursive(fragment: graphql.language.ast.FragmentDefinitionNode) → None
enter_fragment_definition(node: graphql.language.ast.FragmentDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_leave_map: Dict[str, EnterLeaveVisitor]
static enter_operation_definition(*_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., ...],
    Optional[graphql.language.visitor.VisitorActionEnum]]]
Get the visit function for the given node kind and direction.
Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
```

`report_error(error: graphql.error.graphql_error.GraphQLError) → None`

Spec Section: “All Variable Used Defined”

```
class graphql.validation.NoUndefinedVariablesRule(context:
                                                 graphql.validation.validation_context.ValidationContext)
```

Bases: `graphql.validation.rules.ValidationRule`

No undefined variables

A GraphQL operation is only valid if all variables encountered, both directly and via fragment spreads, are defined by that operation.

See <https://spec.graphql.org/draft/#sec-All-Variable-Uses-Defined>

`BREAK = True`

`IDLE = None`

`REMOVE = Ellipsis`

`SKIP = False`

`__init__(context: graphql.validation.validation_context.ValidationContext)`

`context: graphql.validation.validation_context.ValidationContext`

`enter_leave_map: Dict[str, EnterLeaveVisitor]`

`enter_operation_definition(*_args: Any) → None`

`enter_variable_definition(node: graphql.language.ast.VariableDefinitionNode, *_args: Any) → None`

`get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor`

Given a node kind, return the EnterLeaveVisitor for that kind.

`get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]`

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

`leave_operation_definition(operation: graphql.language.ast.OperationDefinitionNode, *_args: Any) → None`

`report_error(error: graphql.error.graphql_error.GraphQLError) → None`

Spec Section: “Fragments must be used”

```
class graphql.validation.NoUnusedFragmentsRule(context:
                                               graphql.validation.validation_context.ASTValidationContext)
```

Bases: `graphql.validation.rules.ASTValidationRule`

No unused fragments

A GraphQL document is only valid if all fragment definitions are spread within operations, or spread within other fragments spread within operations.

See <https://spec.graphql.org/draft/#sec-Fragments-Must-Be-Used>

`BREAK = True`

```
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ASTValidationContext)
context: graphql.validation.validation_context.ASTValidationContext
enter_fragment_definition(node: graphql.language.ast.FragmentDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_operation_definition(node: graphql.language.ast.OperationDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
leave_document(*_args: Any) → None
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “All Variables Used”

```
class graphql.validation.NoUnusedVariablesRule(context:
    graphql.validation.validation_context.ValidationContext)
Bases: graphql.validation.rules.ValidationRule
No unused variables
A GraphQL operation is only valid if all variables defined by an operation are used, either directly or within a spread fragment.
See https://spec.graphql.org/draft/#sec-All-Variables-Used
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext)
context: graphql.validation.validation_context.ValidationContext
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_operation_definition(*_args: Any) → None
```

enter_variable_definition(*definition*: graphql.language.ast.VariableDefinitionNode, *_args: Any) → None

get_enter_leave_for_kind(*kind*: str) → graphql.language.visitor.EnterLeaveVisitor

Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(*kind*: str, *is_leaving*: bool = False) → Optional[Callable[[], ...], Optional[graphql.language.visitor.VisitorActionEnum]]]

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

leave_operation_definition(*operation*: graphql.language.ast.OperationDefinitionNode, *_args: Any) → None

report_error(*error*: graphql.error.graphql_error.GraphQLError) → None

Spec Section: “Field Selection Merging”

class graphql.validation.OverlappingFieldsCanBeMergedRule(*context*: graphql.validation.validation_context.ValidationContext)

Bases: `graphql.validation.rules.ValidationRule`

Overlapping fields can be merged

A selection set is only valid if all fields (including spreading any fragments) either correspond to distinct response names or can be merged without ambiguity.

See <https://spec.graphql.org/draft/#sec-Field-Selection-Merging>

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(*context*: graphql.validation.validation_context.ValidationContext)

context: `graphql.validation.validation_context.ValidationContext`

enter_leave_map: Dict[str, EnterLeaveVisitor]

enter_selection_set(*selection_set*: graphql.language.ast.SelectionSetNode, *_args: Any) → None

get_enter_leave_for_kind(*kind*: str) → graphql.language.visitor.EnterLeaveVisitor

Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(*kind*: str, *is_leaving*: bool = False) → Optional[Callable[[], ...], Optional[graphql.language.visitor.VisitorActionEnum]]]

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

report_error(*error*: graphql.error.graphql_error.GraphQLError) → None

Spec Section: “Fragment spread is possible”

```
class graphql.validation.PossibleFragmentSpreadsRule(context:  
                                                 graphql.validation.validation_context.ValidationContext)  
Bases: graphql.validation.rules.ValidationRule  
  
Possible fragment spread  
  
A fragment spread is only valid if the type condition could ever possibly be true: if there is a non-empty intersection of the possible parent types, and possible types which pass the type condition.  
  
BREAK = True  
  
IDLE = None  
  
REMOVE = Ellipsis  
  
SKIP = False  
  
__init__(context: graphql.validation.validation_context.ValidationContext) → None  
  
context: graphql.validation.validation_context.ValidationContext  
  
enter_fragment_spread(node: graphql.language.ast.FragmentSpreadNode, *_args: Any) → None  
  
enter_inline_fragment(node: graphql.language.ast.InlineFragmentNode, *_args: Any) → None  
  
enter_leave_map: Dict[str, EnterLeaveVisitor]  
  
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor  
  
    Given a node kind, return the EnterLeaveVisitor for that kind.  
  
get_fragment_type(name: str) → Optional[Union[graphql.type.definition.GraphQLObjectType,  
                                              graphql.type.definition.GraphQLInterfaceType,  
                                              graphql.type.definition.GraphQLUnionType]]  
  
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[...],  
                           Optional[graphql.language.visitor.VisitorActionEnum]]]  
  
    Get the visit function for the given node kind and direction.  
  
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.  
  
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Argument Optionality”

```
class graphql.validation.ProvidedRequiredArgumentsRule(context:  
                                                 graphql.validation.validation_context.ValidationContext)  
Bases: graphql.validation.rules.provided_required_arguments.  
ProvidedRequiredArgumentsOnDirectivesRule  
  
Provided required arguments  
  
A field or directive is only valid if all required (non-null without a default value) field arguments have been provided.  
  
BREAK = True  
  
IDLE = None  
  
REMOVE = Ellipsis
```

```
SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext)

context: graphql.validation.validation_context.ValidationContext

enter_leave_map: Dict[str, EnterLeaveVisitor]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[],
    Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

leave_directive(directive_node: graphql.language.ast.DirectiveNode, *_args: Any) → None

leave_field(field_node: graphql.language.ast.FieldNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Leaf Field Selections”

```
class graphql.validation.ScalarLeafsRule(context:
    graphql.validation.validation_context.ValidationContext)

Bases: graphql.validation.rules.ValidationRule

Scalar leafs

A GraphQL document is valid only if all leaf fields (fields without sub selections) are of scalar or enum types.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext) → None

context: graphql.validation.validation_context.ValidationContext

enter_field(node: graphql.language.ast.FieldNode, *_args: Any) → None

enter_leave_map: Dict[str, EnterLeaveVisitor]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[],
    Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
```

```

__init__(context: graphql.validation.validation_context.ASTValidationContext)
check_arg_uniqueness(argument_nodes: Collection[graphql.language.ast.ArgumentNode]) → None
context: graphql.validation.validation_context.ASTValidationContext
enter_directive(node: graphql.language.ast.DirectiveNode, *args: Any) → None
enter_field(node: graphql.language.ast.FieldNode, *_args: Any) → None
enter_leave_map: Dict[str, EnterLeaveVisitor]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,
        Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
report_error(error: graphql.error.graphql_error.GraphQLError) → None

```

Spec Section: “Directives Are Unique Per Location”

```

class graphql.validation.UniqueDirectivesPerLocationRule(context:
    Union[graphql.validation.validation_context.ValidationConte
        graphql.validation.validation_context(SDLValidationConte
Bases: graphql.validation.rules.ASTValidationRule
Unique directive names per location
A GraphQL document is only valid if all non-repeatable directives at a given location are uniquely named.
See https://spec.graphql.org/draft/#sec-Directives-Are-Unique-Per-Location
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False
__init__(context: Union[graphql.validation.validation_context.ValidationContext,
        graphql.validation.validation_context(SDLValidationContext])
context: Union[graphql.validation.validation_context.ValidationContext,
        graphql.validation.validation_context(SDLValidationContext]
enter(node: graphql.language.ast.Node, *_args: Any) → None
enter_leave_map: Dict[str, EnterLeaveVisitor]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,
        Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

```

report_error(error: graphql.error.graphql_error.GraphQLError) → None

Spec Section: “Fragment Name Uniqueness”

```
class graphql.validation.UniqueFragmentNamesRule(context:
                                                graphql.validation.validation_context.ASTValidationContext)
Bases: graphql.validation.rules.ASTValidationRule
Unique fragment names
A GraphQL document is only valid if all defined fragments have unique names.
See https://spec.graphql.org/draft/#sec-Fragment-Name-Uniqueness
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False
__init__(context: graphql.validation.validation_context.ASTValidationContext)
context: graphql.validation.validation_context.ASTValidationContext
enter_fragment_definition(node: graphql.language.ast.FragmentDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_leave_map: Dict[str, EnterLeaveVisitor]
static enter_operation_definition(*_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Input Object Field Uniqueness”

```
class graphql.validation.UniqueInputFieldNamesRule(context:
                                                graphql.validation.validation_context.ASTValidationContext)
Bases: graphql.validation.rules.ASTValidationRule
Unique input field names
A GraphQL input object value is only valid if all supplied fields are uniquely named.
See https://spec.graphql.org/draft/#sec-Input-Object-Field-Uniqueness
BREAK = True
IDLE = None
REMOVE = Ellipsis
```

```
SKIP = False

__init__(context: graphql.validation.validation_context.ASTValidationContext)
context: graphql.validation.validation_context.ASTValidationContext
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_object_field(node: graphql.language.ast.ObjectFieldNode, *_args: Any) → None
enter_object_value(*_args: Any) → None
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[],
        Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
leave_object_value(*_args: Any) → None
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Operation Name Uniqueness”

```
class graphql.validation.UniqueOperationNamesRule(context:
    graphql.validation.validation_context.ASTValidationContext)
Bases: graphql.validation.rules.ASTValidationRule
Unique operation names
A GraphQL document is only valid if all defined operations have unique names.
See https://spec.graphql.org/draft/#sec-Operation-Name-Uniqueness
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ASTValidationContext)
context: graphql.validation.validation_context.ASTValidationContext
static enter_fragment_definition(*_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_operation_definition(node: graphql.language.ast.OperationDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.
```

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,  
    Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Variable Uniqueness”

```
class graphql.validation.UniqueVariableNamesRule(context:  
    graphql.validation.validation_context.ASTValidationContext)
```

Bases: `graphql.validation.rules.ASTValidationRule`

Unique variable names

A GraphQL operation is only valid if all its variables are uniquely named.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

```
__init__(context: graphql.validation.validation_context.ASTValidationContext)
```

```
context: graphql.validation.validation_context.ASTValidationContext
```

```
enter_leave_map: Dict[str, EnterLeaveVisitor]
```

```
enter_operation_definition(node: graphql.language.ast.OperationDefinitionNode, *_args: Any) →  
    None
```

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the EnterLeaveVisitor for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,  
    Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Value Type Correctness”

```
class graphql.validation.ValuesOfCorrectTypeRule(context:  
    graphql.validation.validation_context.ValidationContext)
```

Bases: `graphql.validation.rules.ValidationRule`

Value literals of correct type

A GraphQL document is only valid if all value literals are of the type expected at their position.

See <https://spec.graphql.org/draft/#sec-Values-of-Correct-Type>

BREAK = True

IDLE = None

```
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext) → None
context: graphql.validation.validation_context.ValidationContext

enter_boolean_value(node: graphql.language.ast.BooleanValueNode, *_args: Any) → None
enter_enum_value(node: graphql.language.ast.EnumValueNode, *_args: Any) → None
enter_float_value(node: graphql.language.ast.FloatValueNode, *_args: Any) → None
enter_int_value(node: graphql.language.ast.IntValueNode, *_args: Any) → None
enter_leave_map: Dict[str, EnterLeaveVisitor]

enter_list_value(node: graphql.language.ast.ListValueNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_null_value(node: graphql.language.ast.NullValueNode, *_args: Any) → None
enter_object_field(node: graphql.language.ast.ObjectFieldNode, *_args: Any) → None
enter_object_value(node: graphql.language.ast.ObjectValueNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
enter_string_value(node: graphql.language.ast.StringValueNode, *_args: Any) → None
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[...], Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

is_valid_value_node(node: graphql.language.ast.ValueNode) → None
    Check whether this is a valid value node.
    Any value literal may be a valid representation of a Scalar, depending on that scalar type.

report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “Variables are Input Types”

```
class graphql.validation.VariablesAreInputTypesRule(context:
    graphql.validation.validation_context.ValidationContext)
```

Bases: *graphql.validation.rules.ValidationRule*

Variables are input types

A GraphQL operation is only valid if all the variables it defines are of input types (scalar, enum, or input object).

See <https://spec.graphql.org/draft/#sec-Variables-Are-Input-Types>

BREAK = True

IDLE = None

```
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext) → None
context: graphql.validation.validation_context.ValidationContext
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_variable_definition(node: graphql.language.ast.VariableDefinitionNode, *_args: Any) → None
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

Spec Section: “All Variable Usages Are Allowed”

```
class graphql.validation.VariablesInAllowedPositionRule(context:
    graphql.validation.validation_context.ValidationContext)
Bases: graphql.validation.rules.ValidationRule
Variables in allowed position
Variable usages must be compatible with the arguments they are passed to.
See https://spec.graphql.org/draft/#sec-All-Variable-Usages-are-Allowed
BREAK = True
IDLE = None
REMOVE = Ellipsis
SKIP = False

__init__(context: graphql.validation.validation_context.ValidationContext)
context: graphql.validation.validation_context.ValidationContext
enter_leave_map: Dict[str, EnterLeaveVisitor]
enter_operation_definition(*_args: Any) → None
enter_variable_definition(node: graphql.language.ast.VariableDefinitionNode, *_args: Any) → None
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.
```

```
leave_operation_definition(operation: graphql.language.ast.OperationDefinitionNode, *_args: Any)
    → None
```

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

SDL-specific validation rules

```
class graphql.validation.LoneSchemaDefinitionRule(context:
    graphql.validation.validation_context(SDLValidationContext))
```

Bases: *graphql.validation.rules.SDLValidationRule*

Lone Schema definition

A GraphQL document is only valid if it contains only one schema definition.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

```
__init__(context: graphql.validation.validation_context(SDLValidationContext))
```

```
context: graphql.validation.validation_context(SDLValidationContext)
```

```
enter_leave_map: Dict[str, EnterLeaveVisitor]
```

```
enter_schema_definition(node: graphql.language.ast.SchemaDefinitionNode, *_args: Any) → None
```

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the EnterLeaveVisitor for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[...],  
    Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

```
class graphql.validation.UniqueOperationTypesRule(context:
    graphql.validation.validation_context(SDLValidationContext))
```

Bases: *graphql.validation.rules.SDLValidationRule*

Unique operation types

A GraphQL document is only valid if it has only one type per operation.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

```
__init__(context: graphql.validation.validation_context(SDLValidationContext))
```

```
check_operation_types(node: Union[graphql.language.ast.SchemaDefinitionNode,
    graphql.language.ast.SchemaExtensionNode], *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

context: graphql.validation.validation_context(SDLValidationContext)

enter_leave_map: Dict[str, EnterLeaveVisitor]

enter_schema_definition(node: Union[graphql.language.ast.SchemaDefinitionNode,
    graphql.language.ast.SchemaExtensionNode], *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_schema_extension(node: Union[graphql.language.ast.SchemaDefinitionNode,
    graphql.language.ast.SchemaExtensionNode], *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

report_error(error: graphql.error.graphql_error.GraphQLError) → None

class graphql.validation.UniqueTypeNamesRule(context:
    graphql.validation.validation_context(SDLValidationContext))
    Bases: graphql.validation.rules(SDLValidationRule)
    Unique type names
    A GraphQL document is only valid if all defined types have unique names.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context(SDLValidationContext))

check_type_name(node: graphql.language.ast.TypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

context: graphql.validation.validation_context(SDLValidationContext)

enter_enum_type_definition(node: graphql.language.ast.TypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_input_object_type_definition(node: graphql.language.ast.TypeDefinitionNode, *_args: Any)
    → Optional[graphql.language.visitor.VisitorActionEnum]

enter_interface_type_definition(node: graphql.language.ast.TypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]
```

```

enter_leave_map: Dict[str, EnterLeaveVisitor]

enter_object_type_definition(node: graphql.language.ast.TypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_scalar_type_definition(node: graphql.language.ast.TypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_union_type_definition(node: graphql.language.ast.TypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.
    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

report_error(error: graphql.error.graphql_error.GraphQLError) → None

class graphql.validation.UniqueEnumValueNamesRule(context:
    graphql.validation.validation_context(SDLValidationContext))
    Bases: graphql.validation.rules(SDLValidationRule)
    Unique enum value names
    A GraphQL enum type is only valid if all its values are uniquely named.

    BREAK = True
    IDLE = None
    REMOVE = Ellipsis
    SKIP = False

    __init__(context: graphql.validation.validation_context(SDLValidationContext))

    check_value_uniqueness(node: graphql.language.ast.EnumTypeDefinitionNode, *_args: Any) →
        Optional[graphql.language.visitor.VisitorActionEnum]

    context: graphql.validation.validation_context(SDLValidationContext)

    enter_enum_type_definition(node: graphql.language.ast.EnumTypeDefinitionNode, *_args: Any) →
        Optional[graphql.language.visitor.VisitorActionEnum]

    enter_enum_type_extension(node: graphql.language.ast.EnumTypeDefinitionNode, *_args: Any) →
        Optional[graphql.language.visitor.VisitorActionEnum]

    enter_leave_map: Dict[str, EnterLeaveVisitor]

    get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
        Given a node kind, return the EnterLeaveVisitor for that kind.

```

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

```
class graphql.validation.UniqueFieldDefinitionNamesRule(context:
```

```
    graphql.validation.validation_context(SDLValidationContext)
```

Bases: `graphql.validation.rules(SDLValidationRule)`

Unique field definition names

A GraphQL complex type is only valid if all its fields are uniquely named.

BREAK = `True`

IDLE = `None`

REMOVE = `Ellipsis`

SKIP = `False`

```
__init__(context: graphql.validation.validation_context(SDLValidationContext))
```

```
check_field_uniqueness(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

```
context: graphql.validation.validation_context(SDLValidationContext)
```

```
enter_input_object_type_definition(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

```
enter_input_object_type_extension(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

```
enter_interface_type_definition(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

```
enter_interface_type_extension(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

enter_leave_map: `Dict[str, EnterLeaveVisitor]`

```
enter_object_type_definition(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

```
enter_object_type_extension(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) → Optional[graphql.language.visitor.VisitorActionEnum]
```

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the EnterLeaveVisitor for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```

report_error(error: graphql.error.graphql_error.GraphQLError) → None

class graphql.validation.UniqueArgumentDefinitionNamesRule(context:
    graphql.validation.validation_context(SDLValidationConte
Bases: graphql.validation.rules(SDLValidationRule)

Unique argument definition names

A GraphQL Object or Interface type is only valid if all its fields have uniquely named arguments. A GraphQL Directive is only valid if all its arguments are uniquely named.

See https://spec.graphql.org/draft/#sec-Argument-Uniqueness

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context(SDLValidationContext) → None

check_arg_uniqueness(parent_name: str, argument_nodes:
    Collection[graphql.language.ast.InputValueDefinitionNode]) →
    Optional[graphql.language.visitor.VisitorActionEnum]

check_arg_uniqueness_per_field(name: graphql.language.ast.NameNode, fields:
    Collection[graphql.language.ast.FieldDefinitionNode]) →
    Optional[graphql.language.visitor.VisitorActionEnum]

context: graphql.validation.validation_context(SDLValidationContext)

enter_directive_definition(node: graphql.language.ast.DirectiveDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_interface_type_definition(node: graphql.language.ast.InterfaceTypeDefinitionNode, *_args:
    Any) → Optional[graphql.language.visitor.VisitorActionEnum]

enter_interface_type_extension(node: graphql.language.ast.InterfaceTypeExtensionNode, *_args:
    Any) → Optional[graphql.language.visitor.VisitorActionEnum]

enter_leave_map: Dict[str, EnterLeaveVisitor]

enter_object_type_definition(node: graphql.language.ast.ObjectTypeDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_object_type_extension(node: graphql.language.ast.ObjectTypeExtensionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor

    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[..., Optional[graphql.language.visitor.VisitorActionEnum]]]

    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

```

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None

class graphql.validation.UniqueDirectiveNamesRule(context:
    graphql.validation.validation_context(SDLValidationContext))
Bases: graphql.validation.rules(SDLValidationRule)

Unique directive names

A GraphQL document is only valid if all defined directives have unique names.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context(SDLValidationContext))

context: graphql.validation.validation_context(SDLValidationContext)

enter_directive_definition(node: graphql.language.ast.DirectiveDefinitionNode, *_args: Any) →
    Optional[graphql.language.visitor.VisitorActionEnum]

enter_leave_map: Dict[str, EnterLeaveVisitor]

get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
    Given a node kind, return the EnterLeaveVisitor for that kind.

get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[[...],
    Optional[graphql.language.visitor.VisitorActionEnum]]]
    Get the visit function for the given node kind and direction.

    Deprecated since version 3.2: Please use get_enter_leave_for_kind instead. Will be removed in v3.3.

report_error(error: graphql.error.graphql_error.GraphQLError) → None

class graphql.validation.PossibleTypeExtensionsRule(context:
    graphql.validation.validation_context(SDLValidationContext))
Bases: graphql.validation.rules(SDLValidationRule)

Possible type extension

A type extension is only valid if the type is defined and has the same kind.

BREAK = True

IDLE = None

REMOVE = Ellipsis

SKIP = False

__init__(context: graphql.validation.validation_context(SDLValidationContext))

check_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) → None

context: graphql.validation.validation_context(SDLValidationContext)

enter_enum_type_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) → None
```

```
enter_input_object_type_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) →  
    None
```

```
enter_interface_type_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) →  
    None
```

```
enter_leave_map: Dict[str, EnterLeaveVisitor]
```

```
enter_object_type_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) → None
```

```
enter_scalar_type_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) → None
```

```
enter_union_type_extension(node: graphql.language.ast.TypeExtensionNode, *_args: Any) → None
```

```
get_enter_leave_for_kind(kind: str) → graphql.language.visitor.EnterLeaveVisitor
```

Given a node kind, return the EnterLeaveVisitor for that kind.

```
get_visit_fn(kind: str, is_leaving: bool = False) → Optional[Callable[...,  
    Optional[graphql.language.visitor.VisitorActionEnum]]]
```

Get the visit function for the given node kind and direction.

Deprecated since version 3.2: Please use `get_enter_leave_for_kind` instead. Will be removed in v3.3.

```
report_error(error: graphql.error.graphql_error.GraphQLError) → None
```

**CHAPTER
TWO**

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

g

graphql, 19
graphql.error, 21
graphql.execution, 24
graphql.language, 32
graphql.pyutils, 60
graphql.type, 62
graphql.utilities, 84
graphql.validation, 94
graphql.validation.rules, 98

INDEX

Symbols

`__init__(graphql.error.GraphQLError method)`, 21
`__init__(graphql.error.GraphQLSyntaxError method)`, 22
`__init__(graphql.execution.ExecutionContext method)`, 25
`__init__(graphql.execution.ExecutionResult method)`, 29
`__init__(graphql.execution.MapAsyncIterator method)`, 30
`__init__(graphql.execution.MiddlewareManager method)`, 31
`__init__(graphql.language.ArgumentNode method)`, 32
`__init__(graphql.language.BooleanValueNode method)`, 33
`__init__(graphql.language.ConstArgumentNode method)`, 33
`__init__(graphql.language.ConstDirectiveNode method)`, 33
`__init__(graphql.language.ConstListValueNode method)`, 34
`__init__(graphql.language.ConstObjectFieldNode method)`, 34
`__init__(graphql.language.ConstObjectValueNode method)`, 34
`__init__(graphql.language.DefinitionNode method)`, 35
`__init__(graphql.language.DirectiveDefinitionNode method)`, 35
`__init__(graphql.language.DirectiveNode method)`, 35
`__init__(graphql.language.DocumentNode method)`, 36
`__init__(graphql.language.EnumTypeDefinitionNode method)`, 36
`__init__(graphql.language.EnumTypeExtensionNode method)`, 36
`__init__(graphql.language.EnumValueDefinitionNode method)`, 37
`__init__(graphql.language.EnumValueNode method)`, 37
`__init__(graphql.language.ExecutableDefinitionNode method)`, 37
`__init__(graphql.language.FieldDefinitionNode method)`, 38
`__init__(graphql.language.FieldNode method)`, 38
`__init__(graphql.language.FloatValueNode method)`, 38
`__init__(graphql.language.FragmentDefinitionNode method)`, 39
`__init__(graphql.language.FragmentSpreadNode method)`, 39
`__init__(graphql.language.InlineFragmentNode method)`, 39
`__init__(graphql.language.InputObjectTypeDefinitionNode method)`, 40
`__init__(graphql.language.InputObjectTypeExtensionNode method)`, 40
`__init__(graphql.language.InputValueDefinitionNode method)`, 40
`__init__(graphql.language.IntValueNode method)`, 41
`__init__(graphql.language.InterfaceTypeDefinitionNode method)`, 41
`__init__(graphql.language.InterfaceTypeExtensionNode method)`, 41
`__init__(graphql.language.Lexer method)`, 52
`__init__(graphql.language.ListTypeNode method)`, 42
`__init__(graphql.language.ListValueNode method)`, 42
`__init__(graphql.language.Location method)`, 32
`__init__(graphql.language.NameNode method)`, 42
`__init__(graphql.language.NamedTypeNode method)`, 43
`__init__(graphql.language.Node method)`, 32
`__init__(graphql.language.NonNullTypeNode method)`, 43
`__init__(graphql.language.NullValueNode method)`, 43
`__init__(graphql.language.ObjectFieldNode method)`, 43
`__init__(graphql.language.ObjectTypeDefinitionNode`

`method), 44`
`__init__(graphql.language.ObjectTypeExtensionNode
method), 44`
`__init__(graphql.language.ObjectValueNode
method), 44`
`__init__(graphql.language.OperationDefinitionNode
method), 45`
`__init__(graphql.language.OperationTypeDefinitionNode
method), 45`
`__init__(graphql.language.ParallelVisitor method),
59`
`__init__(graphql.language.ScalarTypeDefinitionNode
method), 46`
`__init__(graphql.language.ScalarTypeExtensionNode
method), 46`
`__init__(graphql.language.SchemaDefinitionNode
method), 46`
`__init__(graphql.language.SchemaExtensionNode
method), 47`
`__init__(graphql.language.SelectionNode method),
47`
`__init__(graphql.language.SelectionSetNode
method), 47`
`__init__(graphql.language.Source method), 56`
`__init__(graphql.language.SourceLocation
method), 54`
`__init__(graphql.language.StringValueNode
method), 47`
`__init__(graphql.language.Token method), 54`
`__init__(graphql.language.TypeDefinitionNode
method), 48`
`__init__(graphql.language.TypeExtensionNode
method), 48`
`__init__(graphql.language.TypeNode method), 48`
`__init__(graphql.language.TypeSystemDefinitionNode
method), 49`
`__init__(graphql.language.UnionTypeDefinitionNode
method), 49`
`__init__(graphql.language.UnionTypeExtensionNode
method), 49`
`__init__(graphql.language.ValueNode method), 50`
`__init__(graphql.language.VariableDefinitionNode
method), 50`
`__init__(graphql.language.VariableNode method),
50`
`__init__(graphql.language.Visitor method), 58`
`__init__(graphql.pyutils.Path method), 61`
`__init__(graphql.pyutils.SimplePubSub method), 61`
`__init__(graphql.pyutils.SimplePubSubIterator
method), 62`
`__init__(graphql.type.GraphQLArgument method),
73`
`__init__(graphql.type.GraphQLDirective method),
79`
`__init__(graphql.type.GraphQLEnumType method),
65`
`__init__(graphql.type.GraphQLEnumValue
method), 73`
`__init__(graphql.type.GraphQLField method), 74`
`__init__(graphql.type.GraphQLInputField method),
75`
`__init__(graphql.type.GraphQLInputObjectType
method), 66`
`__init__(graphql.type.GraphQLInterfaceType
method), 67`
`__init__(graphql.type.GraphQLList method), 72`
`__init__(graphql.type.GraphQLNamedType
method), 76`
`__init__(graphql.type.GraphQLNonNull method),
72`
`__init__(graphql.type.GraphQLObjectType
method), 68`
`__init__(graphql.type.GraphQLResolveInfo
method), 77`
`__init__(graphql.type.GraphQLScalarType
method), 70`
`__init__(graphql.type.GraphQLSchema method), 82`
`__init__(graphql.type.GraphQLType method), 76`
`__init__(graphql.type.GraphQLUnionType method),
71`
`__init__(graphql.type.GraphQLWrappingType
method), 76`
`__init__(graphql.utilities.BreakingChange method),
93`
`__init__(graphql.utilities.DangerousChange
method), 93`
`__init__(graphql.utilities.TypeInfo method), 88`
`__init__(graphql.utilities.TypeInfoVisitor method),
90`
`__init__(graphql.validation.ASTValidationContext
method), 95`
`__init__(graphql.validation.ASTValidationRule
method), 95`
`__init__(graphql.validation.ExecutableDefinitionsRule
method), 99`
`__init__(graphql.validation.FieldsOnCorrectTypeRule
method), 99`
`__init__(graphql.validation.FragmentsOnCompositeTypesRule
method), 100`
`__init__(graphql.validation.KnownArgumentNamesRule
method), 101`
`__init__(graphql.validation.KnownDirectivesRule
method), 101`
`__init__(graphql.validation.KnownFragmentNamesRule
method), 102`
`__init__(graphql.validation.KnownTypeNamesRule
method), 103`
`__init__(graphql.validation.LoneAnonymousOperationRule`

method), 103
`__init__(graphql.validation.LoneSchemaDefinitionRule __init__(method), 117`
`__init__(graphql.validation.NoFragmentCyclesRule __init__(method), 104`
`__init__(graphql.validation.NoUndefinedVariablesRule __init__(method), 105`
`__init__(graphql.validation.NoUnusedFragmentsRule __init__(method), 106`
`__init__(graphql.validation.NoUnusedVariablesRule __init__(method), 106`
`__init__(graphql.validation.OverlappingFieldsCanBeMergedRule __init__(method), 107`
`__init__(graphql.validation.PossibleFragmentSpreadsRule __init__(method), 108`
`__init__(graphql.validation.PossibleTypeExtensionsRule __init__(method), 122`
`__init__(graphql.validation.ProvidedRequiredArgumentsRule __init__(method), 109`
`__init__(graphql.validation(SDLValidationContext __init__(method), 96`
`__init__(graphql.validation(SDLValidationRule __init__(method), 96`
`__init__(graphql.validation.ScalarLeafsRule __init__(method), 109`
`__init__(graphql.validation.SingleFieldSubscriptionsRule __init__(method), 110`
`__init__(graphql.validation.UniqueArgumentDefinitionNamesRule __init__(method), 121`
`__init__(graphql.validation.UniqueArgumentNamesRule __init__(method), 110`
`__init__(graphql.validation.UniqueDirectiveNamesRule __init__(method), 122`
`__init__(graphql.validation.UniqueDirectivesPerLocationRule __init__(method), 111`
`__init__(graphql.validation.UniqueEnumValueNamesRule __init__(method), 119`
`__init__(graphql.validation.UniqueFieldDefinitionNamesRule __init__(method), 120`
`__init__(graphql.validation.UniqueFragmentNamesRule __init__(method), 112`
`__init__(graphql.validation.UniqueInputFieldNamesRule __init__(method), 113`
`__init__(graphql.validation.UniqueOperationNamesRule __init__(method), 113`
`__init__(graphql.validation.UniqueOperationTypesRule __init__(method), 117`
`__init__(graphql.validation.UniqueTypeNamesRule __init__(method), 118`
`__init__(graphql.validation.UniqueVariableNamesRule __init__(method), 114`
`__init__(graphql.validation.ValidationContext __init__(method), 97`
`__init__(graphql.validation.ValidationRule __init__(method), 98`
`method), 115`
`__init__(graphql.validation.ValuesOfCorrectTypeRule __init__(method), 116`
`method), 116`
`__init__(graphql.validation.VariablesAreInputTypesRule __init__(method), 116`
`method), 116`
A
`aclose()`
`(graphql.execution.MapAsyncIterator method), 30`
`acloseRule()`
`(graphql.pyutils.SimplePubSubIterator method), 62`
`add_key()`
`(graphql.pyutils.Path method), 61`
`advance()`
`(graphql.language.Lexer method), 52`
`alias`
`(graphql.language.FieldNode attribute), 38`
`AMP`
`(graphql.language.TokenKind attribute), 53`
`ARG_CHANGED_KIND`
`(graphql.utilities.BreakingChangeType attribute), 93`
`ARG_DEFAULT_VALUE_CHANGE`
`(graphql.utilities.DangerousChangeType attribute), 94`
`ARG_REMOVED`
`(graphql.utilities.BreakingChangeType attribute), 93`
`args`
`(graphql.error.GraphQLError attribute), 21`
`args`
`(graphql.error.GraphQLSyntaxError attribute), 22`
`args`
`(graphql.type.GraphQLDirective attribute), 79`
`argsRule`
`(graphql.type.GraphQLField attribute), 74`
`ARGUMENT_DEFINITION`
`(graphql.language.DirectiveLocation attribute), 51`
`ArgumentNode`
`(class in graphql.language), 32`
`arguments`
`(graphql.language.ConstDirectiveNode attribute), 33`
`arguments`
`(graphql.language.DirectiveDefinitionNode attribute), 35`
`arguments`
`(graphql.language.DirectiveNode attribute), 35`
`arguments`
`(graphql.language.FieldDefinitionNode attribute), 38`
`arguments`
`(graphql.language.FieldNode attribute), 38`
`as_list()`
`(graphql.pyutils.Path method), 61`
`assert_abstract_type()`
`(in module graphql.type), 63`
`assert_composite_type()`
`(in module graphql.type), 63`
`assert_enum_type()`
`(in module graphql.type), 63`
`assert_enum_value_name()`
`(in module graphql.type), 84`
`assert_input_object_type()`
`(in module graphql.type), 63`
`assert_input_type()`
`(in module graphql.type), 63`
`assert_interface_type()`
`(in module graphql.type), 63`
`assert_leaf_type()`
`(in module graphql.type), 63`

assert_list_type() (in module `graphql.type`), 63
assert_name() (in module `graphql.type`), 84
assert_named_type() (in module `graphql.type`), 63
assert_non_null_type() (in module `graphql.type`), 63
assert_nullable_type() (in module `graphql.type`), 63
assert_object_type() (in module `graphql.type`), 63
assert_output_type() (in module `graphql.type`), 63
assert_scalar_type() (in module `graphql.type`), 63
assert_type() (in module `graphql.type`), 63
assert_union_type() (in module `graphql.type`), 63
assert_valid_name() (in module `graphql.utilities`), 92
assert_valid_schema() (in module `graphql.type`), 83
assert_wrapping_type() (in module `graphql.type`), 64
ast_from_value() (in module `graphql.utilities`), 87
ast_node (`graphql.type.GraphQLArgument` attribute), 73
ast_node (`graphql.type.GraphQLDirective` attribute), 79
ast_node (`graphql.type.GraphQLEnumType` attribute), 65
ast_node (`graphql.type.GraphQLEnumValue` attribute), 74
ast_node (`graphql.type.GraphQLField` attribute), 74
ast_node (`graphql.type.GraphQLInputField` attribute), 75
ast_node (`graphql.type.GraphQLInputObjectType` attribute), 66
ast_node (`graphql.type.GraphQLInterfaceType` attribute), 67
ast_node (`graphql.type.GraphQLNamedType` attribute), 76
ast_node (`graphql.type.GraphQLObjectType` attribute), 69
ast_node (`graphql.type.GraphQLScalarType` attribute), 70
ast_node (`graphql.type.GraphQLSchema` attribute), 82
ast_node (`graphql.type.GraphQLUnionType` attribute), 71
ast_to_dict() (in module `graphql.utilities`), 86
ASTValidationContext (class in `graphql.validation`), 94
ASTValidationRule (class in `graphql.validation`), 95
AT (`graphql.language.TokenKind` attribute), 53
athrow() (`graphql.execution.MapAsyncIterator` method), 30
AwaitableOrValue (in module `graphql.pyutils`), 60

B

BANG (`graphql.language.TokenKind` attribute), 53
block (`graphql.language.StringValueNode` attribute), 47
BLOCK_STRING (`graphql.language.TokenKind` attribute), 53
body (`graphql.language.Source` attribute), 57
BooleanValueNode (class in `graphql.language`), 33
BRACE_L (`graphql.language.TokenKind` attribute), 53
BRACE_R (`graphql.language.TokenKind` attribute), 53
BRACKET_L (`graphql.language.TokenKind` attribute), 53
BRACKET_R (`graphql.language.TokenKind` attribute), 53
BREAK (`graphql.language.ParallelVisitor` attribute), 58
BREAK (`graphql.language.Visitor` attribute), 58
BREAK (`graphql.language.visitor.VisitorActionEnum` attribute), 59
BREAK (`graphql.utilities.TypeInfoVisitor` attribute), 89
BREAK (`graphql.validation.ASTValidationRule` attribute), 95
BREAK (`graphql.validation.ExecutableDefinitionsRule` attribute), 98
BREAK (`graphql.validation.FieldsOnCorrectTypeRule` attribute), 99
BREAK (`graphql.validation.FragmentsOnCompositeTypesRule` attribute), 100
BREAK (`graphql.validation.KnownArgumentNamesRule` attribute), 100
BREAK (`graphql.validation.KnownDirectivesRule` attribute), 101
BREAK (`graphql.validation.KnownFragmentNamesRule` attribute), 102
BREAK (`graphql.validation.KnownTypeNamesRule` attribute), 103
BREAK (`graphql.validation.LoneAnonymousOperationRule` attribute), 103
BREAK (`graphql.validation.LoneSchemaDefinitionRule` attribute), 117
BREAK (`graphql.validation.NoFragmentCyclesRule` attribute), 104
BREAK (`graphql.validation.NoUndefinedVariablesRule` attribute), 105
BREAK (`graphql.validation.NoUnusedFragmentsRule` attribute), 105
BREAK (`graphql.validation.NoUnusedVariablesRule` attribute), 106
BREAK (`graphql.validation.OverlappingFieldsCanBeMergedRule` attribute), 107
BREAK (`graphql.validation.PossibleFragmentSpreadsRule` attribute), 108
BREAK (`graphql.validation.PossibleTypeExtensionsRule` attribute), 122
BREAK (`graphql.validation.ProvidedRequiredArgumentsRule` attribute), 108
BREAK (`graphql.validation.ScalarLeafsRule` attribute), 109
BREAK (`graphql.validation(SDLValidationRule` attribute), 96
BREAK (`graphql.validation.SingleFieldSubscriptionsRule` attribute), 110
BREAK (`graphql.validation.UniqueArgumentDefinitionNamesRule` attribute), 121
BREAK (`graphql.validation.UniqueArgumentNamesRule` attribute), 110

BREAK (*graphql.validation.UniqueDirectiveNamesRule attribute*), 122
 BREAK (*graphql.validation.UniqueDirectivesPerLocationRule attribute*), 111
 BREAK (*graphql.validation.UniqueEnumValueNamesRule attribute*), 119
 BREAK (*graphql.validation.UniqueFieldDefinitionNamesRule attribute*), 120
 BREAK (*graphql.validation.UniqueFragmentNamesRule attribute*), 112
 BREAK (*graphql.validation.UniqueInputFieldNamesRule attribute*), 112
 BREAK (*graphql.validation.UniqueOperationNamesRule attribute*), 113
 BREAK (*graphql.validation.UniqueOperationTypesRule attribute*), 117
 BREAK (*graphql.validation.UniqueTypeNamesRule attribute*), 118
 BREAK (*graphql.validation.UniqueVariableNamesRule attribute*), 114
 BREAK (*graphql.validation.ValidationRule attribute*), 98
 BREAK (*graphql.validation.ValuesOfCorrectTypeRule attribute*), 114
 BREAK (*graphql.validation.VariablesAreInputTypesRule attribute*), 115
 BREAK (*graphql.validation.VariablesInAllowedPositionRule attribute*), 116
 BREAK (*in module graphql.language*), 59
BreakingChange (*class in graphql.utilities*), 93
BreakingChangeType (*class in graphql.utilities*), 93
build() (*graphql.execution.ExecutionContext class method*), 25
build_ast_schema() (*in module graphql.utilities*), 85
build_client_schema() (*in module graphql.utilities*), 85
build_resolve_info() (*graphql.execution.ExecutionContext method*), 26
build_response() (*graphql.execution.ExecutionContext static method*), 26
build_schema() (*in module graphql.utilities*), 85

C

cached_property() (*in module graphql.pyutils*), 60
camel_to_snake() (*in module graphql.pyutils*), 60
check_arg_uniqueness() (*graphql.validation.UniqueArgumentDefinitionNamesRule method*), 121
check_arg_uniqueness() (*graphql.validation.UniqueArgumentNamesRule method*), 111
check_arg_uniqueness_per_field() (*graphql.validation.UniqueArgumentDefinitionNamesRule method*), 121
check_extension() (*graphql.validation.PossibleTypeExtensionsRule method*), 122
check_field_uniqueness() (*graphql.validation.UniqueFieldDefinitionNamesRule method*), 120
check_operation_types() (*graphql.validation.UniqueOperationTypesRule method*), 117
check_type_name() (*graphql.validation.UniqueTypeNamesRule method*), 118
check_value_uniqueness() (*graphql.validation.UniqueEnumValueNamesRule method*), 119
coerce_input_value() (*in module graphql.utilities*), 90
collect_subfields() (*graphql.execution.ExecutionContext method*), 26
COLON (*graphql.language.TokenKind attribute*), 53
column (*graphql.language.FormattedSourceLocation attribute*), 55
column (*graphql.language.SourceLocation attribute*), 54
column (*graphql.language.Token attribute*), 54
COMMENT (*graphql.language.TokenKind attribute*), 53
complete_abstract_value() (*graphql.execution.ExecutionContext method*), 26
complete_leaf_value() (*graphql.execution.ExecutionContext static method*), 26
complete_list_value() (*graphql.execution.ExecutionContext method*), 27
complete_object_value() (*graphql.execution.ExecutionContext method*), 27
complete_value() (*graphql.execution.ExecutionContext method*), 27
concat_ast() (*in module graphql.utilities*), 90
ConstArgumentNode (*class in graphql.language*), 33
ConstDirectiveNode (*class in graphql.language*), 33
ConstListValueNode (*class in graphql.language*), 34
ConstObjectFieldNode (*class in graphql.language*), 34
ConstObjectValueNode (*class in graphql.language*), 34
ConstValueNode (*in module graphql.language*), 34
context (*graphql.type.GraphQLResolveInfo attribute*), 77
context (*graphql.validation.ASTValidationRule attribute*), 95
context (*graphql.validation.ExecutableDefinitionsRule attribute*), 99
context (*graphql.validation.FieldsOnCorrectTypeRule attribute*), 99
context (*graphql.validation.FragmentsOnCompositeTypesRule*)

attribute), 100
context (graphql.validation.KnownArgumentNamesRule attribute), 101
context (graphql.validation.KnownDirectivesRule attribute), 101
context (graphql.validation.KnownFragmentNamesRule attribute), 102
context (graphql.validation.KnownTypeNamesRule attribute), 103
context (graphql.validation.LoneAnonymousOperationRule attribute), 103
context (graphql.validation.LoneSchemaDefinitionRule attribute), 117
context (graphql.validation.NoFragmentCyclesRule attribute), 104
context (graphql.validation.NoUndefinedVariablesRule attribute), 105
context (graphql.validation.NoUnusedFragmentsRule attribute), 106
context (graphql.validation.NoUnusedVariablesRule attribute), 106
context (graphql.validation.OverlappingFieldsCanBeMergedRule attribute), 107
context (graphql.validation.PossibleFragmentSpreadsRule attribute), 108
context (graphql.validation.PossibleTypeExtensionsRule attribute), 122
context (graphql.validation.ProvidedRequiredArgumentsRule attribute), 109
context (graphql.validation.ScalarLeafsRule attribute), 109
context (graphql.validation(SDLValidationRule attribute), 96
context (graphql.validation.SingleFieldSubscriptionsRule attribute), 110
context (graphql.validation.UniqueArgumentDefinitionNamesRule attribute), 121
context (graphql.validation.UniqueArgumentNamesRule attribute), 111
context (graphql.validation.UniqueDirectiveNamesRule attribute), 122
context (graphql.validation.UniqueDirectivesPerLocationRule attribute), 111
context (graphql.validation.UniqueEnumValueNamesRule attribute), 119
context (graphql.validation.UniqueFieldDefinitionNamesRule attribute), 120
context (graphql.validation.UniqueFragmentNamesRule attribute), 112
context (graphql.validation.UniqueInputFieldNamesRule attribute), 113
context (graphql.validation.UniqueOperationNamesRule attribute), 113
context (graphql.validation.UniqueOperationTypesRule attribute), 118
context (graphql.validation.UniqueTypeNamesRule attribute), 118
context (graphql.validation.UniqueVariableNamesRule attribute), 114
context (graphql.validation.ValidationRule attribute), 98
context (graphql.validation.ValuesOfCorrectTypeRule attribute), 115
context (graphql.validation.VariablesAreInputTypesRule attribute), 116
context (graphql.validation.VariablesInAllowedPositionRule attribute), 116
context_value (graphql.execution.ExecutionContext attribute), 27
count() (graphql.language.SourceLocation method), 54
count() (graphql.pyutils.Path method), 61
count() (graphql.type.GraphQLResolveInfo method), 77
count() (graphql.utilities.BreakingChange method), 93
count() (graphql.utilities.DangerousChange method), 93
create_event_stream() (in module graphql.execution), 30
create_token() (graphql.language.Lexer method), 52
D
DangerousChange (class in graphql.utilities), 93
DangerousChangeType (class in graphql.utilities), 94
data (graphql.execution.ExecutionResult attribute), 29
data (graphql.execution.FormattedExecutionResult attribute), 29
DEFAULT_DEPRECATED_REASON (in module graphql.type), 79
default_field_resolver() (in module graphql.execution), 24
default_type_resolver() (in module graphql.execution), 25
default_value (graphql.language.InputValueDefinitionNode attribute), 40
default_value (graphql.language.VariableDefinitionNode attribute), 50
default_value (graphql.type.GraphQLArgument attribute), 73
default_value (graphql.type.GraphQLInputField attribute), 75
DefinitionNode (class in graphql.language), 35
definitions (graphql.language.DocumentNode attribute), 36
deprecation_reason (graphql.type.GraphQLArgument attribute), 73
deprecation_reason (graphql.type.GraphQLEnumValue attribute), 74
deprecation_reason (graphql.type.GraphQLField attribute), 74

```

deprecation_reason(graphql.type.GraphQLInputField description      (graphql.utilities.DangerousChange
attribute), 75                                         attribute), 94
desc (graphql.language.Token property), 54           detect_cycle_recursive()
description(graphql.language.DirectiveDefinitionNode   (graphql.validation.NoFragmentCyclesRule
attribute), 35                                         method), 104
description(graphql.language.EnumTypeDefinitionNode did_you_mean() (in module graphql.pyutils), 60
attribute), 36                                         DIRECTIVE_ARG_REMOVED
description(graphql.language.EnumValueDefinitionNode   (graphql.utilities.BreakingChangeType      at-
attribute), 37                                         tribute), 93
description (graphql.language.FieldDefinitionNode    DIRECTIVE_LOCATION_REMOVED
attribute), 38                                         (graphql.utilities.BreakingChangeType      at-
description(graphql.language.InputObjectTypeDefinitionNode   (graphql.utilities.BreakingChangeType      at-
attribute), 40                                         tribute), 93
description(graphql.language.InputValueDefinitionNode   DIRECTIVE_REMOVED (graphql.utilities.BreakingChangeType
attribute), 40                                         attribute), 93
description(graphql.language.InterfaceTypeDefinitionNode (graphql.utilities.BreakingChangeType      at-
attribute), 41                                         tribute), 93
description(graphql.language.ObjectTypeDefinitionNode  DirectiveDefinitionNode      (class      in
attribute), 44                                         graphql.language), 35
description(graphql.language.ScalarTypeDefinitionNode  DirectiveLocation (class in graphql.language), 51
attribute), 46                                         DirectiveNode (class in graphql.language), 35
description (graphql.language.SchemaDefinitionNode    directives(graphql.language.EnumTypeDefinitionNode
attribute), 46                                         attribute), 36
description(graphql.language.TypeDefinitionNode        directives(graphql.language.EnumTypeExtensionNode
attribute), 48                                         attribute), 36
description(graphql.language.UnionTypeDefinitionNode  directives(graphql.language.EnumValueDefinitionNode
attribute), 49                                         attribute), 37
description (graphql.type.GraphQLArgument      at- directives(graphql.language.ExecutableDefinitionNode
attribute), 73                                         attribute), 37
description (graphql.type.GraphQLDirective     at- directives(graphql.language.FieldDefinitionNode attribute),
attribute), 79                                         attribute), 38
description (graphql.type.GraphQLEnumType      at- directives(graphql.language.FieldNode attribute), 38
attribute), 65                                         directives(graphql.language.FragmentDefinitionNode
attribute), 39
description (graphql.type.GraphQLEnumValue     directives(graphql.language.FragmentSpreadNode
attribute), 74                                         attribute), 39
description (graphql.type.GraphQLField attribute), 74
description (graphql.type.GraphQLInputField    directives(graphql.language.InlineFragmentNode
attribute), 75                                         attribute), 39
description (graphql.type.GraphQLInputObjectType directives(graphql.language.InputObjectTypeDefinitionNode
attribute), 66                                         attribute), 40
description (graphql.type.GraphQLInterfaceType  directives(graphql.language.InputObjectTypeExtensionNode
attribute), 67                                         attribute), 40
description (graphql.type.GraphQLNamedType      directives(graphql.language.InputValueDefinitionNode
attribute), 76                                         attribute), 41
description (graphql.type.GraphQLObjectType     directives(graphql.language.InterfaceTypeDefinitionNode
attribute), 69                                         attribute), 41
description (graphql.type.GraphQLScalarType    directives(graphql.language.InterfaceTypeExtensionNode
attribute), 70                                         attribute), 42
description (graphql.type.GraphQLSchema        directives(graphql.language.ObjectTypeDefinitionNode
attribute), 82                                         attribute), 44
description (graphql.type.GraphQLUnionType     directives(graphql.language.ObjectTypeExtensionNode
attribute), 71                                         attribute), 44
description (graphql.utilities.BreakingChange  directives(graphql.language.OperationDefinitionNode
attribute), 93                                         attribute), 45

```

`directives(graphql.language.ScalarTypeDefinitionNode attribute), 46` `enter_directive() (graphql.utilities.TypeInfo method), 88`
`directives(graphql.language.ScalarTypeExtensionNode attribute), 46` `enter_directive() (graphql.validation.KnownArgumentNamesRule method), 101`
`directives(graphql.language.SchemaDefinitionNode attribute), 46` `enter_directive() (graphql.validation.KnownDirectivesRule method), 101`
`directives(graphql.language.SchemaExtensionNode attribute), 47` `enter_directive() (graphql.validation.UniqueArgumentNamesRule method), 111`
`directives(graphql.language.SelectionNode attribute), 47` `enter_directive_definition() (graphql.validation.UniqueArgumentDefinitionNamesRule method), 121`
`directives(graphql.language.TypeDefinitionNode attribute), 48` `enter_directive_definition() (graphql.validation.UniqueDirectiveNamesRule method), 122`
`directives(graphql.language.TypeExtensionNode attribute), 48`
`directives(graphql.language.UnionTypeDefinitionNode attribute), 49` `enter_document() (graphql.validation.ExecutableDefinitionsRule method), 99`
`directives(graphql.language.UnionTypeExtensionNode attribute), 49` `enter_document() (graphql.validation.LoneAnonymousOperationRule method), 103`
`directives(graphql.language.VariableDefinitionNode attribute), 50` `enter_enum_type_definition() (graphql.validation.UniqueEnumValueNamesRule method), 119`
`directives(graphql.type.GraphQLSchema attribute), 82`
`do_types_overlap() (in module graphql.utilities), 92`
`document(graphql.validation.ASTValidationContext attribute), 95`
`document(graphql.validation(SDLValidationContext attribute), 96`
`document(graphql.validation.ValidationContext attribute), 97`
`DocumentNode (class in graphql.language), 36`
`DOLLAR(graphql.language.TokenKind attribute), 53`

E

`emit() (graphql.pyutils.SimplePubSub method), 61`
`empty_queue() (graphql.pyutils.SimplePubSubIterator method), 62`
`end(graphql.language.Location attribute), 32`
`end(graphql.language.Token attribute), 54`
`end_token(graphql.language.Location attribute), 32`
`ensure_valid_runtime_type() (graphql.execution.ExecutionContext method), 27`
`enter() (graphql.utilities.TypeInfo method), 88`
`enter() (graphql.utilities.TypeInfoVisitor method), 90`
`enter() (graphql.validation.UniqueDirectivesPerLocationRule method), 111`
`enter_argument() (graphql.utilities.TypeInfo method), 88`
`enter_argument() (graphql.validation.KnownArgumentNamesRule method), 101`
`enter_boolean_value() (graphql.validation.ValuesOfCorrectTypeRule method), 115`
`enter_field() (graphql.utilities.TypeInfo method), 88`
`enter_field() (graphql.validation.FieldsOnCorrectTypeRule method), 99`
`enter_field() (graphql.validation.ScalarLeafsRule method), 109`
`enter_field() (graphql.validation.UniqueArgumentNamesRule method), 111`
`enter_float_value() (graphql.validation.ValuesOfCorrectTypeRule method), 115`
`enter_fragment_definition() (graphql.utilities.TypeInfo method), 88`
`enter_fragment_definition() (graphql.validation.FragmentsOnCompositeTypesRule method), 104`
`enter_fragment_definition() (graphql.validation.NoFragmentCyclesRule method), 104`
`enter_fragment_definition() (graphql.validation.NoUnusedFragmentsRule method), 104`

```

    method), 106
enter_fragment_definition()
  (graphql.validation.UniqueFragmentNamesRule
    method), 112
enter_fragment_definition()
  (graphql.validation.UniqueOperationNamesRule
    static method), 113
enter_fragment_spread()
  (graphql.validation.KnownFragmentNamesRule
    method), 102
enter_fragment_spread()
  (graphql.validation.PossibleFragmentSpreadsRule
    method), 108
enter_inline_fragment() (graphql.utilities.TypeInfo
  method), 88
enter_inline_fragment()
  (graphql.validation.FragmentsOnCompositeTypesRule
    method), 100
enter_inline_fragment()
  (graphql.validation.PossibleFragmentSpreadsRule
    method), 108
enter_input_object_type_definition()
  (graphql.validation.UniqueFieldDefinitionNamesRule
    method), 120
enter_input_object_type_definition()
  (graphql.validation.UniqueTypeNamesRule
    method), 118
enter_input_object_type_extension()
  (graphql.validation.PossibleTypeExtensionsRule
    method), 122
enter_input_object_type_extension()
  (graphql.validation.UniqueFieldDefinitionNamesRule
    method), 120
enter_int_value() (graphql.validation.ValuesOfCorrectType
  method), 115
enter_interface_type_definition()
  (graphql.validation.UniqueArgumentDefinitionNamesRule
    method), 121
enter_interface_type_definition()
  (graphql.validation.UniqueFieldDefinitionNamesRule
    method), 120
enter_interface_type_definition()
  (graphql.validation.UniqueTypeNamesRule
    method), 118
enter_interface_type_extension()
  (graphql.validation.PossibleTypeExtensionsRule
    method), 123
enter_interface_type_extension()
  (graphql.validation.UniqueArgumentDefinitionNamesRule
    method), 121
enter_interface_type_extension()
  (graphql.validation.UniqueFieldDefinitionNamesRule
    method), 120
enter_leave_map (graphql.language.ParallelVisitor at-
    tribute), 59
enter_leave_map (graphql.language.Visitor attribute),
  58
enter_leave_map (graphql.utilities.TypeInfoVisitor at-
  tribute), 90
enter_leave_map (graphql.validation.ASTValidationRule
  attribute), 95
enter_leave_map (graphql.validation.ExecutableDefinitionsRule
  attribute), 99
enter_leave_map (graphql.validation.FieldsOnCorrectTypeRule
  attribute), 99
enter_leave_map (graphql.validation.FragmentsOnCompositeTypesRule
  attribute), 100
enter_leave_map (graphql.validation.KnownArgumentNamesRule
  attribute), 101
enter_leave_map (graphql.validation.KnownDirectivesRule
  attribute), 101
enter_leave_map (graphql.validation.KnownFragmentNamesRule
  attribute), 102
enter_leave_map (graphql.validation.KnownTypeNamesRule
  attribute), 103
enter_leave_map (graphql.validation.LoneAnonymousOperationRule
  attribute), 103
enter_leave_map (graphql.validation.LoneSchemaDefinitionRule
  attribute), 117
enter_leave_map (graphql.validation.NoFragmentCyclesRule
  attribute), 104
enter_leave_map (graphql.validation.NoUndefinedVariablesRule
  attribute), 105
enter_leave_map (graphql.validation.NoUnusedFragmentsRule
  attribute), 106
enter_leave_map (graphql.validation.NoUnusedVariablesRule
  attribute), 106
enter_leave_map (graphql.validation.OverlappingFieldsCanBeMergedRule
  attribute), 107
enter_leave_map (graphql.validation.PossibleFragmentSpreadsRule
  attribute), 108
enter_leave_map (graphql.validation.PossibleTypeExtensionsRule
  attribute), 123
enter_leave_map (graphql.validation.ProvidedRequiredArgumentsRule
  attribute), 109
enter_leave_map (graphql.validation.ScalarLeafsRule
  attribute), 109
enter_leave_map (graphql.validation.SDKValidationRule
  attribute), 96
enter_leave_map (graphql.validation.SingleFieldSubscriptionsRule
  attribute), 110
enter_leave_map (graphql.validation.UniqueArgumentDefinitionNamesRule
  attribute), 121
enter_leave_map (graphql.validation.UniqueArgumentNamesRule
  attribute), 111
enter_leave_map (graphql.validation.UniqueDirectiveNamesRule
  attribute), 122
enter_leave_map (graphql.validation.UniqueDirectivesPerLocationRule
  attribute), 137

```

```
        attribute), 111
enter_leave_map(graphql.validation.UniqueEnumValueNamesRule method), 121
        attribute), 119
                enter_object_type_extension()
enter_leave_map(graphql.validation.UniqueFieldDefinitionNamesRule method), 120
        attribute), 120
enter_leave_map(graphql.validation.UniqueFragmentNameRule method), 121
        attribute), 112
                enter_object_value()
enter_leave_map(graphql.validation.UniqueInputFieldNamesRule method), 113
        attribute), 113
                enter_object_value()
enter_leave_map(graphql.validation.UniqueOperationNamesRule method), 115
        attribute), 113
                enter_operation_definition()
enter_leave_map(graphql.validation.UniqueOperationTypeRule method), 88
        attribute), 118
enter_leave_map(graphql.validation.UniqueTypeNamesRule method), 104
        attribute), 118
                enter_operation_definition()
enter_leave_map(graphql.validation.UniqueVariableNamesRule method), 104
        attribute), 114
                enter_operation_definition()
enter_leave_map(graphql.validation.ValidationRule method), 104
        attribute), 98
                enter_operation_definition()
enter_leave_map(graphql.validation.ValuesOfCorrectTypeRule method), 104
        attribute), 115
                enter_operation_definition()
enter_leave_map(graphql.validation.VariablesAreInputTypesRule method), 105
        attribute), 116
                enter_operation_definition()
enter_leave_map(graphql.validation.VariablesInAllowedPositionRule method), 106
        attribute), 116
                enter_operation_definition()
enter_list_value() (graphql.utilities.TypeInfo method), 88
        enter_operation_definition()
enter_list_value() (graphql.validation.ValuesOfCorrectTypeRule method), 106
        method), 115
                enter_operation_definition()
enter_named_type() (graphql.validation.KnownTypeNamesRule method), 103
        enter_operation_definition()
enter_null_value() (graphql.validation.ValuesOfCorrectTypeRule method), 115
        enter_operation_definition()
enter_object_field() (graphql.utilities.TypeInfo method), 88
        enter_operation_definition()
enter_object_field() (graphql.validation.UniqueInputFieldNamesRule method), 113
        enter_operation_definition()
enter_object_field() (graphql.validation.ValuesOfCorrectTypeRule method), 115
        enter_operation_definition()
enter_object_type_definition() (graphql.validation.UniqueArgumentDefinitionNamesRule method), 121
        enter_scalar_type_definition()
enter_object_type_definition() (graphql.validation.UniqueFieldDefinitionNamesRule method), 120
        enter_scalar_type_extension()
enter_object_type_definition() (graphql.validation.UniqueTypeNamesRule method), 119
        enter_schema_definition()
enter_object_type_extension() (graphql.validation.PossibleTypeExtensionsRule method), 123
        enter_schema_definition()
enter_object_type_extension() (graphql.validation.UniqueOperationTypesRule
```

method), 118
enter_schema_extension()
(graphql.validation.UniqueOperationTypesRule method), 118
enter_selection_set() (*graphql.utilities.TypeInfo method*), 88
enter_selection_set()
(graphql.validation.OverlappingFieldsCanBeMergedRule method), 107
enter_string_value()
(graphql.validation.ValuesOfCorrectTypeRule method), 115
enter_union_type_definition()
(graphql.validation.UniqueTypeNamesRule method), 119
enter_union_type_extension()
(graphql.validation.PossibleTypeExtensionsRule method), 123
enter_variable_definition()
(graphql.utilities.TypeInfo method), 88
enter_variable_definition()
(graphql.validation.NoUndefinedVariablesRule method), 105
enter_variable_definition()
(graphql.validation.NoUnusedVariablesRule method), 106
enter_variable_definition()
(graphql.validation.VariablesAreInputTypesRule method), 116
enter_variable_definition()
(graphql.validation.VariablesInAllowedPositionRule method), 116
ENUM (*graphql.language.DirectiveLocation attribute*), 51
ENUM (*graphql.type.TypeKind attribute*), 79
ENUM_VALUE (*graphql.language.DirectiveLocation attribute*), 51
EnumTypeDefinitionNode (*class in graphql.language*), 36
EnumTypeExtensionNode (*class in graphql.language*), 36
EnumValueDefinitionNode (*class in graphql.language*), 37
EnumValueNode (*class in graphql.language*), 37
EOF (*graphql.language.TokenKind attribute*), 53
EQUALS (*graphql.language.TokenKind attribute*), 53
errors (*graphql.execution.ExecutionContext attribute*), 28
errors (*graphql.execution.ExecutionResult attribute*), 29
errors (*graphql.execution.FormattedExecutionResult attribute*), 29
ExecutableDefinitionNode (*class in graphql.language*), 37
ExecutableDefinitionsRule (*graphql.validation*), 98
execute() (*in module graphql.execution*), 24
execute_field() (*graphql.execution.ExecutionContext method*), 28
execute_fields() (*graphql.execution.ExecutionContext method*), 28
execute_fields_serially()
(graphql.execution.ExecutionContext method), 28
execute_operation()
(graphql.execution.ExecutionContext method), 28
execute_sync() (*in module graphql.execution*), 24
ExecutionContext (*class in graphql.execution*), 25
ExecutionResult (*class in graphql.execution*), 29
extend_schema() (*in module graphql.utilities*), 85
extension_ast_nodes
(graphql.type.GraphQLEnumType attribute), 65
extension_ast_nodes
(graphql.type.GraphQLInputObjectType attribute), 66
extension_ast_nodes
(graphql.type.GraphQLInterfaceType attribute), 67
extension_ast_nodes
(graphql.type.GraphQLNamedType attribute), 76
extension_ast_nodes
(graphql.type.GraphQLObjectType attribute), 69
extension_ast_nodes
(graphql.type.GraphQLScalarType attribute), 70
extension_ast_nodes (*graphql.type.GraphQLSchema attribute*), 82
extension_ast_nodes
(graphql.type.GraphQLUnionType attribute), 71
extensions (*graphql.error.GraphQLError attribute*), 21
extensions (*graphql.error.GraphQLFormattedError attribute*), 23
extensions (*graphql.error.GraphQLSyntaxError attribute*), 22
extensions (*graphql.execution.ExecutionResult attribute*), 29
extensions (*graphql.execution.FormattedExecutionResult attribute*), 29
extensions (*graphql.type.GraphQLArgument attribute*), 73
extensions (*graphql.type.GraphQLDirective attribute*), 79
extensions (*graphql.type.GraphQLEnumType attribute*), 65
extensions (*graphql.type.GraphQLEnumValue attribute*),

tribute), 74
extensions (*graphql.type.GraphQLField* attribute), 74
extensions (*graphql.type.GraphQLInputField* attribute), 75
extensions (*graphql.type.GraphQLInputObjectType* attribute), 66
extensions (*graphql.type.GraphQLInterfaceType* attribute), 67
extensions (*graphql.type.GraphQLNamedType* attribute), 76
extensions (*graphql.type.GraphQLObjectType* attribute), 69
extensions (*graphql.type.GraphQLScalarType* attribute), 70
extensions (*graphql.type.GraphQLSchema* attribute), 82
extensions (*graphql.type.GraphQLUnionType* attribute), 71

F

FIELD (*graphql.language.DirectiveLocation* attribute), 51
FIELD_CHANGED_KIND (*graphql.utilities.BreakingChangeType* attribute), 93
FIELD_DEFINITION (*graphql.language.DirectiveLocation* attribute), 51
field_name (*graphql.type.GraphQLResolveInfo* attribute), 77
field_nodes (*graphql.type.GraphQLResolveInfo* attribute), 77
FIELD_REMOVED (*graphql.utilities.BreakingChangeType* attribute), 93
field_resolver (*graphql.execution.ExecutionContext* attribute), 28
FieldDefinitionNode (class in *graphql.language*), 37
FieldNode (class in *graphql.language*), 38
fields (*graphql.language.ConstObjectValueNode* attribute), 34
fields (*graphql.language.InputObjectTypeDefinitionNode* attribute), 40
fields (*graphql.language.InputObjectTypeExtensionNode* attribute), 40
fields (*graphql.language.InterfaceTypeDefinitionNode* attribute), 41
fields (*graphql.language.InterfaceTypeExtensionNode* attribute), 42
fields (*graphql.language.ObjectTypeDefinitionNode* attribute), 44
fields (*graphql.language.ObjectTypeExtensionNode* attribute), 44
fields (*graphql.language.ObjectValueNode* attribute), 45
fields (*graphql.type.GraphQLInputObjectType* property), 66

fields (*graphql.type.GraphQLInterfaceType* property), 67
fields (*graphql.type.GraphQLObjectType* property), 69
FieldsOnCorrectTypeRule (class in *graphql.validation*), 99
find_breaking_changes() (in *graphql.utilities*), 92
find_dangerous_changes() (in *graphql.utilities*), 92
FLOAT (*graphql.language.TokenKind* attribute), 53
FloatValueNode (class in *graphql.language*), 38
formatted (*graphql.error.GraphQLError* property), 21
formatted (*graphql.error.GraphQLSyntaxError* property), 22
formatted (*graphql.execution.ExecutionResult* property), 29
formatted (*graphql.language.SourceLocation* property), 55
FormattedExecutionResult (class in *graphql.execution*), 29
FormattedSourceLocation (class in *graphql.language*), 55

FRAGMENT_DEFINITION (*graphql.language.DirectiveLocation* attribute), 51
FRAGMENT_SPREAD (*graphql.language.DirectiveLocation* attribute), 51
FragmentDefinitionNode (class in *graphql.language*), 39
fragments (*graphql.execution.ExecutionContext* attribute), 28
fragments (*graphql.type.GraphQLResolveInfo* attribute), 77
FragmentsOnCompositeTypesRule (class in *graphql.validation*), 100
FragmentSpreadNode (class in *graphql.language*), 39
FrozenError (class in *graphql.pyutils*), 61

G

get_argument() (*graphql.utilities.TypeInfo* method), 89
get_argument() (*graphql.validation.ValidationContext* method), 97
get_default_value() (*graphql.utilities.TypeInfo* method), 89
get_directive() (*graphql.type.GraphQLSchema* method), 82
get_directive() (*graphql.utilities.TypeInfo* method), 89
get_directive() (*graphql.validation.ValidationContext* method), 97
get_directive_values() (in *graphql.execution*), 31
get_enter_leave_for_kind() (*graphql.language.ParallelVisitor* method),

```

59
get_enter_leave_for_kind()
    (graphql.language.Visitor method), 58
get_enter_leave_for_kind()
    (graphql.utilities.TypeInfoVisitor method), 90
get_enter_leave_for_kind()
    (graphql.validation.ASTValidationRule method), 95
get_enter_leave_for_kind()
    (graphql.validation.ExecutableDefinitionsRule method), 99
get_enter_leave_for_kind()
    (graphql.validation.FieldsOnCorrectTypeRule method), 99
get_enter_leave_for_kind()
    (graphql.validation.FragmentsOnCompositeTypesRule method), 100
get_enter_leave_for_kind()
    (graphql.validation.KnownArgumentNamesRule method), 101
get_enter_leave_for_kind()
    (graphql.validation.KnownDirectivesRule method), 102
get_enter_leave_for_kind()
    (graphql.validation.KnownFragmentNamesRule method), 102
get_enter_leave_for_kind()
    (graphql.validation.KnownTypeNamesRule method), 103
get_enter_leave_for_kind()
    (graphql.validation.LoneAnonymousOperationRule method), 104
get_enter_leave_for_kind()
    (graphql.validation.LoneSchemaDefinitionRule method), 117
get_enter_leave_for_kind()
    (graphql.validation.NoFragmentCyclesRule method), 104
get_enter_leave_for_kind()
    (graphql.validation.NoUndefinedVariablesRule method), 105
get_enter_leave_for_kind()
    (graphql.validation.NoUnusedFragmentsRule method), 106
get_enter_leave_for_kind()
    (graphql.validation.NoUnusedVariablesRule method), 107
get_enter_leave_for_kind()
    (graphql.validation.OverlappingFieldsCanBeMergedRule method), 107
get_enter_leave_for_kind()
    (graphql.validation.PossibleFragmentSpreadsRule method), 108
get_enter_leave_for_kind()
    (graphql.validation.PossibleTypeExtensionsRule method), 123
get_enter_leave_for_kind()
    (graphql.validation.ProvidedRequiredArgumentsRule method), 109
get_enter_leave_for_kind()
    (graphql.validation.ScalarLeafsRule method), 109
get_enter_leave_for_kind()
    (graphql.validation.SDKValidationRule method), 96
get_enter_leave_for_kind()
    (graphql.validation.SingleFieldSubscriptionsRule method), 110
get_enter_leave_for_kind()
    (graphql.validation.UniqueArgumentDefinitionNamesRule method), 121
get_enter_leave_for_kind()
    (graphql.validation.UniqueArgumentNamesRule method), 111
get_enter_leave_for_kind()
    (graphql.validation.UniqueDirectiveNamesRule method), 122
get_enter_leave_for_kind()
    (graphql.validation.UniqueDirectivesPerLocationRule method), 111
get_enter_leave_for_kind()
    (graphql.validation.UniqueEnumValueNamesRule method), 119
get_enter_leave_for_kind()
    (graphql.validation.UniqueFieldDefinitionNamesRule method), 120
get_enter_leave_for_kind()
    (graphql.validation.UniqueFragmentNamesRule method), 112
get_enter_leave_for_kind()
    (graphql.validation.UniqueInputFieldNamesRule method), 113
get_enter_leave_for_kind()
    (graphql.validation.UniqueOperationNamesRule method), 113
get_enter_leave_for_kind()
    (graphql.validation.UniqueOperationTypesRule method), 118
get_enter_leave_for_kind()
    (graphql.validation.UniqueTypeNamesRule method), 119
get_enter_leave_for_kind()
    (graphql.validation.UniqueVariableNamesRule method), 114
get_enter_leave_for_kind()
    (graphql.validation.ValidationRule method), 98
get_enter_leave_for_kind()

```

(*graphql.validation.ValuesOfCorrectTypeRule method*), 115
get_enter_leave_for_kind()
 (*graphql.validation.VariablesAreInputTypesRule method*), 116
get_enter_leave_for_kind()
 (*graphql.validation.VariablesInAllowedPositionRule method*), 116
get_enum_value() (*graphql.utilities.TypeInfo method*), 89
get_enum_value() (*graphql.validation.ValidationContext method*), 97
get_field_def() (*graphql.utilities.TypeInfo method*), 89
get_field_def() (*graphql.validation.ValidationContext method*), 97
get_field_resolver()
 (*graphql.execution.MiddlewareManager method*), 31
get_fragment() (*graphql.validation.ASTValidationContext method*), 95
get_fragment() (*graphql.validation(SDLValidationContext method)*), 96
get_fragment() (*graphql.validation.ValidationContext method*), 97
get_fragment_spreads()
 (*graphql.validation.ASTValidationContext method*), 95
get_fragment_spreads()
 (*graphql.validation(SDLValidationContext method)*), 96
get_fragment_spreads()
 (*graphql.validation.ValidationContext method*), 97
get_fragment_type()
 (*graphql.validation.PossibleFragmentSpreadsRule method*), 108
get_implementations()
 (*graphql.type.GraphQLSchema method*), 82
get_input_type() (*graphql.utilities.TypeInfo method*), 89
get_input_type() (*graphql.validation.ValidationContext method*), 97
get_introspection_query() (in module *graphql.utilities*), 84
get_location() (*graphql.language.Source method*), 57
get_location() (in module *graphql.language*), 54
get_named_type() (in module *graphql.type*), 64
get_nullable_type() (in module *graphql.type*), 64
get_operation_ast() (in module *graphql.utilities*), 84
get_operation_root_type() (in module *graphql.utilities*), 84
get_parent_input_type() (*graphql.utilities.TypeInfo method*), 89
get_parent_input_type() (*graphql.validation.ValidationContext method*), 97
get_parent_type() (in module *graphql.utilities.TypeInfo method*), 89
get_parent_type() (*graphql.validation.ValidationContext method*), 97
get_possible_types() (*graphql.type.GraphQLSchema method*), 82
get_recursive_variable_usages() (*graphql.validation.ValidationContext method*), 97
get_recursively_referenced_fragments() (*graphql.validation.ASTValidationContext method*), 95
get_recursively_referenced_fragments() (*graphql.validation(SDLValidationContext method)*), 96
get_recursively_referenced_fragments() (*graphql.validation.ValidationContext method*), 97
get_root_type() (*graphql.type.GraphQLSchema method*), 82
get_subscriber() (*graphql.pyutils.SimplePubSub method*), 61
get_type() (*graphql.type.GraphQLSchema method*), 82
get_type() (*graphql.utilities.TypeInfo method*), 89
get_type() (*graphql.validation.ValidationContext method*), 97
get_variable_usages() (*graphql.validation.ValidationContext method*), 97
get_variable_values() (in module *graphql.execution*), 31
get_visit_fn() (in module *graphql.language.ParallelVisitor method*), 59
get_visit_fn() (in module *graphql.language.Visitor method*), 58
get_visit_fn() (in module *graphql.utilities.TypeInfoVisitor method*), 90
get_visit_fn() (in module *graphql.validation.ASTValidationRule method*), 95
get_visit_fn() (in module *graphql.validation.ExecutableDefinitionsRule method*), 99
get_visit_fn() (in module *graphql.validation.FieldsOnCorrectTypeRule method*), 99
get_visit_fn() (in module *graphql.validation.FragmentsOnCompositeTypesRule method*), 100
get_visit_fn() (in module *graphql.validation.KnownArgumentNamesRule method*), 101
get_visit_fn() (in module *graphql.validation.KnownDirectivesRule method*), 102
get_visit_fn() (in module *graphql.validation.KnownFragmentNamesRule*)

```

        method), 102
get_visit_fn() (graphql.validation.KnownTypeNamesRule get_visit_fn() (graphql.validation.ValuesOfCorrectTypeRule
        method), 103                                     method), 115
get_visit_fn() (graphql.validation.LoneAnonymousOperator get_visit_fn() (graphql.validation.VariablesAreInputTypesRule
        method), 104                                     method), 116
get_visit_fn() (graphql.validation.LoneSchemaDefinitionRule get_visit_fn() (graphql.validation.VariablesInAllowedPositionRule
        method), 117                                     method), 116
get_visit_fn() (graphql.validation.NoFragmentCyclesRule graphql
        method), 104                                     module, 19
get_visit_fn() (graphql.validation.NoUndefinedVariableRule graphql() (in module graphql), 20
        method), 105                                     graphql.error
get_visit_fn() (graphql.validation.NoUnusedFragmentsRule module, 21
        method), 106                                     graphql.execution
get_visit_fn() (graphql.validation.NoUnusedVariablesRule module, 24
        method), 107                                     graphql.language
get_visit_fn() (graphql.validation.OverlappingFieldsCanBeMergedRule module, 25
        method), 107                                     graphql.pyutils
get_visit_fn() (graphql.validation.PossibleFragmentSpreadsRule module, 60
        method), 108                                     graphql.type
get_visit_fn() (graphql.validation.PossibleTypeExtensionsRule module, 62
        method), 123                                     graphql.utilities
get_visit_fn() (graphql.validation.ProvidedRequiredArgumentsRule module, 84
        method), 109                                     graphql.validation
get_visit_fn() (graphql.validation.ScalarLeafsRule module, 94
        method), 109                                     graphql.validation.rules
get_visit_fn() (graphql.validation(SDLValidationRule module, 98
        method), 96                                     GRAPHQL_MAX_INT (in module graphql.type), 80
get_visit_fn() (graphql.validation.SingleFieldSubscriptRule GRAPHQL_MIN_INT (in module graphql.type), 80
        method), 110                                     graphql_sync() (in module graphql), 20
get_visit_fn() (graphql.validation.UniqueArgumentDefinitionRule GraphQLAbstractType (in module graphql.type), 73
        method), 121                                     GraphQLArgument (class in graphql.type), 73
get_visit_fn() (graphql.validation.UniqueArgumentNameRule GraphQLArgumentMap (in module graphql.type), 73
        method), 111                                     GraphQLBoolean (in module graphql.type), 80
get_visit_fn() (graphql.validation.UniqueDirectiveNameRule GraphQLCompositeType (in module graphql.type), 73
        method), 122                                     GraphQLDeprecatedDirective (in module graphql.type), 73
get_visit_fn() (graphql.validation.UniqueDirectivesPerLocationRule GraphQLDirective (class in graphql.type), 78
        method), 111                                     GraphQLDirective (class in graphql.type), 78
get_visit_fn() (graphql.validation.UniqueEnumValueNameRule GraphQLEnumType (class in graphql.type), 64
        method), 119                                     GraphQLEnumValue (class in graphql.type), 73
get_visit_fn() (graphql.validation.UniqueFieldDefinitionRule GraphQLEnumValueMap (in module graphql.type), 74
        method), 120                                     GraphQLError (class in graphql.error), 21
get_visit_fn() (graphql.validation.UniqueFragmentNameRule GraphQLField (class in graphql.type), 74
        method), 112                                     GraphQLFieldMap (in module graphql.type), 75
get_visit_fn() (graphql.validation.UniqueInputFieldNameRule GraphQLFieldResolver (in module graphql.type), 77
        method), 113                                     GraphQLFloat (in module graphql.type), 80
get_visit_fn() (graphql.validation.UniqueOperationNameRule GraphQLFormattedError (class in graphql.error), 23
        method), 113                                     GraphQLID (in module graphql.type), 80
get_visit_fn() (graphql.validation.UniqueOperationTypeRule GraphQLIncludeDirective (in module graphql.type),
        method), 118                                     79
get_visit_fn() (graphql.validation.UniqueTypeNamesRule GraphQLInputField (class in graphql.type), 75
        method), 119                                     GraphQLInputFieldMap (in module graphql.type), 75
get_visit_fn() (graphql.validation.UniqueVariableNameRule GraphQLInputObjectType (class in graphql.type), 65
        method), 114                                     GraphQLInputType (in module graphql.type), 75
get_visit_fn() (graphql.validation.ValidationRule GraphQLInt (in module graphql.type), 80

```

GraphQLInterfaceType (*class in graphql.type*), 67
GraphQLIsTypeOfFn (*in module graphql.type*), 77
GraphQLLeafType (*in module graphql.type*), 75
GraphQLList (*class in graphql.type*), 72
GraphQLNamedType (*class in graphql.type*), 76
GraphQLNonNull (*class in graphql.type*), 72
GraphQLNullableType (*in module graphql.type*), 76
GraphQLObjectType (*class in graphql.type*), 68
GraphQLOutputType (*in module graphql.type*), 76
GraphQLResolveInfo (*class in graphql.type*), 77
GraphQLScalarType (*class in graphql.type*), 69
GraphQLSchema (*class in graphql.type*), 81
GraphQLSkipDirective (*in module graphql.type*), 79
GraphQLString (*in module graphql.type*), 80
GraphQLSyntaxError (*class in graphql.error*), 22
GraphQLType (*class in graphql.type*), 76
GraphQLTypeResolver (*in module graphql.type*), 78
GraphQLUnionType (*class in graphql.type*), 70
GraphQLWrappingType (*class in graphql.type*), 76

H

handle_field_error()
 (*graphql.execution.ExecutionContext method*), 28

I

identity_func() (*in module graphql.pyutils*), 60
IDLE (*graphql.language.ParallelVisitor attribute*), 59
IDLE (*graphql.language.Visitor attribute*), 58
IDLE (*graphql.utilities.TypeInfoVisitor attribute*), 90
IDLE (*graphql.validation.ASTValidationRule attribute*), 95
IDLE (*graphql.validation.ExecutableDefinitionsRule attribute*), 98
IDLE (*graphql.validation.FieldsOnCorrectTypeRule attribute*), 99
IDLE (*graphql.validation.FragmentsOnCompositeTypesRule attribute*), 100
IDLE (*graphql.validation.KnownArgumentNamesRule attribute*), 101
IDLE (*graphql.validation.KnownDirectivesRule attribute*), 101
IDLE (*graphql.validation.KnownFragmentNamesRule attribute*), 102
IDLE (*graphql.validation.KnownTypeNamesRule attribute*), 103
IDLE (*graphql.validation.LoneAnonymousOperationRule attribute*), 103
IDLE (*graphql.validation.LoneSchemaDefinitionRule attribute*), 117
IDLE (*graphql.validation.NoFragmentCyclesRule attribute*), 104
IDLE (*graphql.validation.NoUndefinedVariablesRule attribute*), 105

IDLE (*graphql.validation.NoUnusedFragmentsRule attribute*), 105
IDLE (*graphql.validation.NoUnusedVariablesRule attribute*), 106
IDLE (*graphql.validation.OverlappingFieldsCanBeMergedRule attribute*), 107
IDLE (*graphql.validation.PossibleFragmentSpreadsRule attribute*), 108
IDLE (*graphql.validation.PossibleTypeExtensionsRule attribute*), 122
IDLE (*graphql.validation.ProvidedRequiredArgumentsRule attribute*), 108
IDLE (*graphql.validation.ScalarLeafsRule attribute*), 109
IDLE (*graphql.validation.SDKValidationRule attribute*), 96
IDLE (*graphql.validation.SingleFieldSubscriptionsRule attribute*), 110
IDLE (*graphql.validation.UniqueArgumentDefinitionNamesRule attribute*), 121
IDLE (*graphql.validation.UniqueArgumentNamesRule attribute*), 110
IDLE (*graphql.validation.UniqueDirectiveNamesRule attribute*), 122
IDLE (*graphql.validation.UniqueDirectivesPerLocationRule attribute*), 111
IDLE (*graphql.validation.UniqueEnumValueNamesRule attribute*), 119
IDLE (*graphql.validation.UniqueFieldDefinitionNamesRule attribute*), 120
IDLE (*graphql.validation.UniqueFragmentNamesRule attribute*), 112
IDLE (*graphql.validation.UniqueInputFieldNamesRule attribute*), 112
IDLE (*graphql.validation.UniqueOperationNamesRule attribute*), 113
IDLE (*graphql.validation.UniqueOperationTypesRule attribute*), 117
IDLE (*graphql.validation.UniqueTypeNamesRule attribute*), 118
IDLE (*graphql.validation.UniqueVariableNamesRule attribute*), 114
IDLE (*graphql.validation.ValidationRule attribute*), 98
IDLE (*graphql.validation.ValuesOfCorrectTypeRule attribute*), 114
IDLE (*graphql.validation.VariablesAreInputTypesRule attribute*), 115
IDLE (*graphql.validation.VariablesInAllowedPositionRule attribute*), 116
IDLE (*in module graphql.language*), 59
IMPLEMENTED_INTERFACE_ADDED
 (*graphql.utilities.DangerousChangeType attribute*), 94
IMPLEMENTED_INTERFACE_REMOVED
 (*graphql.utilities.BreakingChangeType attribute*)

tribute), 93

index() (*graphql.language.SourceLocation* method), 55

index() (*graphql.pyutils.Path* method), 61

index() (*graphql.type.GraphQLResolveInfo* method), 77

index() (*graphql.utilities.BreakingChange* method), 93

index() (*graphql.utilities.DangerousChange* method), 94

INLINE_FRAGMENT (*graphql.language.DirectiveLocation* attribute), 51

InlineFragmentNode (*class* in *graphql.language*), 39

INPUT_FIELD_DEFINITION
(graphql.language.DirectiveLocation attribute), 51

INPUT_OBJECT (*graphql.language.DirectiveLocation attribute*), 51

INPUT_OBJECT (*graphql.type.TypeKind* attribute), 79

InputObjectTypeDefinitionNode (*class* in *graphql.language*), 40

InputObjectTypeExtensionNode (*class* in *graphql.language*), 40

InputValueDefinitionNode (*class* in *graphql.language*), 40

inspect() (*in module graphql.pyutils*), 60

INT (*graphql.language.TokenKind* attribute), 53

INTERFACE (*graphql.language.DirectiveLocation attribute*), 51

INTERFACE (*graphql.type.TypeKind* attribute), 80

interfaces (*graphql.language.InterfaceTypeDefinitionNodes* attribute), 41

interfaces (*graphql.language.InterfaceTypeExtensionNodes* attribute), 42

interfaces (*graphql.language.ObjectTypeDefinitionNode* *is_specified_directive*()), 44

interfaces (*graphql.language.ObjectTypeExtensionNode* attribute), 44

interfaces (*graphql.type.GraphQLInterfaceType* property), 67

interfaces (*graphql.type.GraphQLObjectType* property), 69

InterfaceTypeDefinitionNode (*class* in *graphql.language*), 41

InterfaceTypeExtensionNode (*class* in *graphql.language*), 41

introspection_from_schema() (*in module graphql.utilities*), 84

introspection_types (*in module graphql.type*), 80

IntValueNode (*class* in *graphql.language*), 41

is_awaitable (*graphql.type.GraphQLResolveInfo* attribute), 78

is_awaitable() (*graphql.execution.ExecutionContext* static method), 28

is_awaitable() (*in module graphql.pyutils*), 60

is_closed (*graphql.execution.MapAsyncIterator* prop-
erty), 30

is_collection() (*in module graphql.pyutils*), 60

is_composite_type() (*in module graphql.type*), 62

is_const_value_node() (*in module graphql.language*), 51

is_definition_node() (*in module graphql.language*), 51

is_directive() (*in module graphql.type*), 78

is_enum_type() (*in module graphql.type*), 62

is_equal_type() (*in module graphql.utilities*), 91

is_executable_definition_node() (*in module graphql.language*), 51

is_input_object_type() (*in module graphql.type*), 62

is_input_type() (*in module graphql.type*), 62

is_interface_type() (*in module graphql.type*), 62

is_introspection_type() (*in module graphql.type*), 79

is_iterable() (*in module graphql.pyutils*), 60

is_leaf_type() (*in module graphql.type*), 62

is_list_type() (*in module graphql.type*), 62

is_named_type() (*in module graphql.type*), 62

is_non_null_type() (*in module graphql.type*), 62

is_nullable_type() (*in module graphql.type*), 62

is_object_type() (*in module graphql.type*), 62

is_output_type() (*in module graphql.type*), 62

is_repeatable (*graphql.type.GraphQLDirective attribute*), 79

is_scalar_type() (*in module graphql.type*), 62

is_selection_node() (*in module graphql.language*), 51

is_specified_directive() (*in module graphql.type*), 78

is_specified_scalar_type() (*in module graphql.type*), 80

is_sub_type() (*graphql.type.GraphQLSchema* method), 82

is_type() (*in module graphql.type*), 63

is_type_definition_node() (*in module graphql.language*), 52

is_type_extension_node() (*in module graphql.language*), 52

is_type_node() (*in module graphql.language*), 52

is_type_of (*graphql.type.GraphQLObjectType* attribute), 69

is_type_sub_type_of() (*in module graphql.utilities*), 92

is_type_system_definition_node() (*in module graphql.language*), 52

is_type_system_extension_node() (*in module graphql.language*), 52

is_union_type() (*in module graphql.type*), 63

is_valid_name_error() (*in module graphql.utilities*), 92

is_valid_value_node()
 (graphql.validation.ValuesOfCorrectTypeRule
 method), 115

is_value_node() (in module graphql.language), 51

is_wrapping_type() (in module graphql.type), 63

K

key (graphql.pyutils.Path attribute), 61

keys (graphql.language.ArgumentNode attribute), 32

keys (graphql.language.BooleanValueNode attribute), 33

keys (graphql.language.ConstArgumentNode attribute), 33

keys (graphql.language.ConstDirectiveNode attribute), 33

keys (graphql.language.ConstListValueNode attribute), 34

keys (graphql.language.ConstObjectFieldNode attribute), 34

keys (graphql.language.ConstObjectValueNode attribute), 34

keys (graphql.language.DefinitionNode attribute), 35

keys (graphql.language.DirectiveDefinitionNode attribute), 35

keys (graphql.language.DirectiveNode attribute), 35

keys (graphql.language.DocumentNode attribute), 36

keys (graphql.language.EnumTypeDefinitionNode attribute), 36

keys (graphql.language.EnumTypeExtensionNode attribute), 36

keys (graphql.language.EnumValueDefinitionNode attribute), 37

keys (graphql.language.EnumValueNode attribute), 37

keys (graphql.language.ExecutableDefinitionNode attribute), 37

keys (graphql.language.FieldDefinitionNode attribute), 38

keys (graphql.language.FieldNode attribute), 38

keys (graphql.language.FloatValueNode attribute), 38

keys (graphql.language.FragmentDefinitionNode attribute), 39

keys (graphql.language.FragmentSpreadNode attribute), 39

keys (graphql.language.InlineFragmentNode attribute), 39

keys (graphql.language.InputObjectTypeDefinitionNode attribute), 40

keys (graphql.language.InputObjectTypeExtensionNode attribute), 40

keys (graphql.language.InputValueDefinitionNode attribute), 41

keys (graphql.language.InterfaceTypeDefinitionNode attribute), 41

keys (graphql.language.InterfaceTypeExtensionNode attribute), 42

keys (graphql.language.IntValueNode attribute), 41

keys (graphql.language.ListTypeNode attribute), 42

keys (graphql.language.ListValueNode attribute), 42

keys (graphql.language.NamedTypeNode attribute), 43

keys (graphql.language.NameNode attribute), 42

keys (graphql.language.Node attribute), 32

keys (graphql.language.NonNullTypeNode attribute), 43

keys (graphql.language.NullValueNode attribute), 43

keys (graphql.language.ObjectFieldNode attribute), 43

keys (graphql.language.ObjectTypeDefinitionNode attribute), 44

keys (graphql.language.ObjectTypeExtensionNode attribute), 44

keys (graphql.language.ObjectValueNode attribute), 45

keys (graphql.language.OperationDefinitionNode attribute), 45

keys (graphql.language.OperationTypeDefinitionNode attribute), 45

keys (graphql.language.ScalarTypeDefinitionNode attribute), 46

keys (graphql.language.ScalarTypeExtensionNode attribute), 46

keys (graphql.language.SchemaDefinitionNode attribute), 46

keys (graphql.language.SchemaExtensionNode attribute), 47

keys (graphql.language.SelectionNode attribute), 47

keys (graphql.language.SelectionSetNode attribute), 47

keys (graphql.language.StringValueNode attribute), 48

keys (graphql.language.TypeDefinitionNode attribute), 48

keys (graphql.language.TypeExtensionNode attribute), 48

keys (graphql.language.TypeNode attribute), 48

keys (graphql.language.TypeSystemDefinitionNode attribute), 49

keys (graphql.language.UnionTypeDefinitionNode attribute), 49

keys (graphql.language.UnionTypeExtensionNode attribute), 49

keys (graphql.language.ValueNode attribute), 50

keys (graphql.language.VariableDefinitionNode attribute), 50

keys (graphql.language.VariableNode attribute), 50

kind (graphql.language.ArgumentNode attribute), 32

kind (graphql.language.BooleanValueNode attribute), 33

kind (graphql.language.ConstArgumentNode attribute), 33

kind (graphql.language.ConstDirectiveNode attribute), 33

kind (graphql.language.ConstListValueNode attribute), 34

kind (graphql.language.ConstObjectFieldNode attribute), 34

kind (`graphql.language.ConstObjectValueNode` attribute), 34

kind (`graphql.language.DefinitionNode` attribute), 35

kind (`graphql.language.DirectiveDefinitionNode` attribute), 35

kind (`graphql.language.DirectiveNode` attribute), 35

kind (`graphql.language.DocumentNode` attribute), 36

kind (`graphql.language.EnumTypeDefinitionNode` attribute), 36

kind (`graphql.language.EnumTypeExtensionNode` attribute), 36

kind (`graphql.language.EnumValueDefinitionNode` attribute), 37

kind (`graphql.language.EnumValueNode` attribute), 37

kind (`graphql.language.ExecutableDefinitionNode` attribute), 37

kind (`graphql.language.FieldDefinitionNode` attribute), 38

kind (`graphql.language.FieldNode` attribute), 38

kind (`graphql.language.FloatValueNode` attribute), 38

kind (`graphql.language.FragmentDefinitionNode` attribute), 39

kind (`graphql.language.FragmentSpreadNode` attribute), 39

kind (`graphql.language.InlineFragmentNode` attribute), 39

kind (`graphql.language.InputObjectTypeDefinitionNode` attribute), 40

kind (`graphql.language.InputObjectTypeExtensionNode` attribute), 40

kind (`graphql.language.InputValueDefinitionNode` attribute), 41

kind (`graphql.language.InterfaceTypeDefinitionNode` attribute), 41

kind (`graphql.language.InterfaceTypeExtensionNode` attribute), 42

kind (`graphql.language.IntValueNode` attribute), 41

kind (`graphql.language.ListTypeNode` attribute), 42

kind (`graphql.language.ListValueNode` attribute), 42

kind (`graphql.language.NamedTypeNode` attribute), 43

kind (`graphql.language.NameNode` attribute), 42

kind (`graphql.language.Node` attribute), 32

kind (`graphql.language.NonNullTypeNode` attribute), 43

kind (`graphql.language.NullValueNode` attribute), 43

kind (`graphql.language.ObjectFieldNode` attribute), 43

kind (`graphql.language.ObjectTypeDefinitionNode` attribute), 44

kind (`graphql.language.ObjectTypeExtensionNode` attribute), 44

kind (`graphql.language.ObjectValueNode` attribute), 45

kind (`graphql.language.OperationDefinitionNode` attribute), 45

kind (`graphql.language.OperationTypeDefinitionNode` attribute), 45

kind (`graphql.language.ScalarTypeDefinitionNode` attribute), 46

kind (`graphql.language.ScalarTypeExtensionNode` attribute), 46

kind (`graphql.language.SchemaDefinitionNode` attribute), 46

kind (`graphql.language.SchemaExtensionNode` attribute), 47

kind (`graphql.language.SelectionNode` attribute), 47

kind (`graphql.language.SelectionSetNode` attribute), 47

kind (`graphql.language.StringValueNode` attribute), 48

kind (`graphql.language.Token` attribute), 54

kind (`graphql.language.TypeDefinitionNode` attribute), 48

kind (`graphql.language.TypeExtensionNode` attribute), 48

kind (`graphql.language.TypeNode` attribute), 48

kind (`graphql.language.TypeSystemDefinitionNode` attribute), 49

kind (`graphql.language.UnionTypeDefinitionNode` attribute), 49

kind (`graphql.language.UnionTypeExtensionNode` attribute), 49

kind (`graphql.language.ValueNode` attribute), 50

kind (`graphql.language.VariableDefinitionNode` attribute), 50

kind (`graphql.language.VariableNode` attribute), 50

`KnownArgumentNamesRule` (class in `graphql.validation`), 100

`KnownDirectivesRule` (class in `graphql.validation`), 101

`KnownFragmentNamesRule` (class in `graphql.validation`), 102

`KnownTypeNamesRule` (class in `graphql.validation`), 102

L

`leave()` (`graphql.utilities.TypeInfo` method), 89

`leave()` (`graphql.utilities.TypeInfoVisitor` method), 90

`leave_argument()` (`graphql.utilities.TypeInfo` method), 89

`leave_directive()` (`graphql.utilities.TypeInfo` method), 89

`leave_directive()` (`graphql.validation.ProvidedRequiredArgumentsRule` method), 109

`leave_document()` (`graphql.validation.NoUnusedFragmentsRule` method), 106

`leave_enum_value()` (`graphql.utilities.TypeInfo` method), 89

`leave_field()` (`graphql.utilities.TypeInfo` method), 89

`leave_field()` (`graphql.validation.ProvidedRequiredArgumentsRule` method), 109

`leave_fragment_definition()` (`graphql.utilities.TypeInfo` method), 89

leave_inline_fragment() (`graphql.utilities.TypeInfo method`), 89
leave_list_value() (`graphql.utilities.TypeInfo method`), 89
leave_object_field() (`graphql.utilities.TypeInfo method`), 89
leave_object_value() (`graphql.validation.UniqueInputFieldNamesRule method`), 113
leave_operation_definition() (`graphql.utilities.TypeInfo method`), 89
leave_operation_definition() (`graphql.validation.NoUndefinedVariablesRule method`), 105
leave_operation_definition() (`graphql.validation.NoUnusedVariablesRule method`), 107
leave_operation_definition() (`graphql.validation.VariablesInAllowedPositionRule method`), 116
leave_selection_set() (`graphql.utilities.TypeInfo method`), 89
leave_variable_definition() (`graphql.utilities.TypeInfo method`), 89
Lexer (class in `graphql.language`), 52
lexicographic_sort_schema() (in module `graphql.utilities`), 86
line (`graphql.language.FormattedSourceLocation attribute`), 55
line (`graphql.language.SourceLocation attribute`), 55
line (`graphql.language.Token attribute`), 54
LIST (`graphql.type.TypeKind attribute`), 80
ListTypeNode (class in `graphql.language`), 42
ListValueNode (class in `graphql.language`), 42
loc (`graphql.language.ArgumentNode attribute`), 32
loc (`graphql.language.BooleanValueNode attribute`), 33
loc (`graphql.language.ConstArgumentNode attribute`), 33
loc (`graphql.language.ConstDirectiveNode attribute`), 33
loc (`graphql.language.ConstListValueNode attribute`), 34
loc (`graphql.language.ConstObjectFieldNode attribute`), 34
loc (`graphql.language.ConstObjectValueNode attribute`), 34
loc (`graphql.language.DefinitionNode attribute`), 35
loc (`graphql.language.DirectiveDefinitionNode attribute`), 35
loc (`graphql.language.DirectiveNode attribute`), 35
loc (`graphql.language.DocumentNode attribute`), 36
loc (`graphql.language.EnumTypeDefinitionNode attribute`), 36
loc (`graphql.language.EnumTypeExtensionNode attribute`), 36
loc (`graphql.language.EnumValueDefinitionNode attribute`), 37
loc (`graphql.language.ExecutableDefinitionNode attribute`), 37
loc (`graphql.language.FieldDefinitionNode attribute`), 38
loc (`graphql.language.FieldNode attribute`), 38
loc (`graphql.language.FloatValueNode attribute`), 38
loc (`graphql.language.FragmentDefinitionNode attribute`), 39
loc (`graphql.language.FragmentSpreadNode attribute`), 39
loc (`graphql.language.InlineFragmentNode attribute`), 39
loc (`graphql.language.InputObjectTypeDefinitionNode attribute`), 40
loc (`graphql.language.InputObjectTypeExtensionNode attribute`), 40
loc (`graphql.language.InputValueDefinitionNode attribute`), 41
loc (`graphql.language.InterfaceTypeDefinitionNode attribute`), 41
loc (`graphql.language.InterfaceTypeExtensionNode attribute`), 42
loc (`graphql.language.IntValueNode attribute`), 41
loc (`graphql.language.ListTypeNode attribute`), 42
loc (`graphql.language.ListValueNode attribute`), 42
loc (`graphql.language.NamedTypeNode attribute`), 43
loc (`graphql.language.NameNode attribute`), 42
loc (`graphql.language.Node attribute`), 32
loc (`graphql.language.NonNullTypeNode attribute`), 43
loc (`graphql.language.NullValueNode attribute`), 43
loc (`graphql.language.ObjectFieldNode attribute`), 44
loc (`graphql.language.ObjectTypeDefinitionNode attribute`), 44
loc (`graphql.language.ObjectTypeExtensionNode attribute`), 44
loc (`graphql.language.ObjectValueNode attribute`), 45
loc (`graphql.language.OperationDefinitionNode attribute`), 45
loc (`graphql.language.OperationTypeDefinitionNode attribute`), 45
loc (`graphql.language.ScalarTypeDefinitionNode attribute`), 46
loc (`graphql.language.ScalarTypeExtensionNode attribute`), 46
loc (`graphql.language.SchemaDefinitionNode attribute`), 46
loc (`graphql.language.SchemaExtensionNode attribute`), 47
loc (`graphql.language.SelectionNode attribute`), 47
loc (`graphql.language.SelectionSetNode attribute`), 47
loc (`graphql.language.StringValueNode attribute`), 48
loc (`graphql.language.TypeDefinitionNode attribute`), 48
loc (`graphql.language.TypeExtensionNode attribute`), 48

loc (`graphql.language.TypeNode` attribute), 48
loc (`graphql.language.TypeSystemDefinitionNode` attribute), 49
loc (`graphql.language.UnionTypeDefinitionNode` attribute), 49
loc (`graphql.language.UnionTypeExtensionNode` attribute), 49
loc (`graphql.language.ValueNode` attribute), 50
loc (`graphql.language.VariableDefinitionNode` attribute), 50
loc (`graphql.language.VariableNode` attribute), 50
located_error() (in module `graphql.error`), 23
Location (class in `graphql.language`), 32
location_offset (`graphql.language.Source` attribute), 57
locations (`graphql.error.GraphQLError` attribute), 21
locations (`graphql.error.GraphQLFormattedError` attribute), 23
locations (`graphql.error.GraphQLSyntaxError` attribute), 22
locations (`graphql.language.DirectiveDefinitionNode` attribute), 35
locations (`graphql.type.GraphQLDirective` attribute), 79
LoneAnonymousOperationRule (class in `graphql.validation`), 103
LoneSchemaDefinitionRule (class in `graphql.validation`), 117
lookahead() (`graphql.language.Lexer` method), 52

M

MapAsyncIterator (class in `graphql.execution`), 30
message (`graphql.error.GraphQLError` attribute), 22
message (`graphql.error.GraphQLFormattedError` attribute), 23
message (`graphql.error.GraphQLSyntaxError` attribute), 22
Middleware (in module `graphql.execution`), 30
middleware_manager (`graphql.execution.ExecutionContext` attribute), 28
MiddlewareManager (class in `graphql.execution`), 31
middlewares (`graphql.execution.MiddlewareManager` attribute), 31
module
 `graphql`, 19
 `graphql.error`, 21
 `graphql.execution`, 24
 `graphql.language`, 32
 `graphql.pyutils`, 60
 `graphql.type`, 62
 `graphql.utilities`, 84
 `graphql.validation`, 94
 `graphql.validation.rules`, 98

MUTATION (`graphql.language.DirectiveLocation` attribute), 51
MUTATION (`graphql.language.OperationType` attribute), 45
mutation_type (`graphql.type.GraphQLSchema` attribute), 83

N

name (`graphql.language.ArgumentNode` attribute), 32
name (`graphql.language.ConstArgumentNode` attribute), 33
name (`graphql.language.ConstDirectiveNode` attribute), 33
name (`graphql.language.ConstObjectFieldNode` attribute), 34
name (`graphql.language.DirectiveDefinitionNode` attribute), 35
name (`graphql.language.DirectiveNode` attribute), 35
name (`graphql.language.EnumTypeDefinitionNode` attribute), 36
name (`graphql.language.EnumTypeExtensionNode` attribute), 36
name (`graphql.language.EnumValueDefinitionNode` attribute), 37
name (`graphql.language.ExecutableDefinitionNode` attribute), 37
name (`graphql.language.FieldDefinitionNode` attribute), 38
name (`graphql.language.FieldNode` attribute), 38
name (`graphql.language.FragmentDefinitionNode` attribute), 39
name (`graphql.language.FragmentSpreadNode` attribute), 39
name (`graphql.language.InputObjectTypeDefinitionNode` attribute), 40
name (`graphql.language.InputObjectTypeExtensionNode` attribute), 40
name (`graphql.language.InputValueDefinitionNode` attribute), 41
name (`graphql.language.InterfaceTypeDefinitionNode` attribute), 41
name (`graphql.language.InterfaceTypeExtensionNode` attribute), 42
name (`graphql.language.NamedTypeNode` attribute), 43
name (`graphql.language.ObjectFieldNode` attribute), 44
name (`graphql.language.ObjectTypeDefinitionNode` attribute), 44
name (`graphql.language.ObjectTypeExtensionNode` attribute), 44
name (`graphql.language.OperationDefinitionNode` attribute), 45
name (`graphql.language.ScalarTypeDefinitionNode` attribute), 46

name (*graphql.language.ScalarTypeExtensionNode* attribute), 46
name (*graphql.language.Source* attribute), 57
NAME (*graphql.language.TokenKind* attribute), 53
name (*graphql.language.TypeDefinitionNode* attribute), 48
name (*graphql.language.TypeExtensionNode* attribute), 48
name (*graphql.language.UnionTypeDefinitionNode* attribute), 49
name (*graphql.language.UnionTypeExtensionNode* attribute), 49
name (*graphql.language.VariableNode* attribute), 50
name (*graphql.type.GraphQLDirective* attribute), 79
name (*graphql.type.GraphQLEnumType* attribute), 65
name (*graphql.type.GraphQLInputObjectType* attribute), 66
name (*graphql.type.GraphQLInterfaceType* attribute), 67
name (*graphql.type.GraphQLNamedType* attribute), 76
name (*graphql.type.GraphQLObjectType* attribute), 69
name (*graphql.type.GraphQLScalarType* attribute), 70
name (*graphql.type.GraphQLUnionType* attribute), 71
NamedTypeNode (class in *graphql.language*), 43
NameNode (class in *graphql.language*), 42
natural_comparison_key() (in module *graphql.pyutils*), 60
next (*graphql.language.Token* attribute), 54
Node (class in *graphql.language*), 32
nodes (*graphql.error.GraphQLError* attribute), 22
nodes (*graphql.error.GraphQLSyntaxError* attribute), 23
NoFragmentCyclesRule (class in *graphql.validation*), 104
NON_NULL (*graphql.type.TypeKind* attribute), 80
NonNullTypeNode (class in *graphql.language*), 43
NoUndefinedVariablesRule (class in *graphql.validation*), 105
NoUnusedFragmentsRule (class in *graphql.validation*), 105
NoUnusedVariablesRule (class in *graphql.validation*), 106
NullValueNode (class in *graphql.language*), 43

O

OBJECT (*graphql.language.DirectiveLocation* attribute), 51
OBJECT (*graphql.type.TypeKind* attribute), 80
ObjectFieldNode (class in *graphql.language*), 43
ObjectTypeDefinitionNode (class in *graphql.language*), 44
ObjectTypeExtensionNode (class in *graphql.language*), 44
ObjectValueNode (class in *graphql.language*), 44
of_type (*graphql.type.GraphQLList* attribute), 72
of_type (*graphql.type.GraphQLNonNull* attribute), 72

of_type (*graphql.type.GraphQLWrappingType* attribute), 76
on_error() (*graphql.validation.ASTValidationContext* method), 95
on_error() (*graphql.validation(SDLValidationContext* method), 96
on_error() (*graphql.validation.ValidationContext* method), 98
operation (*graphql.execution.ExecutionContext* attribute), 28
operation (*graphql.language.OperationDefinitionNode* attribute), 45
operation (*graphql.language.OperationTypeDefinitionNode* attribute), 45
operation (*graphql.type.GraphQLResolveInfo* attribute), 78
operation_types (*graphql.language.SchemaDefinitionNode* attribute), 46
operation_types (*graphql.language.SchemaExtensionNode* attribute), 47
OperationDefinitionNode (class in *graphql.language*), 45
OperationType (class in *graphql.language*), 45
OperationTypeDefinitionNode (class in *graphql.language*), 45
OPTIONAL_ARG_ADDED (*graphql.utilities.DangerousChangeType* attribute), 94
OPTIONAL_INPUT_FIELD_ADDED (*graphql.utilities.DangerousChangeType* attribute), 94
original_error (*graphql.error.GraphQLError* attribute), 22
original_error (*graphql.error.GraphQLSyntaxError* attribute), 23
out_name (*graphql.type.GraphQLArgument* attribute), 73
out_name (*graphql.type.GraphQLInputField* attribute), 75
out_type() (*graphql.type.GraphQLInputObjectType* static method), 66
OverlappingFieldsCanBeMergedRule (class in *graphql.validation*), 107

P

ParallelVisitor (class in *graphql.language*), 58
PAREN_L (*graphql.language.TokenKind* attribute), 53
PAREN_R (*graphql.language.TokenKind* attribute), 54
parent_type (*graphql.type.GraphQLResolveInfo* attribute), 78
parse() (in module *graphql.language*), 55
parse_const_value() (in module *graphql.language*), 56
parse_literal() (*graphql.type.GraphQLEnumType* method), 65

`parse_literal()` (`graphql.type.GraphQLScalarType method`), 70
`parse_type()` (*in module* `graphql.language`), 55
`parse_value()` (`graphql.type.GraphQLEnumType method`), 65
`parse_value()` (`graphql.type.GraphQLScalarType static method`), 70
`parse_value()` (*in module* `graphql.language`), 56
`Path` (*class in* `graphql.pyutils`), 61
`path` (`graphql.error.GraphQLError attribute`), 22
`path` (`graphql.error.GraphQLFormattedError attribute`), 23
`path` (`graphql.error.GraphQLSyntaxError attribute`), 23
`path` (`graphql.type.GraphQLResolveInfo attribute`), 78
`PIPE` (`graphql.language.TokenKind attribute`), 54
`positions` (`graphql.error.GraphQLError attribute`), 22
`positions` (`graphql.error.GraphQLSyntaxError attribute`), 23
`PossibleFragmentSpreadsRule` (*class in* `graphql.validation`), 107
`PossibleTypeExtensionsRule` (*class in* `graphql.validation`), 122
`prev` (`graphql.language.Token attribute`), 54
`prev` (`graphql.pyutils.Path attribute`), 61
`print_ast()` (*in module* `graphql.language`), 56
`print_code_point_at()` (`graphql.language.Lexer method`), 52
`print_introspection_schema()` (*in module* `graphql.utilities`), 86
`print_location()` (*in module* `graphql.language`), 55
`print_path_list()` (*in module* `graphql.pyutils`), 61
`print_schema()` (*in module* `graphql.utilities`), 86
`print_source_location()` (*in module* `graphql.language`), 57
`print_type()` (*in module* `graphql.utilities`), 86
`ProvidedRequiredArgumentsRule` (*class in* `graphql.validation`), 108
`push_value()` (`graphql.pyutils.SimplePubSubIterator method`), 62

Q

`QUERY` (`graphql.language.DirectiveLocation attribute`), 51
`QUERY` (`graphql.language.OperationType attribute`), 45
`query_type` (`graphql.type.GraphQLSchema attribute`), 83

R

`read_block_string()` (`graphql.language.Lexer method`), 52
`read_comment()` (`graphql.language.Lexer method`), 52
`read_digits()` (`graphql.language.Lexer method`), 52
`read_escaped_character()` (`graphql.language.Lexer method`), 52
`read_escaped_unicode_fixed_width()` (`graphql.language.Lexer method`), 53
`read_escaped_unicode_variable_width()` (`graphql.language.Lexer method`), 53
`read_name()` (`graphql.language.Lexer method`), 53
`read_next_token()` (`graphql.language.Lexer method`), 53
`read_number()` (`graphql.language.Lexer method`), 53
`read_string()` (`graphql.language.Lexer method`), 53
`register_description()` (*in module* `graphql.pyutils`), 60
`REMOVE` (`graphql.language.ParallelVisitor attribute`), 59
`REMOVE` (`graphql.language.Visitor attribute`), 58
`REMOVE` (`graphql.language.visitor.VisitorActionEnum attribute`), 59
`REMOVE` (`graphql.utilities.TypeInfoVisitor attribute`), 90
`REMOVE` (`graphql.validation.ASTValidationRule attribute`), 95
`REMOVE` (`graphql.validation.ExecutableDefinitionsRule attribute`), 99
`REMOVE` (`graphql.validation.FieldsOnCorrectTypeRule attribute`), 99
`REMOVE` (`graphql.validation.FragmentsOnCompositeTypesRule attribute`), 100
`REMOVE` (`graphql.validation.KnownArgumentNamesRule attribute`), 101
`REMOVE` (`graphql.validation.KnownDirectivesRule attribute`), 101
`REMOVE` (`graphql.validation.KnownFragmentNamesRule attribute`), 102
`REMOVE` (`graphql.validation.KnownTypeNamesRule attribute`), 103
`REMOVE` (`graphql.validation.LoneAnonymousOperationRule attribute`), 103
`REMOVE` (`graphql.validation.LoneSchemaDefinitionRule attribute`), 117
`REMOVE` (`graphql.validation.NoFragmentCyclesRule attribute`), 104
`REMOVE` (`graphql.validation.NoUndefinedVariablesRule attribute`), 105
`REMOVE` (`graphql.validation.NoUnusedFragmentsRule attribute`), 106
`REMOVE` (`graphql.validation.NoUnusedVariablesRule attribute`), 106
`REMOVE` (`graphql.validation.OverlappingFieldsCanBeMergedRule attribute`), 107
`REMOVE` (`graphql.validation.PossibleFragmentSpreadsRule attribute`), 108
`REMOVE` (`graphql.validation.PossibleTypeExtensionsRule attribute`), 122
`REMOVE` (`graphql.validation.ProvidedRequiredArgumentsRule attribute`), 108
`REMOVE` (`graphql.validation.ScalarLeafsRule attribute`), 109

REMOVE (graphql.validation.SDLValidationRule attribute), 96
REMOVE (graphql.validation.SingleFieldSubscriptionsRule attribute), 110
REMOVE (graphql.validation.UniqueArgumentDefinitionName attribute), 121
REMOVE (graphql.validation.UniqueArgumentNamesRule attribute), 110
REMOVE (graphql.validation.UniqueDirectiveNamesRule attribute), 122
REMOVE (graphql.validation.UniqueDirectivesPerLocationRule attribute), 111
REMOVE (graphql.validation.UniqueEnumValueNamesRule attribute), 119
REMOVE (graphql.validation.UniqueFieldDefinitionNamesRule attribute), 120
REMOVE (graphql.validation.UniqueFragmentNamesRule attribute), 112
REMOVE (graphql.validation.UniqueInputFieldNamesRule attribute), 112
REMOVE (graphql.validation.UniqueOperationNamesRule attribute), 113
REMOVE (graphql.validation.UniqueOperationTypesRule attribute), 117
REMOVE (graphql.validation.UniqueTypeNamesRule attribute), 118
REMOVE (graphql.validation.UniqueVariableNamesRule attribute), 114
REMOVE (graphql.validation.ValidationRule attribute), 98
REMOVE (graphql.validation.ValuesOfCorrectTypeRule attribute), 114
REMOVE (graphql.validation.VariablesAreInputTypesRule attribute), 115
REMOVE (graphql.validation.VariablesInAllowedPositionRule attribute), 116
REMOVE (in module graphql.language), 59
repeatable (graphql.language.DirectiveDefinitionNode attribute), 35
report_error() (graphql.validation.ASTValidationContext method), 95
report_error() (graphql.validation.ASTValidationRule method), 95
report_error() (graphql.validation.ExecutableDefinitionNode method), 99
report_error() (graphql.validation.FieldsOnCorrectType method), 100
report_error() (graphql.validation.FragmentsOnComposition method), 100
report_error() (graphql.validation.KnownArgumentName method), 101
report_error() (graphql.validation.KnownDirectivesRule method), 102
report_error() (graphql.validation.KnownFragmentName method), 102
at- report_error() (graphql.validation.KnownTypeNamesRule method), 103
report_error() (graphql.validation.LoneAnonymousOperationRule method), 104
report_error() (graphql.validation.LoneSchemaDefinitionRule method), 117
report_error() (graphql.validation.NoFragmentCyclesRule method), 104
report_error() (graphql.validation.NoUndefinedVariablesRule method), 105
report_error() (graphql.validation.NoUnusedFragmentsRule method), 106
report_error() (graphql.validation.NoUnusedVariablesRule method), 107
report_error() (graphql.validation.OverlappingFieldsCanBeMergedRule method), 107
report_error() (graphql.validation.PossibleFragmentSpreadsRule method), 108
report_error() (graphql.validation.PossibleTypeExtensionsRule method), 123
report_error() (graphql.validation.ProvidedRequiredArgumentsRule method), 109
report_error() (graphql.validation.ScalarLeafsRule method), 109
report_error() (graphql.validation(SDLValidationContext method), 96
report_error() (graphql.validation(SDLValidationRule method), 96
report_error() (graphql.validation.SingleFieldSubscriptionsRule method), 110
report_error() (graphql.validation.UniqueArgumentDefinitionNamesRule method), 121
report_error() (graphql.validation.UniqueEnumValueNamesRule method), 120
report_error() (graphql.validation.UniqueFieldDefinitionNamesRule method), 120
report_error() (graphql.validation.UniqueInputFieldNamesRule method), 113
report_error() (graphql.validation.UniqueOperationNamesRule method), 114
report_error() (graphql.validation.UniqueOperationTypesRule method), 118
report_error() (graphql.validation.UniqueTypeNamesRule method), 119
report_error() (graphql.validation.UniqueVariableNamesRule method), 114

`report_error()` (`graphql.validation.ValidationContext method`), 98
`report_error()` (`graphql.validation.ValidationRule method`), 98
`report_error()` (`graphql.validation.ValuesOfCorrectTypeRule method`), 115
`report_error()` (`graphql.validation.VariablesAreInputTypesRule method`), 116
`report_error()` (`graphql.validation.VariablesInAllowedPositionRule attribute`), 117
`REQUIRED_ARG_ADDED` (`graphql.utilities.BreakingChangeType attribute`), 93
`REQUIRED_DIRECTIVE_ARG_ADDED` (`graphql.utilities.BreakingChangeType attribute`), 93
`REQUIRED_INPUT_FIELD_ADDED` (`graphql.utilities.BreakingChangeType attribute`), 93
`resolve` (`graphql.type.GraphQLField attribute`), 74
`resolve_thunk()` (in module `graphql.type`), 83
`resolve_type` (`graphql.type.GraphQLInterfaceType attribute`), 68
`resolve_type` (`graphql.type.GraphQLUnionType attribute`), 71
`return_type` (`graphql.type.GraphQLResolveInfo attribute`), 78
`root_value` (`graphql.execution.ExecutionContext attribute`), 28
`root_value` (`graphql.type.GraphQLResolveInfo attribute`), 78

S

`SCALAR` (`graphql.language.DirectiveLocation attribute`), 51
`SCALAR` (`graphql.type.TypeKind attribute`), 80
`ScalarLeafsRule` (class in `graphql.validation`), 109
`ScalarTypeDefinitionNode` (class in `graphql.language`), 46
`ScalarTypeExtensionNode` (class in `graphql.language`), 46
`schema` (`graphql.execution.ExecutionContext attribute`), 28
`SCHEMA` (`graphql.language.DirectiveLocation attribute`), 51
`schema` (`graphql.type.GraphQLResolveInfo attribute`), 78
`schema` (`graphql.validation(SDLValidationContext attribute)`), 96
`schema` (`graphql.validation.ValidationContext attribute`), 98
`SchemaDefinitionNode` (class in `graphql.language`), 46
`SchemaExtensionNode` (class in `graphql.language`), 47
`SchemaMetaFieldDef` (in module `graphql.type`), 80
`SDLValidationContext` (class in `graphql.validation`), 95
`SDLValidationRule` (class in `graphql.validation`), 96
`selection_set` (`graphql.language.ExecutableDefinitionNode attribute`), 37
`selection_set` (`graphql.language.FieldNode attribute`), 38
`selection_set` (`graphql.language.FragmentDefinitionNode`), 39
`selection_set` (`graphql.language.InlineFragmentNode`), 40
`selection_set` (`graphql.language.OperationDefinitionNode attribute`), 45
`SelectionNode` (class in `graphql.language`), 47
`selections` (`graphql.language.SelectionSetNode attribute`), 47
`SelectionSetNode` (class in `graphql.language`), 47
`separate_operations()` (in module `graphql.utilities`), 90
`serialize()` (`graphql.type.GraphQLEnumType method`), 65
`serialize()` (`graphql.type.GraphQLScalarType static method`), 70
`SimplePubSub` (class in `graphql.pyutils`), 61
`SimplePubSubIterator` (class in `graphql.pyutils`), 62
`SingleFieldSubscriptionsRule` (class in `graphql.validation`), 110
`SKIP` (`graphql.language.ParallelVisitor attribute`), 59
`SKIP` (`graphql.language.Visitor attribute`), 58
`SKIP` (`graphql.language.visitor.VisitorActionEnum attribute`), 59
`SKIP` (`graphql.utilities.TypeInfoVisitor attribute`), 90
`SKIP` (`graphql.validation.ASTValidationRule attribute`), 95
`SKIP` (`graphql.validation.ExecutableDefinitionsRule attribute`), 99
`SKIP` (`graphql.validation.FieldsOnCorrectTypeRule attribute`), 99
`SKIP` (`graphql.validation.FragmentsOnCompositeTypesRule attribute`), 100
`SKIP` (`graphql.validation.KnownArgumentNamesRule attribute`), 101
`SKIP` (`graphql.validation.KnownDirectivesRule attribute`), 101
`SKIP` (`graphql.validation.KnownFragmentNamesRule attribute`), 102
`SKIP` (`graphql.validation.KnownTypeNamesRule attribute`), 103
`SKIP` (`graphql.validation.LoneAnonymousOperationRule attribute`), 103
`SKIP` (`graphql.validation.LoneSchemaDefinitionRule attribute`), 117
`SKIP` (`graphql.validation.NoFragmentCyclesRule attribute`), 104
`SKIP` (`graphql.validation.NoUndefinedVariablesRule attribute`), 105

SKIP (*graphql.validation.NoUnusedFragmentsRule attribute*), 106
SKIP (*graphql.validation.NoUnusedVariablesRule attribute*), 106
SKIP (*graphql.validation.OverlappingFieldsCanBeMergedRule attribute*), 107
SKIP (*graphql.validation.PossibleFragmentSpreadsRule attribute*), 108
SKIP (*graphql.validation.PossibleTypeExtensionsRule attribute*), 122
SKIP (*graphql.validation.ProvidedRequiredArgumentsRule attribute*), 108
SKIP (*graphql.validation.ScalarLeafsRule attribute*), 109
SKIP (*graphql.validation(SDLValidationRule attribute*), 96
SKIP (*graphql.validation.SingleFieldSubscriptionsRule attribute*), 110
SKIP (*graphql.validation.UniqueArgumentDefinitionNamesRule attribute*), 121
SKIP (*graphql.validation.UniqueArgumentNamesRule attribute*), 110
SKIP (*graphql.validation.UniqueDirectiveNamesRule attribute*), 122
SKIP (*graphql.validation.UniqueDirectivesPerLocationRule attribute*), 111
SKIP (*graphql.validation.UniqueEnumValueNamesRule attribute*), 119
SKIP (*graphql.validation.UniqueFieldDefinitionNamesRule attribute*), 120
SKIP (*graphql.validation.UniqueFragmentNamesRule attribute*), 112
SKIP (*graphql.validation.UniqueInputFieldNamesRule attribute*), 112
SKIP (*graphql.validation.UniqueOperationNamesRule attribute*), 113
SKIP (*graphql.validation.UniqueOperationTypesRule attribute*), 117
SKIP (*graphql.validation.UniqueTypeNamesRule attribute*), 118
SKIP (*graphql.validation.UniqueVariableNamesRule attribute*), 114
SKIP (*graphql.validation.ValidationRule attribute*), 98
SKIP (*graphql.validation.ValuesOfCorrectTypeRule attribute*), 115
SKIP (*graphql.validation.VariablesAreInputTypesRule attribute*), 116
SKIP (*graphql.validation.VariablesInAllowedPositionRule attribute*), 116
SKIP (*in module graphql.language*), 59
`snake_to_camel()` (*in module graphql.pyutils*), 60
SOF (*graphql.language.TokenKind attribute*), 54
Source (*class in graphql.language*), 56
`source` (*graphql.error.GraphQLError attribute*), 22
`source` (*graphql.error.GraphQLSyntaxError attribute*), 23
`source` (*graphql.language.Location attribute*), 32
SourceLocation (*class in graphql.language*), 54
`specified_by_url` (*graphql.type.GraphQLScalarType attribute*), 70
`specified_directives` (*in module graphql.type*), 79
`specified_rules` (*in module graphql.validation*), 98
SPREAD (*graphql.language.TokenKind attribute*), 54
`start` (*graphql.language.Location attribute*), 32
`start` (*graphql.language.Token attribute*), 54
`start_token` (*graphql.language.Location attribute*), 32
STRING (*graphql.language.TokenKind attribute*), 54
StringValueNode (*class in graphql.language*), 47
`strip_ignored_characters()` (*in module graphql.utilities*), 90
`subscribe` (*graphql.type.GraphQLField attribute*), 74
`subscribe()` (*in module graphql.execution*), 29
`Subscribe_field_resolver` (*graphql.execution.ExecutionContext attribute*), 29
subscribers (*graphql.pyutils.SimplePubSub attribute*), 62
SUBSCRIPTION (*graphql.language.DirectiveLocation attribute*), 51
SUBSCRIPTION (*graphql.language.OperationType attribute*), 45
`subscription_type` (*graphql.type.GraphQLSchema attribute*), 83
`suggestion_list()` (*in module graphql.pyutils*), 61

T

Thunk (*in module graphql.type*), 76
ThunkCollection (*in module graphql.type*), 77
ThunkMapping (*in module graphql.type*), 77
`to_dict()` (*graphql.language.ArgumentNode method*), 33
`to_dict()` (*graphql.language.BooleanValueNode method*), 33
`to_dict()` (*graphql.language.ConstArgumentNode method*), 33
`to_dict()` (*graphql.language.ConstDirectiveNode method*), 33
`to_dict()` (*graphql.language.ConstListValueNode method*), 34
`to_dict()` (*graphql.language.ConstObjectFieldNode method*), 34
`to_dict()` (*graphql.language.ConstObjectValueNode method*), 34
`to_dict()` (*graphql.language.DefinitionNode method*), 35
`to_dict()` (*graphql.language.DirectiveDefinitionNode method*), 35
`to_dict()` (*graphql.language.DirectiveNode method*), 36

```

to_dict() (graphql.language.DocumentNode method), 36
to_dict() (graphql.language.EnumTypeDefinitionNode method), 36
to_dict() (graphql.language.EnumTypeExtensionNode method), 36
to_dict() (graphql.language.EnumValueDefinitionNode method), 37
to_dict() (graphql.language.EnumValueNode method), 37
to_dict() (graphql.language.ExecutableDefinitionNode method), 37
to_dict() (graphql.language.FieldDefinitionNode method), 38
to_dict() (graphql.language.FieldNode method), 38
to_dict() (graphql.language.FloatValueNode method), 39
to_dict() (graphql.language.FragmentDefinitionNode method), 39
to_dict() (graphql.language.FragmentSpreadNode method), 39
to_dict() (graphql.language.InlineFragmentNode method), 40
to_dict() (graphql.language.InputObjectTypeDefinitionNode method), 40
to_dict() (graphql.language.InputObjectTypeExtensionNode method), 40
to_dict() (graphql.language.InputValueDefinitionNode method), 41
to_dict() (graphql.language.InterfaceTypeDefinitionNode method), 41
to_dict() (graphql.language.InterfaceTypeExtensionNode method), 42
to_dict() (graphql.language.IntValueNode method), 41
to_dict() (graphql.language.ListTypeNode method), 42
to_dict() (graphql.language.ListValueNode method), 42
to_dict() (graphql.language.NamedTypeNode method), 43
to_dict() (graphql.language.NameNode method), 43
to_dict() (graphql.language.Node method), 32
to_dict() (graphql.language.NonNullTypeNode method), 43
to_dict() (graphql.language.NullValueNode method), 43
to_dict() (graphql.language.ObjectFieldNode method), 44
to_dict() (graphql.language.ObjectTypeDefinitionNode method), 44
to_dict() (graphql.language.ObjectTypeExtensionNode method), 44
to_dict() (graphql.language.ObjectValueNode method), 45
to_dict() (graphql.language.OperationDefinitionNode
           method), 45
to_dict() (graphql.language.OperationTypeDefinitionNode
           method), 46
to_dict() (graphql.language.ScalarTypeDefinitionNode
           method), 46
to_dict() (graphql.language.ScalarTypeExtensionNode
           method), 46
to_dict() (graphql.language.SchemaDefinitionNode
           method), 47
to_dict() (graphql.language.SchemaExtensionNode
           method), 47
to_dict() (graphql.language.SelectionNode method), 47
to_dict() (graphql.language.SelectionSetNode
           method), 47
to_dict() (graphql.language.StringValueNode
           method), 48
to_dict() (graphql.language.TypeDefinitionNode
           method), 48
to_dict() (graphql.language.TypeExtensionNode
           method), 48
to_dict() (graphql.language.TypeNode method), 49
to_dict() (graphql.language.TypeSystemDefinitionNode
           method), 49
to_dict() (graphql.language.UnionTypeDefinitionNode
           method), 49
to_dict() (graphql.language.UnionTypeExtensionNode
           method), 49
to_dict() (graphql.language.ValueNode method), 50
to_dict() (graphql.language.VariableDefinitionNode
           method), 50
to_kw_args() (graphql.type.GraphQLArgument
              method), 73
to_kw_args() (graphql.type.GraphQLDirective method), 79
to_kw_args() (graphql.type.GraphQLEnumType
              method), 65
to_kw_args() (graphql.type.GraphQLEnumValue
              method), 74
to_kw_args() (graphql.type.GraphQLField method), 74
to_kw_args() (graphql.type.GraphQLInputField
              method), 75
to_kw_args() (graphql.type.GraphQLInputObjectType
              method), 66
to_kw_args() (graphql.type.GraphQLInterfaceType
              method), 68
to_kw_args() (graphql.type.GraphQLNamedType
              method), 76
to_kw_args() (graphql.type.GraphQLObjectType
              method), 69
to_kw_args() (graphql.type.GraphQLScalarType
              method), 70
to_kw_args() (graphql.type.GraphQLSchema method),

```

83
to_kwarg() (graphql.type.GraphQLUnionType method), 71
Token (class in graphql.language), 54
TokenKind (class in graphql.language), 53
type (graphql.language.FieldDefinitionNode attribute), 38
type (graphql.language.InputValueDefinitionNode attribute), 41
type (graphql.language.ListTypeNode attribute), 42
type (graphql.language.NonNullTypeNode attribute), 43
type (graphql.language.OperationTypeDefinitionNode attribute), 46
type (graphql.language.VariableDefinitionNode attribute), 50
type (graphql.type.GraphQLEntryType attribute), 73
type (graphql.type.GraphQLField attribute), 74
type (graphql.type.GraphQLInputField attribute), 75
type (graphql.utilities.BreakingChange attribute), 93
type (graphql.utilities.DangerousChange attribute), 94
TYPE_ADDED_TO_UNION
 (graphql.utilities.DangerousChangeType attribute), 94
TYPE_CHANGED_KIND (graphql.utilities.BreakingChangeType attribute), 93
type_condition (graphql.language.FragmentDefinitionNode attribute), 39
type_condition (graphql.language.InlineFragmentNode attribute), 40
type_from_ast() (in module graphql.utilities), 86
type_map (graphql.type.GraphQLSchema attribute), 83
TYPE_REMOVED (graphql.utilities.BreakingChangeType attribute), 93
TYPE_REMOVED_FROM_UNION
 (graphql.utilities.BreakingChangeType attribute), 93
type_resolver (graphql.execution.ExecutionContext attribute), 29
TypeDefintionNode (class in graphql.language), 48
TypeExtensionNode (class in graphql.language), 48
TypeInfo (class in graphql.utilities), 88
TypeInfoVisitor (class in graphql.utilities), 89
TypeKind (class in graphql.type), 79
TypeMetaFieldDef (in module graphql.type), 80
typename (graphql.pyutils.Path attribute), 61
TypeNameMetaFieldDef (in module graphql.type), 80
TypeNode (class in graphql.language), 48
types (graphql.language.UnionTypeDefinitionNode attribute), 49
types (graphql.language.UnionTypeExtensionNode attribute), 50
types (graphql.type.GraphQLUnionType property), 71
TypeSystemDefinitionNode (class in graphql.language), 49
TypeSystemExtensionNode (in module graphql.language), 49

U
Undefined (in module graphql.pyutils), 62
UNION (graphql.language.DirectiveLocation attribute), 51
UNION (graphql.type.TypeKind attribute), 80
UnionTypeDefinitionNode (class in graphql.language), 49
UnionTypeExtensionNode (class in graphql.language), 49
UniqueArgumentDefinitionNamesRule (class in graphql.validation), 121
UniqueArgumentNamesRule (class in graphql.validation), 110
UniqueDirectiveNamesRule (class in graphql.validation), 122
UniqueDirectivesPerLocationRule (class in graphql.validation), 111
UniqueEnumValueNamesRule (class in graphql.validation), 119
UniqueFieldDefinitionNamesRule (class in graphql.validation), 120
UniqueFragmentNamesRule (class in graphql.validation), 112
UniqueInputFieldNamesRule (class in graphql.validation), 112
UniqueOperationNamesRule (class in graphql.validation), 113
UniqueOperationTypesRule (class in graphql.validation), 117
UniqueTypeNamesRule (class in graphql.validation), 118
UniqueVariableNamesRule (class in graphql.validation), 114
unregister_description() (in module graphql.pyutils), 60

V
validate() (in module graphql.validation), 94
validate_schema() (in module graphql.type), 83
validation_errors (graphql.type.GraphQLSchema property), 83
ValidationContext (class in graphql.validation), 97
ValidationRule (class in graphql.validation), 98
value (graphql.language.ArgumentNode attribute), 33
value (graphql.language.BooleanValueNode attribute), 33
value (graphql.language.ConstArgumentNode attribute), 33
value (graphql.language.ConstObjectFieldNode attribute), 34
value (graphql.language.EnumValueNode attribute), 37

value (*graphql.language.FloatValueNode* attribute), 39
value (*graphql.language.IntValueNode* attribute), 41
value (*graphql.language.NameNode* attribute), 43
value (*graphql.language.ObjectFieldNode* attribute), 44
value (*graphql.language.StringValueNode* attribute), 48
value (*graphql.language.Token* attribute), 54
value (*graphql.type.GraphQLEnumValue* attribute), 74
VALUE_ADDED_TO_ENUM
 (*graphql.utilities.DangerousChangeType*
 attribute), 94
value_from_ast() (*in module graphql.utilities*), 86
value_from_ast_untyped() (*in module*
 graphql.utilities), 87
VALUE_REMOVED_FROM_ENUM
 (*graphql.utilities.BreakingChangeType* at-
 tribute), 93
ValueNode (*class in graphql.language*), 50
values (*graphql.language.ConstListValueNode* at-
 tribute), 34
values (*graphql.language.EnumTypeDefinitionNode* at-
 tribute), 36
values (*graphql.language.EnumTypeExtensionNode* at-
 tribute), 36
values (*graphql.language.ListValueNode* attribute), 42
values (*graphql.type.GraphQLEnumType* attribute), 65
ValuesOfCorrectTypeRule (*class in*
 graphql.validation), 114
variable (*graphql.language.VariableDefinitionNode* at-
 tribute), 50
VARIABLE_DEFINITION
 (*graphql.language.DirectiveLocation* at-
 tribute), 51
variable_definitions
 (*graphql.language.ExecutableDefinitionNode*
 attribute), 37
variable_definitions
 (*graphql.language.FragmentDefinitionNode*
 attribute), 39
variable_definitions
 (*graphql.language.OperationDefinitionNode*
 attribute), 45
variable_values (*graphql.execution.ExecutionContext*
 attribute), 29
variable_values (*graphql.type.GraphQLResolveInfo*
 attribute), 78
VariableDefinitionNode (*class in graphql.language*),
 50
VariableNode (*class in graphql.language*), 50
VariablesAreInputTypesRule (*class in*
 graphql.validation), 115
VariablesInAllowedPositionRule (*class in*
 graphql.validation), 116
visit() (*in module graphql.language*), 57
Visitor (*class in graphql.language*), 57

W

with_traceback() (*graphql.error.GraphQLError*
 method), 22
with_traceback() (*graphql.error.GraphQLSyntaxError*
 method), 23